South Dakota State University

Open PRAIRIE: Open Public Research Access Institutional Repository and Information Exchange

Electronic Theses and Dissertations

1983

Optimum Irrigation Loading Rates of Highly Saline Wastewater on a Montmorillonitic Soil

John H. Bischoff

Follow this and additional works at: https://openprairie.sdstate.edu/etd

Recommended Citation

Bischoff, John H., "Optimum Irrigation Loading Rates of Highly Saline Wastewater on a Montmorillonitic Soil" (1983). *Electronic Theses and Dissertations*. 4324. https://openprairie.sdstate.edu/etd/4324

This Thesis - Open Access is brought to you for free and open access by Open PRAIRIE: Open Public Research Access Institutional Repository and Information Exchange. It has been accepted for inclusion in Electronic Theses and Dissertations by an authorized administrator of Open PRAIRIE: Open Public Research Access Institutional Repository and Information Exchange. For more information, please contact michael.biondo@sdstate.edu.

OPTIMUM IRRIGATION LOADING RATES OF HIGHLY SALINE WASTEWATER ON A MONTMORILLONITIC SOIL

bу

John H. Bischoff

A thesis submitted
in partial fulfillment of the requirements for the
degree Master of Science, Major in Agricultural Engineering
South Dakota State University

ABSTRACT

Annual applications of 125, 90, and 50 cm of secondary-treated municipal effluent were applied to a 0.76 cm/hr glaciated soil growing alfalfa for 3 years. All treatments had weekly applications with the depth of application varying from 1.5-3.2 cm for the low rate plot to 3.8-8 cm for the high plot. The amounts applied paralleled the evapotranspiration curve of the crop with weekly applications lowest in the spring and fall and highest during the summer. Water quality varied from 1500-3000 μ Siemens/cm for the electrolyte concentration, from 5-11 for the sodium adsorption ratio, and from 0.1-12.4 ppm for nitrate nitrogen.

A water table developed within 1.2 meters of the surface for the 90 cm plot (treatment 35G) and within 1.1 meters of the surface on the 125 cm plot (treatment 50) at the end of the second irrigation season. Treatment 50 had lost 1-2% of the plant population at the end of the second year and 15-20% by the end of the third year of irrigating. Leaching fractions of 0.08-0.10 for total moisture should not be exceeded to prevent water table problems from developing near the surface.

Annual soil applications of gypsum were added to the 90 cm plot (treatment 35G) to determine the efficiency in removing exchangeable sodium from the soil colloid exchange sites. After two annual applications of powdered gypsum, no significant difference between the gypsum plot (treatment 35G) and the non-gypsum plot (treatment 35) was detected in the top 1.2 meters. However, the sodium level for 35G in observation wells at the center of the plot were 2-5 times higher than the

non-gypsum plot (35) with the same annual rate of effluent. Sulphate levels were 4-8 times higher on 35G versus 35 and magnesium was 4 times higher. Calcium was replacing magnesium and sodium on the exchange complex at depths below 1.2 meters.

Nitrate levels in the soil varied according to the nitrate levels in the effluent. In situ soil water extracts were monitored with depth and time across treatments. There was no difference in the nitrate levels in the soil according to treatment. Nitrate nitrogen levels were the highest in the ground waters beneath the plot with the thickest sand layer in the subsoil.

Soil dispersion caused by sodic irrigation water for the top 3 cm of soil was evident at the end of the three-year project on the 50 cm annual application plot (treatment 20). Concentrating effects of ET and low leaching caused high sodium adsorption ratios of the soil solution (SAR_{SS}) during the irrigation season on treatment 20. Treatments 50, 35, and 35G did not show signs of soil dispersion on the top 3 cm.

OPTIMUM IRRIGATION LOADING RATES OF HIGHLY SALINE WASTEWATER ON A MONTMORILLONITIC SOIL

This thesis is approved as a creditable and independent investigation by a candidate for the degree, Master of Science, and is acceptable for meeting the thesis requirements for this degree. Acceptance of this thesis does not imply that the conclusions reached by the candidate are necessarily the conclusions of the major department.

Dr. L. O. Fine Thesis Advisor Date

Mr. M. A. Hellickson Head, Major Department Daye

иг. и. w. µевоег Major advisor / Date

ACKNOWLEDGEMENTS

I would like to dedicate this to my family, Marilynn, Travis, Jill, and Joni. This is just a token of my appreciation for the self-sacrifices and added responsibilities you all have made during the course of this graduate work. Especially to you, Marilynn, I take this opportunity to thank you for all the late nights you spent alone, for all the support you provided for the children and me, and for the added responsibilities you took on in my absence. Yes, now that vanity in the bathroom will be built!

I, also, would like to thank Dr. L. O. Fine, Dr. C. G. Carlson, Dr. J. L. Wiersma, Dr. D. W. DeBoer, Alan Bender and countless other university staff for their guidance, support, and time which they committed to me for my educational benefit. Really, you have been wonderful to work with and I very much appreciate your dedication to help others develop their personal goals.

To all the students who helped move the irrigation pipe, dry, and weigh alfalfa, shovel gypsum (some of the professors got in on that, too!), and who waded up to their waist in "waste", I truly appreciate your commitment to hang on to your job! Without your assistance, Owen, Larry, Todd, Paul, Allen, this would have been much easier! Thanks, Sher, Kent, and Lisa for your adept skills on the HP computer. I can go on and on with the list of friends of whom I appreciate for their support and belief. Thanks, Cheryl, for being there when I expected this thesis to be typed.

I wish to thank, also, the Office of Water Research and Technology, now the Office of Water Policy, under the U.S. Department of the Interior, for making grant money available for this research.

JHB

TABLE OF CONTENTS

														Page
ACKNOWLEDGEMENTS														111
LIST OF TABLES				. :		•					•	•	•	vi
LIST OF FIGURES					•	•		•	•		•	•	•	vii
INTRODUCTION		•			•	•		•	•	•	•	•	•	1
LITERATURE REVIEW AND OBJECT	EVES .	•			•	•		•	•	•	•	•	•	4
MATERIALS AND METHODS														7
Experimental Procedure a	and Si	te (Chai	ract	er	ist	ics							7
Wastewater Characterist														18
Agronomic Information .														19
Soil Amendment Rates .														24
RESULTS AND DISCUSSION														37
Forage Yields														37
Effects of Gypsum Amenda														40
														53
Saturated Hydraulic Cond	ductiv	ıty	•	•	• •	•		•	•	•	•	•	•	
Drainage Water Quality		•	• •	•	• •	•		•	•	•	•	•	•	61
Drainage Water Quantity	• • •	•	• •	•	• •	•	• •	•	•	٠	٠	•	•	75
SUMMARY AND CONCLUSIONS						•		•	•		•	•	•	83
REFERENCES		•				•			•	•	•	•	•	86
APPENDIXES													•	88
A. Laboratory-determine extracts 1980		•				•		•	•	•	•	•	•	89
B. Laboratory-determine extracts 1981		•		•		•		•	•	•	•	•	•	101
C. Laboratory-determin extracts 1982														118
D. Soil chemical chara treatments, depth,										-				130
E. James River water q	uality	da	ta	198	0-1	982	2 .							149
F. Secondary-treated m	unicip	al	eff	lue	nt	wat	er	qu	a1	it	y			
data at Huron 1980-													•	151
G. Plot observation we													•	154
H. Dry matter alfalfa														
year, and cutting 1	980-19	82		•		•		•	•	•	•	•	•	157
I. Rainfall and irriga	tion f	req	uen	су	and	an	noun	its	,	Hu	ro	n,		
S.D. 1980-1982														161

LIST OF TABLES

<u>Table</u>		Page
1	Clay mineralogy of a $0-30~\mathrm{cm}$ soil sample (Houdek loam)	10
2	Soil mechanical analysis of a 0-30 cm (Houdek loam)	10
3	Terminal average bulk densities of treatments	11
4	Analysis of variance of bulk densities of a 0-3 cm depth using Dunnett's test	11
5	Treatments, annual effluent rates, and soil amendments for the project	12
6	Huron effluent organic and inorganic chemical levels as compared to EPA maximum contaminant levels (1980)	23
7	Agronomic crop information 1980-1982	26
8	Treatment 35G calcium requirements (1980) needed to maintain an SAR_{iw} of 3 or 5	28
9	Treatment 35G calcium requirements (1981) needed to maintain an SAR_{iw} of 3 of 5	29
10	Treatment 35G calcium requirements (1982) needed to maintain an SAR_{iw} of 3 or 5	30
11	Treatment 20 calcium requirements needed to maintain an $SAR_{\mbox{iw}}$ at 3 or 5	32
12	Moisture and yield data of alfalfa plots 1980-1982	38
13	Single-degree-freedom partitions of treatment sum of squares for alfalfa yields (kg/ha)	39
14	Chemical soil analysis 1980-1982 (average of 2-3 sites)	48
15	Solubilities of CaCO3 at various pH's	51
16	Replications of saturated hydraulic conductivity measurements for the top 3 cm of soil for the various treatments	55
17	Analysis of variance for laboratory $K(\theta_{\mathbf{S}})$ measurements of the top 3 cm of soil	56
18	Dunnett's test of check mean vs treatment means for $K(\theta_S)$	5

LIST OF FIGURES

Figure		Page
1	Plot layout with contours and irrigation regime	8
2	Observation well boring logs of the various treatments	9
3	Water level recording device mounted over an observation well	15
4	A station of suction tensiometers and evacuated jugs at each plot	16
5	Right and wrong way to build a suction tensiometer for obtaining soil water extracts	17
6	Huron's secondary effluent water quality (EC, Na, SAR, adj. SAR)	20
7	Huron's secondary effluent water quality (TKN, NO ₃ , C1, alk(MO))	21
8	Huron's secondary effluent water quality (Ca, Mg, SO ₄ , alk(P))	22
9	Experimental plot irrigation system on 35G with new seeding of Agate alfalfa June 1980	25
10	Representation of the design of acrylic Tempe cell used to hold undisturbed soil cores for saturated hydraulic conductivity measurements	34
11	Schematic representation of the design used in measuring saturated hydraulic conductivities	. 35
12	Depiction of the alfalfa population reduction at the low end of treatment 50 August 1982	. 41
13	Treatment 35G plot before harvest 1982 showing yel- lowing of alfalfa because of excess water	. 42
14	Soluble sodium levels with time and depth from plot 35G, 1981	. 43
15	Soluble sodium levels with time and depth from plot 50, 1981	. 45
16	Soluble sodium field extracts by depth from plot 50,	

Figure		Pa	ige
17	Graphical depiction of the change of $K(\boldsymbol{\Theta}_S)$ with increasing pressure heads on two treatments	5	8
18	Changes in observation well water quality (EC, Na, C1, NO ₃) with time for plot 50 \dots	6	3
19	Changes in observation well water quality (EC, Na, C1, NO3) with time for plot 35G	6	54
20	Changes in observation well water quality (EC, Na, Cl, NO ₃) with time for plot 35 · · · · · · · · · · · · · · · · · ·	6	55
21	Changes in observation well water quality (EC, Na, Cl, NO ₃) with time for plot 20	6	66
22	Nitrate levels at various times and depths in the soil solution from plot 50, 1981	e	57
23	Effect of a heavy rainfall on the salinity in the soil profile for plot 50, 1981	6	69
24	EC values in the soil with time and depth on plot 35G, 1981	7	71
25	Changes in pH in the soil with depth and time for plot 50, 1981	7	73
26	Changes in pH in the soil with depth and time for plot 50, 1982		74
27	Bicarbonate ion concentration in the soil with depth and time in plot 50, 1982	. :	76
28	Cumulative precipitation departures from the normal 30 year average of 40.6 cm (16 in) for Huron, S.D. 1980-1982		78
29	Water table levels obtained from observation wells for 1981 for the various treatments		79

INTRODUCTION

Municipal wastewater disposal has been a concern and a problem for mankind since community sewage systems were first developed. Surface waters were extremely convenient for disposing of raw wastes because of their ability "to dilute" the pollutants to make them less hazardous. Eventually, however, as the pollutant volumes exceeded the dilution volumes the water quality deteriorated rapidly. Thus, came the need for treatment of wastes to prevent point-source pollution of streams and lakes.

Sanitary engineers have been familiar with land treatment of wastes for centuries. Ancient Greek and European "sewage farms" have been reported as very successful and still in existence today (1). As modern technology developed methods of wastewater treatment which met the discharge requirements of the times, and public acceptance of "sewage farming" dwindled, the soil, as a means of wastewater treatment, became a minority alternative among engineering consulting firms.

It wasn't until 1972, when more stringent regulations formulated from the Federal Water Pollution Control Act Amendments (Public law 92-500) were finalized, that land application regained popularity due to economic considerations for smaller communities. Amid the regulations a statement that said any community who chose land application as a cost-effective viable alternative for wastewater treatment and disposal was eligible for 75% of the cost of that system paid for by federal funds. In South Dakota, 175 communities utilize lagoons for wastewater treatment and stabilization (2). Of those 175 communities, approximately 50

are considered suitable for irrigation based on an empirical formula developed from one season's sampling (2). Approximately 45 of the communities had water quality in the range of 2000-3500 μ S/cm and/or SAR's in the range of 5-10 which classified them as marginally suitable for irrigation. These marginally suited lagoons amount to approximately 400 hectares serving 50,000 people. Because most of those communities are small, tertiary treatment facility costs loom like an ominous black cloud. Consequently, land application systems may provide an alternative for wastewater disposal not only for cost-effective treatment but also as a resource for increased agricultural crop production.

If irrigation is a possible alternative for wastewater disposal, one of the main considerations is to minimize capital and annual costs which include land, water spreading equipment, maintenance, and energy. Therefore, the objective is to provide a maximum amount of water on a minimum amount of land area while maintaining a productive agronomic resource. This is especially important where soils which have adequate internal drainage are scarce. This type of management is contrary to conventional irrigation practices. Little information is available in regard to high hydraulic loading rates on fine-textured glaciated soils for this particular application.

In addition to the hydraulic loading aspect, many lagoons are poor in terms of water quality for conventional irrigation because of the high sodium content contributed by water softening brine, street runoff, and human wastes. When sodic waters are applied to montmorillonitic soils, studies have demonstrated that the saturated hydraulic conductivity decreases with decreasing electrolyte concentrations

for a given SAR of the applied water (4,5,6). It is a well-established fact that soil salinity, and, to some extent, sodicity can be reduced by increased leaching fractions if the soil will accept the increased hydraulic load (3). Usually, calcium and magnesium are accordingly high when the sodium level is high for many irrigation wells in South Dakota. However, this may not be so in the case of many municipal effluents because of the additional sodium added for water softening. Consequently, the potential for using these effluents for irrigation may be feasible only if applications of soil amendments are made either in the irrigation water or on the soil to maintain soil permeabilities. Nevertheless, the added costs of these amendments and the limitation to moderately salt tolerant to salt tolerant crops may prove to be less costly than a tertiary treatment facility. High level soil-crop management and monitoring would have to be included for such a system to be feasible, however.

LITERATURE REVIEW AND OBJECTIVES

The University of Minnesota and Agricultural Research Service did extensive studies using wastewaters for irrigation at Apple Valley 1972 through 1977 (7, 8, 9, 10). Their main concerns dealt with nitrogen removals and differences in crop yields and persistence of forage crops with different cutting regimes. They worked with a constant weekly application (5, 10, and 13 cm/wk) from April through October with annual amounts of 137 and 240 cm on forage and 109 and 197 cm on corn. They also were working on a well-drained silt loam soil with gravel outwash at 60 cm with a water table at approximately 150 cm. The secondary treated effluent had an average EC of 1695 μ S/cm and an SAR of 5.7. They concluded that most nitrogen removal was by crop uptake and that forage removed considerably more than corn.

Karlen, et al. (11) used simulated municipal effluent of annual hydraulic loading rates of 25, 50, 100, and 200 cm on corn to determine optimum yields and hydraulic loading rates on a tiled, loamy, calcareous till. The application rate was .78 cm/hr, but the water quality was excellent in terms of lagoon effluent (EC \approx 1800 μ S/cm, SAR=2-3). They concluded that tile drained Conover loam should not receive over 100 cm annual loading to derive beneficial nutrient uptake by plants.

Adriano et al. (12) evaluated the long term renovating capacities of land treatment systems under sprinkler irrigation and looked at the soil profile distributions of N, PO4, and organic C. They looked at average daily applications of 5 and 10 cm on sand and loamy sands with gravel outwash subsoil. Again, the wastewater quality used of 1350 μ S/cm

total salinity and an SAR of 4.3 is considered good in a semi-arid climate.

Bole and Bell (13) worked with yield differences and chemical composition of forage crops with lagooned municipal wastewater on a loamy sand with an infiltration rate of 15 cm/hr. Application rates were 1.7 and 3.4 cm/hr with annual loading rates of 50 through 150 cm.

Ellis et al. (14) concluded that applying more than 88 to 100 cm of annual effluent to a .5 cm/hr loam would hydraulically overload the soil, causing the biosystem to lose its renovation capacity.

Our approach was to work with weekly applications which paralleled the ET curve of alfalfa over the season and to allow for some relief after a substantial rain. A moisture tolerant alfalfa was selected as the forage because of its agronomic value and its ability to use high amounts of N and water. A water quality of 2000 to 3000 µS/cm and an SAR of 7-9 was desired to test the marginally suited lagoon waters. A soil type was selected which represented an extensive soil series throughout eastern South Dakota which was classified in the 0.75 cm/hr intake family by the Soil Conservation Service. The site selection was based not only on water quality and soil parameters but also on the fact that the city of 15,000 was looking for possible alternatives to effluent disposal in the James River. Therefore, this three-year study was undertaken to explore the possibility of using marginally suited lagoon effluents for irrigation and feasible forage crop production in a semi-arid climate on marginally suited soils. The main objectives were:

(1) to determine the annual rate of hydraulic loading for a relatively fine textured montmorillonitic soil that will allow

- sustained crop production, maintain acceptable soil structural and chemical characteristics, while providing for a cost-effective municipal waste disposal system;
- (2) to determine the quantity and quality of the drainage water passing below the root zone under different hydraulic loading rates;
- (3) to determine the effect of gypsum amendments upon soil exchangeable sodium percentages and physical characteristics, and crop production.


MATERIALS AND METHODS

Experimental Procedure and Site Characteristics

The study was conducted on a Houdek loam (subgroup=Typic Argiustoll; family=fine-loamy; mixed, mesic) located adjacent to the city of Huron's 130 ha stabilization ponds. The soil which developed from loamy, calcareous till is nearly level with slopes from 0-2% (Figure 1), has slow surface run-off, has moderate permeability for the solum for moderately slow permeability for the underlying till, and received approximately 45-52 cm (17-20 inches) of annual precipitation. The soil below 30 cm is mostly clay loam and, occasionally, silt loam; however, boring logs of the observation wells show scattering of sand lenses at various depths and sites (Figure 2). Clay mineralogy and bulk density are quite significant in determining hydraulic conductivities of soils. Tables 1 and 2 show the clay mineralogy and texture of a 0-30 cm composite sample. There were only small amounts of montmorillonite and mica and traces of kaolinite detected by X-ray diffraction. This indicates that probably some of the clay is amorphous and/or poor crystalline structure which caused low relative amounts in the diffraction analysis. Table 3 lists the average bulk densities of the different treatments. They range from a low of 1.34 to 1.61 with an average bulk density of 1.47. Table 4 shows the analysis of variance of the bulk densities compared to the check. bulk density for treatments 50, 35, and 20G are significantly higher than the check at the .05 level. The bulk density for treatment 35 is significantly different at the .01 level.

Approximately 1/3 hectare plots were established with three basic annual effluent loading rates of 125, 90 and 50 cm, hereafter designated

LAYOUT OF ALFALFA PLOTS



-2- ELEVATION CONTOURS METERS ABOVE B.M.

Figure 1. Plot set-up for alfalfa with a portion of the full and half-circle sprinklers represented showing overlap.

Boring Logs of Observation Wells 10/30/80




Figure 2. Observation well boring logs for the different treatments. Depths are in meters.

Table 1. Clay mineralogy of the 30 cm depth sample (courtesy of Midwest Technical Service Center, Soil Conservation Service, U.S. Dept. of Agriculture, Lincoln, Nebraska).

Soil	Clay	mir	er	alog	зу
Houdek	MT2	MI	2	KK	1

MT--montmorillonite

MI--mica

KK--kaolinite

Relative amount: 2--small, 1--trace

Table 2. Soil mechanical analysis of a sample taken from the top 30 cm.

					Total	
<u>Order</u>	Subgroup	Series	Depth	Clay <.002mm	Silt .00205mm	Sand . 05-2mm
Mollisol	Typic argiustoll	Houdek loam	0-30cm	22.1%	32.9%	45.0%

Clay	S1	.1t
Fine clay	Fine silt	Coarse silt
<.0002mm	.00202	.0205
14.2%	17.9%	15.0%

		Sand		
Very fine	Fine .1025mm	Med1um .2550mm		Very coarse 1-2mm
3.8%	12.3%	18.9%	9.1%	0.9%

Table	3.	Terminal	average	bu1k	densities	οf	treatments.
-------	----	----------	---------	------	-----------	----	-------------

Depth (cm)	50	35G	35	20	20G	Check
0-3	1.39	1.39	1.53	1.34	1.53	1.25
15-30		1.42		1.46		
30-45		1.47		1.45		
45-60		1.49		1.45		
60-75		1.46		1.46		
75-90		1.61		1.40		
90-105		1.56		1.41		
105-120		1.56		1.47		
120-135		1.60		1.51		
135-150		1.53		1.56		

Table 4. Analysis of variance of bulk densities between treatments for the 0-3 cm using Dunnett's test.

Check vs	50	2.71	*
Check vs	35G	2.61	
Check vs	35	5.41	**
Check vs	20	1.03	
Check vs	20G	3.17	*

Critical value of d.05 (5,33) >2.65; d.01 (5,33) >3.31. *Significant at the .05 level. **Significant at the .01 level.

as treatment 50, 35, and 20, respectively (Table 5). Another plot (35G) was established identical to the 90 cm plot with the only difference being the annual application of gypsum.

Table 5. Treatments, annual effluent rates and soil amendments for the project.

		Annual amendment rates
	Annual effluent	CaSO4 • 2H2O
Treatment #	cm (in.)	kg/ha (tons/acre)
		<u>1980</u> <u>1981</u> <u>1982</u>
50	127 (50)	
35	90 (35)	
35G	90 (35)	2422 3660
		(1.17) (1.63)
20	50 (20)	
20G	50 (20)	9000
('82 only)	•	(4.0)
Check	0 (0)	•

In 1982, treatment 20 was split in half with the east half receiving 9000 kg/ha of gypsum in the spring. This was a test to see if a heavy, unincorporated one-time application of gypsum would cause any significant change in the ESP levels at the end of the irrigation season.

The four plots were then irrigated with unchlorinated secondary treated wastewater from the last stage of stabilization ponds. The water was applied to all plots at 1.0 cm/hr with a solid set impulse sprinkler system (Figure 1). The water was pumped from the last stage of the 130 ha stabilization ponds to the plots approximately .8 km (.5 mile) away. A 22 kw (30 hp) electric motor and centrifugal pump was used to deliver approximately 454 liters/min (120 gpm) per plot at 380 KPascals (55 psi). The nozzle size was 4.36 mm (11/64 inch) diameter which delivered approximately 23.8 liters/min (6.3 gpm) for the full circles and 3.175 mm (1/8 inch) diameter for the part circles

delivering 12.9 liters/min (3.4 gpm). The <u>frequency</u> of application was the same for all plots, usually weekly; however the <u>depth</u> of application varied among plots according to the ratio among the different annual loading rates. All plots then received a specific amount at each irrigation (Appendix I lists the rainfall and irrigation amounts for the project treatments by year). A water meter was used to determine the amount for each plot assuming average irrigation efficiencies of .8. The water was applied parallel to the ET curve of the alfalfa crop, with consideration given to recent precipitation patterns. Consequently, weekly applications varied from 1.5 to 3.2 cm on the 20 plot and 3.8 to 8 cm on the 50 plot.

Because of the lack of penetration of water into the root zone on the 20 plot from the shallow frequent applications of water during 1981, water was applied every third week with the application depth three times as great for 1982. This assured better distribution of water and salts throughout the root zone.

Neutron probe access tubes were installed to 1.7 m at the center of each plot to monitor changes in soil moisture. A neutron radiating moisture meter was used to determine volumetric moisture contents at different levels. Readings were taken before each irrigation to determine the soil's capacity to accept more water.

Ten cm diameter observation wells were installed ath the center of each plot (Figure 1) for the purpose of monitoring groundwater levels and quality. Medium sand was packed around the casing with bentonite grouted near the surface to guard against short-circuiting. Water level recording meters were housed and situated over the wells with floats

inside the well casing (Figure 3). Water quality samples were taken approximately once a month and analyzed for EC, Na, NO3, HCO3, pH, Cl, and NH3.

Soil samples were taken initially before irrigation started to a depth of 120 cm and every year thereafter at the end of the irrigation season. Four to six sub-samples were composited from each site/depth at 30 cm intervals with 3 sites per treatment. The soils were air dried, ground and sieved and checked for exchangeable Na, Ca, and Mg, EC of the saturation extract, cation exchange capacity (CEC), SAR of soil solution, and pH, using the methods described in U.S. Agricultural Handbook 60 (15). At the end of 1981, the exchangeable sodium percentage (ESP) on treatment 20 was reported higher than expected. Therefore, the top 30 cm was sampled at 6 additional sites per treatment in the spring of 1982 to check this and to see if changes occur over the winter. In total, five sampling periods were made: spring 1980, fall 1980, fall 1981, spring 1982, and fall 1982.

Suction tensiometers were also installed near the center of each plot to a depth of 150 cm (~5 ft) at 30 cm (1 ft) intervals for the purpose of evaluating the leaching water with depth under different loading rates (Figure 4). Each tensiometer was equipped with a small nylon tube which led to a 4 liter glass jug which was evacuated weekly prior to an irrigation. Any moisture in the soil held at less than .67-.80 bar could then move into the ceramic cup at the bottom of the tensiometer. At this point, one important aspect of suction tensiometer construction should be mentioned. Figure 5 shows a simplified version of the correct way and the wrong way to build a




Figure 3. A strip chart recorder logging water fluctuations with time from observation wells near the center of each plot.



Figure 4. A station of suction tensiometers and evacuated jugs at each plot. $\$




Figure 5. Correct and incorrect way to install the extraction tubing when building a suction tensiometer.

suction tensiometer for the purpose of extracting soil water.

During an irrigation or a rainfall, a downward moving wetting front exists from the beginning of the event when the soil surface usually is near saturation until equilibrium soil tension is reached at a particular depth long after the event has stopped. The rate of movement and the depth of penetration of the water is dependent upon many things such as texture, structure, bulk density, organic matter content, and exchangeable sodium percentage. By using the tensionmeter on the left in Figure 5 during a wetting event water could conceivably move into the ceramic cup with the water level increasing to the point of touching the end of the nylon tube and then move back into the soil through the cup as the soil matrix potential increases during evapotranspiration. While the water level inside the tensiometer is rising, the potential inside the tube is decreasing thereby reducing the pulling

power on the soil across the ceramic tip. Consequently, no water is obtained in the jug. However, if the small nylon "sphaghetti" tube were placed to the bottom of the ceramic cup, any water which was pulled into the cup would begin to move immediately to the jug. The two limiting factors for obtaining a water sample under these conditions would be (1) the extent of tension exerted on the tensiometer without pulling in air through the cup and, (2) the depth of the tip relative to the top of the jug.

Because of the configuration used at the left in Figure 5, in situ soil extracts from plot 20 were not obtained simply because of the lower moisture contents and higher soil matrix potentials moving the water out of the tube before it went into the jug. Samples taken on plot 35, 35G, and 50 may have had some diluting occurring from sampling to sampling thereby causing some delay in response to a particularly significant event, however, it did not appear to be a significant problem. Sufficient samples were consistently collected from the other plots. The samples which were collected were collected prior to an irrigation and analyzed in the laboratory for EC, C1, NO3, Na, total PO4, pH, HCO3 and NH3.

Wastewater Characteristics

The city of Huron derives its water from the James River.

Appendix E shows the James River water quality taken below the dam for the time period of 1980-1982. The water quality fluctuates with precipitation cycles which occur 100-500 km north. The city does partial softening of the water with the addition of unslaked lime (CaO) necessary for the removal of iron and manganese. This contributes to the sodium

hazard associated with applying the water to the soil by reducing the concentration of divalent cations thus increasing the SAR. The specific conductance (EC) of the water varied from 1500 to 3000 µS/cm as a dry year (1981) followed a normal year and the sodium adsorption ratio (SAR) varied from 5.0 to 11.5. Appendix F shows the numerical values of the various parameters tested in the effluent. Total Kjeldahl nitrogen (TKN) values were 20-24 ppm in the spring dropping to 3-6 ppm in the summer and fall. The nitrate levels peaked out at 3-4.5 ppm about July 1 as the organic and ammonium nitrogen were broken down and volatilized by rising temperatures and increased biological activity. Figures 6, 7 and 8 graphically show the fluctuations with time of the various water quality parameters of EC, Na, sodium adsorption ratio (SAR), adjusted SAR (adjusts for the precipitation of CaCO3), TKN (total Kjeldahl nitrogen), NO3, Cl, alkalinity (MO), alkalinity (P), Ca, Mg, and SO4.

Organic and inorganic chemicals were looked at the first year to determine the levels in the lagoon and, if any were found to be high, they would be looked at in the ground water beneath the plots. Table 6 lists the constituents in the water on August 14, 1980. They all were below the maximum EPA contaminant levels for ground water. Because of the high cost involved for analysis of these constituents and the low levels found, it was decided not to look at that aspect of the study.

Agronomic Information

Before the experiment began, the site had a 6-year old established sparse stand of alfalfa. Twenty cm (8 in) of water was applied to all

HURON EFFLUENT WATER QUALITY

—— 1980 ····· 1981 **~~~** 1982




Figure 6. Huron's secondary effluent water quality 1980-1982.

HURON EFFLUENT WATER QUALITY

____ 1980 ····· 1981 --- 1982




Figure 7. Huron's secondary effluent water quality 1980-1982.

HURON EFFLUENT WATER QUALITY

<u> 1980 ····· 1981 --- 1982</u>




Figure 8. Huron's secondary effluent water quality 1980-1982.

Table 6. Huron effluent organic and inorganic chemical levels as compared to EPA maximum contaminant levels 1980.

EPA MAXIMUM CONTAMINANT LEVELS FOR ORGANIC CHEMICALS FOR GROUNDWATER

	MAXIMUM LIMITS	Huron effluent values (8/14/80)
Endrin	.0002 PPM	<.0001*
LINDANE	.004 PPM	<.00002*
METHOXYCHLOR	.1 PPM	<.0005*
Toxaphene	.005 PPM	· <.001*
2,4-D	.1 PPM	<.1
SILVEX	.01 PPM	<.01

^{*}MINIMUM DETECTABLE LIMIT

EPA MAXIMUM CONTAMINANT LEVELS FOR INORGANIC CHEMICALS FOR GROUNDWATER

		HURON EFFLUENT
	MAXIMUM LIMITS	YALUES (8/14/80)
ARSENIC	50 РРВ	13
BARIUM	1000 РРВ	92
CADMIUM	10 PPB	< 0.1
CHROMIUM	50 PPB	21
LEAD	50 PPB	< 1
MERCURY	2 PPB	< 0.5
SELENIUM	10 РРВ	2
SILVER	50 PPB	< 1
IRON		10
NITRATE (N)	10 PPM	0.02

plots the first two days. This was done to bring the extremely dry soil to normal moisture levels and to possibly stimulate growth of dormant plants. The stand remained unacceptable so after the first harvest a more moisture tolerant variety of alfalfa (Agate) was seeded and quickly established. Irrigations were applied at equal depths across treatments to establish an even stand (Figure 9). Four cuttings were approximately 5 weeks apart with only 3 cuttings in 1981 due to the seeding setback. Table 7 lists the seeding and harvest dates, fertilizers, insecticide, and herbicide for the entire project. A 10-12.5 cm (4-5 in) stubble was left after harvest and a 6.1 meter (20 ft) row sample was weighed and tested for moisture content. Three sites were selected at each harvest on each plot for yield determinations. Soil fertility samples were taken in the fall of 1981 because of increased lodging of plants on the fourth cutting. One hundred fifteen kg/ha of 0-46-0 was recommended and applied in the spring of 1982.

Soil Amendment Rates

Near the end of the 1980 irrigation season, bagged powdered gypsum was obtained from Iowa and applied to the 35G plot. An estimate had to be made of the application rate since soil samples were to be taken after the last irrigation. Therefore, the water analysis and depth of application at each irrigation were used to total up the weight of calcium needed to maintain an SARiw of less than 5 throughout the season. If the ESP (exchangeable sodium percentage) levels equal the SAR of the irrigation water (SARiw) near the soil surface when the soil solution is in equilibrium with exchangeable cations, then an SAR, or ESP, of 5 should be an acceptable level to allow in the soil without causing



Figure 9. The experimental plot irrigation system on 35G with new seeding of alfalfa June 1980.

Table 7. Agronomic crop information, 1980-1982.

	Variety	Seeding date	Harvest dates (11 cm stubble)	Commercial fertilization	Insecticide	<u>Herbicide</u>
1980	Agate	June 11, '80	June 2 July 16 Aug. 28			6/10/80 Eptam(6E) (4.5 1/ha)
1981			May 26 July 1 July 27 Sept. 3		Furadan 4F (1.17 1/ha)	
1982			June 2 July 8 Aug. 5 Sept. 20	6/8/82 0-46-0 (20 kg/ha)		

any deterioration of structure or tilth. However, cation exchange capacity, clay mineralogy, organic matter content, structure and irrigation management all play major roles in mitigating the extent of soil dispersion at various ESP levels.

Tables 8, 9, and 10 show the amount of calcium needed to add to the soil to bring the SAR to either 3 or 5. The seasonal calcium requirement was added to the soil near the end of the irrigation season, however, and was not mixed with the water prior to application. This method was tested to determine if removal of potential exchangeable sodium was feasible and effective under this type of annual hydraulic loading.

Based on the seasonal total of calcium required each year from Table 8, gypsum (CaSO4·2H2O) rates were determined by the following method:

 $\frac{\text{Total kg Ca required}}{1 \text{ season}} \times \frac{\text{CaSO4.2H2O(formula wt)}}{\text{Ca(atomic wt)}} = \frac{\text{Total kg CaSO4.2H2O}}{\text{required}}$

For 1980,

153.7 kg Ca x
$$\frac{172.2 \text{ gms } (\text{CaSO}_4 \cdot 2\text{H}_20)}{40.1 \text{ gms } (\text{Ca})} = 660 \text{ kg CaSO}_4 \cdot 2\text{H}_20$$

Then, assuming a standard "rule of thumb" of 25% loss of calcium in the replacement reaction for exchangeable sodium below 10%, an efficiency factor must be used to calculate the total weight of pure CaSO4·2H₂O needed for sodium removal. Thus,

 $660 \text{ kg } \text{CaSO}_4 \cdot 2\text{H}_2\text{O} \times 1.25 = 825 \text{ kg}$

Approximately 900 kg of pure $CaSO_4 \cdot 2H_2O$ was applied to the plot with a drop fertilizer spreader on September 4th, 1980. A total of six passes were made with three each direction.

In 1981, the water quality worsened and the SAR increased because

Table 8. Treatment $\underline{356}$ calcium requirements (1980) needed to maintain the $\mathrm{SAR_{iw}}$ at 3 or 5 based upon the water analysis and depth of water applied at each irrigation during the season. Total calcium requirements for the season are given at the bottom.

	_		SAR=3		SAR=5					
				kg Ca			kg Ca			
1	Effluent	•	kg Ca	per plot	me/l Ca	kg Ca	per plot			
	Applied	to be	per ha	per	to be	per ha	per			
DATE	(আ)	added	per an	irrig	added	per cm	irrig			
800513	12.70	13.21	26.55	125.28	-0.04	-0.09	-0.40			
800519	9.14	13.21	26.55	90.20	-0.04	-0.09	-0.29			
800528	4.32	16.96	34.08	54.69	0.29	0.53	0.93			
800612	2.72	16.96	34.08	34.42	0.29	0.58	0.58			
800616	2.82	16.96	34.08	35.71	0.29	0.58	0.61			
800620	1.78	16.96	34.03	22.52	0.29	0.58	0.38			
800702	4.57	16.95	34.03	57.91	0.29	0.58	0.98			
800710	3.91	17.19	34.54	50.21	1.31	2.63	3.83			
800722	5.33	16.13	32.43	64.28	1.29	2.59	5.12			
800725	3.66	16.13	32.43	44.08	1.29	2.59	3.51			
800731	4.37	25.70	51.66	83.87	4.17	8.38	13.61			
800305	4.01	25.70	51.66	77.0 5	4.17	8.38	12.50			
800808	3.66	25.70	51.66	70.22	4.17	8.38	11.40			
800813	5.33	27.68	55.64	110.29	4.29	8.61	17.07			
800822	5.69	27.68	55.64	117.64	4.29	8.61	18.21			
800911	5.66	31.54	63.39	133.42	4.86	9.77	20.56			
800916	5.66	31.54	63.39	133.42	4.86	9.77	20.56			
800925	3.71	31.26	62.84	86.59	4.92	9.90	13.64			
800930	2.90	29.26	58.81	63.29	4.09	8.21	8.84			
801007	2.72	21.78	43.78	44.22	1.01	2.02	2.04			
TOTALS	94.67			1499.3			153.7			

Table 9. Treatment 35G calcium requirments (1981) needed to maintain an SAR_{iw} at 3 or 5 based upon the water analysis and depth of water applied at each irrigation during the season. Total calcium requirements are given at the bottom.

			SAR=3		SAR=5				
DATE	Effluent Applied (cm)	me/l Ca to be added	kg Ca per ha per cm	kg Ca per plot per irrig	me/l Ca to be added	kg Ca per ha per cm	kg Ca cer plot per irrig		
810505	5.84	28.41	57.09	123.95	3.40	6.82	14.82		
810513	4.50	28.41	57.09	95.38	3.40	6.82	11.40		
810519	5.87	32.58	65.4 8	142.77	4.87	9.80	21.36		
810601	4.47	36.54	73.44	121.99	6.54	13.15	21.85		
810603	3.86	36.54	73.44	105.36	6.54	13.15	18.87		
810612	1.24	45.62	91.69	42.41	9.60	19.30	8.93		
810619	4.67	66.92	134.52	233.61	17.21	34.60	60.09		
810626	6.78	66.92	134.52	339.00	17.21	34.60	87.19		
810706	5 . 87	62.89	126.41	275.62	16.59	33.34	72.70		
810714	5.59	61.51	123.64	256.74	16.32	32.80	68.11		
810811	5 . 2 8	123.03	247.30	485.51	38.72	77.83	152.80		
810818	5.46	79.54	159.88	324.44	22.65	45.53	92.40		
810826	3.40	79.54	159.88	202.21	22.65	45.53	57.59		
810917	3.66	74.39	149.53	203.24	19.95	40.10	54.50		
810929		74.39	149.53	197.59	19.95	40.10	52.99		
TOTALS	78.11			3402.6			85 9.4		

Table 10. Treatment $\underline{35G}$ calcium requirements (1982) needed to maintain an SAR $_{iw}$ at 3 or 5 based upon the water analysis and depth of water applied at each irrigation during the season. Total calcium requirements are given at the bottom.

			SAR=3		SAR=5					
DATE	Effluent Applied (cm)	to be	per ha		to be	kg Ca per ha per cm				
820608 820617 820624 820630 820707 820713 820723 820727	1.91 2.46 6.38 7 2.64 1.85 0.79 7 2.18 4.14	21.10 12.10 17.57 30.15 30.15 26.57 26.57 23.87	42.40 42.40 24.32 35.32 60.61 60.61 53.40 53.40	50.43 30.02 22.27 83.68 59.50 41.76 15.62 43.34 73.82	2.22 2.22 -2.00 0.23 5.47 5.47 4.73 4.73 2.49	0.46 11.00 11.00 9.50 9.50 5.01	5.30 3.15 -3.68 1.08 10.80 7.58 2.78 7.71 7.71			
820810 820819			46.99 48.92	93.14 96.50	2.90 2.19	5.83 4.41	11.55 8.69			
820825 820903 820909	3.38 3.2.18	23.53 23.53	47.29 47.29 78.44	59.37 38.39 103.65	2.15 2.15 7.21	4.32 4.32 14.49	5.42 3.50			
TOTALS	48.69			870.9			96.2			

of low precipitation amounts during the winter and through the summer. Concentrating effects were evident both in the James River and in the stabilization ponds and the calcium requirements accordingly were increased. Table 9 indicates that 860 kg of calcium was needed to counteract the sodium amounts applied. By going through the same calculations above, a season gypsum requirement for the 35G plot was 4600 kg gypsum, much higher than the first year. This "drought" year was not accounted for in the gypsum supply, consequently only 1360 kg gypsum was applied on September 15, 1982 to that plot.

After soil samples were taken in the fall of 1981, results showed quite high exchangeable sodium levels on treatment 20 for all three sites. Consequently, the 20 plot was split in half with the calcium requirements applied to the east half of the plot. Table 11 shows the total calcium requirements per plot for the total season for each year. The amount of CaSO₄·2H₂O needed is calculated as follows from Table 11:

1980 + 1981 Ca requirements (kg) x
$$\frac{172.2}{40.1}$$
 x 1.25 x $\frac{1}{2}$ (half a plot)

= total kg
$$CaSO_4 \cdot 2H_2O/\frac{1}{2}$$
 plot

Then,

$$(572.6+88.6) \times \frac{172.2}{40.1} \times 1.25 \times \frac{1}{2} = \frac{1775 \text{ kg } \text{CaSO}_4 \cdot 2\text{H}_2\text{O}}{2}$$

The amount applied to the split 20 plot amounted to $1680 \text{ kg CaSO}_4 \cdot 2\text{H}_2\text{O}$ which was somewhat short. However, it was desirable to see how effective a heavier one time application was in lowering the ESP below 15% which was present at the top 30 cm.

Table 11. Treatment $\underline{20}$ calcium requirements (1980 and 1981) to maintain the SAR_{iw} at 3 or 5 based upon the water analysis and depth of water applied at each irrigation during the season. Total calcium requirements for the season are given at the bottom of each year.

		son are g	SAR=3	circ poccom	or cach	SAR=5	
				kg Ca			kg Ca
	Effluent	me/l Ca	kg Ca	per plot	me/l Ca	kg Ca	per plot
	Applied		per ha	per	to be	per ha	per
DATE	(cm)	added	per an	irrig	added	per cm	irrig
800513	12.70	13.21	26.55	125.28	-0.04	-0.09	-0.40
800519		13.21	26.55	80.18	-0.04	-0.09	-0.26
800528			34.08	25.74	0.29	0.58	0.44
300612			34.08	34.42	0.29	0.53	0.58
800616			34.08	35.71	0.29	0.58	0.61
800620		16.96	34.08	22.52	0.29	0.58	0.38
800702			34.08	38.60	0.29	0.58	0.65
800710			34.54	30.65	1.31	2.63	2.34
800722			32.43	36.73	1.29	2.59	2.93
800729			32.43	28.77	1.29	2.59	2.29
800731			51.66	48.76	4.17	8.38	7.91
800809			51.66	46.81	4.17	8.38	7.60
800808			51.66	40.96	4.17	8.38	6.65
800813			55.64	63.02	4.29	8.61	9.76
800822			55.64	67.75	4.29	8.61	10.49
80091			63.39	71.79	4.86	9.77	11.06
800916			63.39	74.19	4.86	9.77	11.43
800929			62.84	51.01	4.92	9.90	8.03
800930			58.81	34.97	4.09	8.21	4.88
801007	7 1.57	21.78	43.78	25.62	1.01	2.02	1.18
TOTAL	66.04			983.5			88.6
810509	3.45	28.41	57.09	73.29	3.40	6.82	8.76
810513	3 2.34	28.41	57.09	49.58	3.40	6.82	5.93
810519	3.56	32.58	65.48	86.53	4.87	9.80	12.95
810601	2.59	36.54	73.44	70.70	6.54	13.15	12.66
810608			73.44	79.71	6.54	13.15	14.28
810619			134.52	138.39	17.21	34.60	35.59
810626			134.52	152.36	17.21	34.60	39.19
810706			126.41	168.24	16.59		44.38
810714			123.64	151.71	16.32	32.80	40.25
81072			127.53	144.45	16.02	32.21	36.48
81081			247.30	275.43	38.72	77.83	86.69
810818			159.88	188.63	22.65	45.53	53.72
810826			159.88	111.67	22.65	45.53	31.80
81091			149.53	122.79	19.95	40.10	32.93
810929	2.03	74.39	149.53	112.91	19.95	40.10	30.28
TOTAL	45.90			2201.8			572.6

At the same time, past irrigation management on the 20 plot was limited to weekly applications of 1.7-3.4 cm (.7-1.4 in) per irrigation with the depth dependent upon ET demands. This was contrary to the most efficient use of the water and apparently concentrated much of the sodium applied in the top foot of soil. Therefore, the irrigation schedule on the 20 and 20G plot for 1982 was changed to irrigate every third week with three times the depth of application. This regime was more desirable for prevention of sodium accumulations near the surface, however, it was contrary to the best management for sodium reclamation (18). During this type of experiment, water has to be disposed of yet sodium has to be removed from the exchange complex while trying to minimize exchangeable sodium.

Upon project completion, numerous undisturbed soil cores at the 0-3 cm depth were collected from all treatments including surrounding checks on unirrigated areas to determine if ESP (exchangeable sodium percentages) correlated with reduced saturated hydraulic conductivities. A Eulen core sampler (with brass ring inserts), which uses 3 cm by 5.4 cm ID brass sleeves, was used to take the samples within the boundaries of the sprinkler heads. A petroleum jelly was used to coat the inside of the rings prior to sampling to prevent compaction during sampling and channeling during testing.

A constant rate peristaltic pump was used to move deionized water through the cores which were placed inside acrylic Tempe cells similar to the one shown in Figure 10. Polyethylene filters with 35 micron openings were used in place of the ceramic plates. Twenty-four cores were tested at the same time with each channel of the pump delivering




Figure 10. Representation of the design of acrylic Tempe cell used to hold undisturbed soil cores for saturated hydraulic conductivity measurements. (Taken from Methods of Soil Analysis, Agronomy Monograph No. 9, page 218.)




Figure 11. Schematic representation of the design used in measuring saturated hydraulic conductivities.

water simultaneously to six cores (Figure 11). Piezoresistive pressure transducers were used to monitor the pressure head while the delivery rate was kept constant by the pump. Graduated cylinders were used to measure hourly volumes and a subsequent $K(\Theta_S)$ value was calculated. The test was conducted for six hours and the six $K(\Theta_S)$ values were averaged for each core. Darcy's law,

$$V = -K\frac{h}{L}$$

where V = velocity of flow, cm/hr

K = hydraulic conductivity, cm/hr

h/L = potential gradient, cm/cm

was used to calculate the K value. By rearranging the above terms

$$K = - \frac{qL}{ah}$$

where q = volume collected in time t, cm^3

a = cross-sectional area of core, cm^2

h = pressure head, cm

L = length of core, cm

and the hydraulic conductivity could then be calculated.

RESULTS AND DISCUSSION

Forage Yields

The dry matter alfalfa yields for the treatments by year and replication are given in Appendix H. The average treatment yields per cutting are given in Table 12. There was a significant difference in yield every year among the treatments at the .01 level. However, this was contributed entirely by the check plot as is evident in Table 13. Single degree of freedom comparisons were used to identify differences in mean yields. However, only the 20 plot in 1981 showed any significant (.05 level) difference from the other treatments. This was due to the shortage of rainfall throughout the season and total moisture fell below ET demands. Statistically, there were no significant yield differences caused by varying the annual hydraulic loading from 50 cm to 127 cm except during an exceptionally dry year (1981).

The extra increase in dry matter yield over the check due to irrigation varied from 1615 kg/ha (.72 ton/acre) per cutting for the 20 plot average to 1856 kg/ha (.83 tons/acre) per cutting for the 35 and 35G plot averages. Assuming four cuttings per year that relates to a range of 6460 kg/ha-7424 kg/ha (2.88-3.31 tons/acre) for alfalfa dry matter yield increases. At \$55/1000 kg (\$50/ton) that would amount to \$355-\$408/ha (\$144-\$165/acre) increase in gross revenues.

Water table problems showed up at the end of the second year in both the 50 and 35G plots. Loss of alfalfa plants began at that time on the 50 plot. By the end of the third year a 15-20% reduction in alfalfa plants had occurred near the east lower end of the plot

Table 12. Moisture and yield data of alfalfa plots 1980-1982, dry matter.

Treatment	Year	Cumulative rainfall cm(in)*	Cumulative irrigation cm(in)	Total cm(in)	Seasonal ET, cm(in)	ΔStorage plus leaching+RO cm(in)	Average per cutting yield kg/ha(tons/A)
50	1980	40 (15.6)	120 (47.1)	160 (62.7)	77 (30.3)	82 (32.3)	2179 (0.97)
	1981	27 (10.5)	108 (42.5)	135 (53.0)	76 (29.8)	59 (23.1)	2696 (1.20)
	1982	48 (19.0)	78 (30.9)	126 (49.9)	76 (29.9)	51 (19.9)	2606 (1.16)
	Avg.	38 (15.0)	102 (40.2)	140 (55.2)	76 (30.0)		2516 (1.12)
35G	1980	40 (15.6)	95 (37.3)	135 (52.9)	77 (30.3)	57 (22.5)	2471 (1.10)
	1981	27 (10.5)	75 (29.7)	102 (40.2)	76 (29.8)	26 (10.3)	2471 (1.10)
	1982	48 (19.0)	45 (17.8)	93 (36.8)	76 (29.9)	18 (6.9)	2808 (1.25)
	Avg.	36 (15.0)	72 (28.3)	110 (43.3)	76 (30.0)		2577 (1.15)
35	1980	40 (15.6)	94 (36.9)	134 (52.5)	77 (30.3)	56 (22.2)	2224 (0.99)
	1981	27 (10.5)	75 (29.7)	102 (40.2)	76 (29.8)	26 (10.3)	2696 (1.20)
	1982	48 (19.0)	45 (17.8)	93 (36.8)	76 (29.9)	18 (6.9)	2741 (1.22)
	Avg.	38 (15.0)	71 (28.1)	110 (43.2)	76 (30.0)		2579 (1.15)
20	1980	40 (15.6)	66 (26.0)	106 (41.6)	77 (30.3)	29 (11.3)	2134 (0.95)
	1981	27 (10.5)	43 (16.9)	70 (27.4)	76 (29.8)	-6 (-2.5)	2246 (1.00)
	1982	48 (19.0)	27 (10.5)	75 (29.5)	76 (29.9)	-1 (-0.4)	2673 (1.19)
	Avg.	38 (15.0)	45 (17.8)	84 (32.8)	76 (30.0)		2338 (1.04)
Check	1980	40 (15.6)	0 (0.0)		77 (30.3)	-37 (-14.8)	1235 (0.55)
	1981	27 (10.5)	0 (0.0)		76 (29.8)	-49 (-19.4)	0 (0.00)
	1982	48 (19.0)	0 (0.0)		76 (29.9)	-28 (-10.9)	899 (0.40)
	Avg.	38 (15.0)	0 (0.0)		76 (30.0)		723 (0.32)
20G	1982	48 (19.0)	27 (10.5)	75 (29.5)	76 (29.9)	-1 (-0.4)	2336 (1.04)

^{*}May 1 → October 31

[†]Based on last three cuttings, 1982. RO=run-off

Table 13. Single degree of freedom partitions of treatment sum of squares for alfalfa yields (kg/ha), 1980-1982.

	Partition	DF	<u>ss</u>	MS	F
1980	TREATMENT	4	3661.0	921.0	6.87 **
(3 cuttings)	50 vs $(\overline{35+35G+20})$	1	38.0	38.0	0.29
(35 vs $(35G+20+50)$	1	2.2	2.2	0.02
	35G vs $(20+35+50)$	1	276.0	276.0	2.07
	20 vs (35+50+35G)	1	78.0	78.0	0.59
	Check vs $(35+50+35G+20)$	1	3369.0	3369.0	25.21 **
	ERROR	40	5346.0	133.7	
1981	TREATMENT	4	27944.0	6986.0	70.56 **
(4 cuttings)	50 vs $(35+35G+20)$	1	193.0	193.0	1.95
	35 vs (35G+20+50)	1	225.0	225.0	2.27
	35G vs $(20+50+35)$	1	25.0	25.0	0.25
	20 vs (50+35+35G)	1	571.0	571.0	5.77 *
	·Check vs (50+35+35G+20)	1	27183.0	27183.0	275.02 **
	ERROR	55	5436.0	988	
1982	TREATMENT	4	14255.0	3565.0	25.69 **
(4 cuttings)	50 vs (35+35G+20)	1	61.0	61.0	0.82
	35 vs $(35G+20+50)$	1	7.0	7.0	0.09
	35G vs (20+50+35)	1	67.0	67.0	0.91
	20 vs (50+35+35G)	1	9.0	9.0	0.12
	Check vs $(50+35+35G+20)$	1	14150.0	14150.0	190.91 **
	20G vs $(50+35+35G+20)^{\dagger}$	1	74.0	74.0	0.98
	ERROR	55	7629.0	139.0	
TOTAL	TREATMENT	4	41063.0	10266.0	66.04 **
(Based on	50 vs (<u>35+35G+20</u>)	1	0.2	0.2	0.001
first 3	35 vs $(35G+20+50)$	1	94.0	94.0	0.61
cuttings)	35G vs $(20+50+35)$	1	115.0	115.0	0.74
	20 vs (50+35+35G)	1	436.0	436.0	2.80
	Check vs $(50+35+35G+20)$	1	40587.0	40587.0	261.15 **
	ERROR	160	24867.0	155.0	

^{*}Significant at the .05 level.
**Significant at the .01 level.
†Based on last three cuttings of 1982.

(Figure 12). This was caused by either reduced aeration caused by saturation or disease brought about by saturation or both. It was evident on all plots that as local surface water movement increased due to reduced infiltration and/or saturated soils, depressional areas and border soils received increased water amounts. If the project were to be continued with the same hydraulic loading rates, the 50 plot would certainly further decline in yield because of continued alfalfa plant losses. In 1982, treatment 50 was the only plot which showed a decline in yield; however, it was not significant. All other treatments increased in yield from the previous year.

Treatment 35G did show signs of potential alfalfa plant reductions with yellowing of plants in a plow furrow the length of the plot (Figure 13.). Local water movement caused increased amounts of moisture applied to the lower area. The water table was within .9 meters (2.9 ft) of the surface at that time according to the neutron access tube. Effects of Gypsum Amendments

As mentioned earlier, the amendment required for treatment 35G in 1980 was applied in September 1980. The effects of that application would be seen at the following soil sampling and analysis (fall 1981), if one were to look at annual effects only. However, suction tensiometers were used throughout the irrigation season to extract soil water samples in addition to soil sampling. Figure 14 is a graphical representation of the concentrations of soluble sodium for 1981 on plot 35G. If gypsum is effective in removing sodium from the exchange complex over the winter and spring months, an increase in the soluble sodium concentration should occur and be evident in the early part of




Figure 12. Depiction of the alfalfa population reduction at the low end of the 50 plot August 1982.



Figure 13. A 1982 picture of 35G plot before harvest. A plow furrow running the length of the plot accumulated localized run-off and created the yellowing of the alfalfa. The water table was approximately 1.3 meters below the surface according to the observation well.

Figure 14. Soluble sodium levels with time and depth from plot 35G,




the following season. July 6, 1981 was the earliest date that soil extract samples were obtained from the 30 and 45 cm depths and they both show sodium levels higher than in the other treatments on that date (Figures 14 and 15). As irrigation amounts increased over the season, sodium levels at the 30, 45, and 60 cm depths decreased while the sodium at the 90 cm depth increased. There appeared to be no change in the sodium level at the 120 and 150 cm depth for 1981. It would appear that as the SARiw increased and the cumulative irrigations increased, the soluble sodium moved from the upper layers and was deposited into the 90 cm depth. Numerical values of the concentrations are presented in Appendixes A, B and C for the 3 years.

Soluble sodium concentrations gradually increased at the 30, 45, and 60 cm depths for all treatments in 1980. However, the concentrations at the deeper depths all remained fairly low and constant for the first year (Figure 16). Apparently most of the sodium is staying in the top meter, at least for the first two seasons.

Plot 20 for 1980 displayed an exception to this at the 150 cm depth with 690-2360 ppm sodium near the end of the irrigation season. A one-time sample in November from the 20 plot showed 12,200 ppm soluble sodium in the top 30 cm. This small amount of evidence indicates that light infrequent irrigation amounts can be devastating to soil structure by concentrating the applied sodium near the surface.

For 1981, on treatment 35G, EC, chloride, and sodium trends show much the same pattern for the 30, 45, and 60 cm depths. This indicates that a large portion of the cations and anions contributing to the salt load are sodium and chloride. However, for the 90, 120, and 150 cm






Figure 16. Soluble sodium field extracts by depth from plot 50, 1980.

depth, it's another story. Chloride seems to be the major anion, but sodium is not the dominant cation. Calcium from the gypsum and magnesium (exchanged for calcium on the soil complex) must be the dominant cations. In observation well analyses, magnesium is 4-9 times higher in the 35G over the other treatments but calcium seems to be similar to the other plots (Appendix G).

Soil sampling analyses for the various years on the different plots are averaged for three sites per treatment and presented in Table 14. In determining the effectiveness of gypsum applications, the exchangeable sodium percentage (ESP) is used as a guide. Usually, increasing the ESP will cause decreasing soil permeabilities; however, more research is needed to determine what effect other parameters have on causing a significant realistic change of soil permeability.

It must be understood that annual or semi-annual soil samplings may not be sufficient to determine a critical situation which may occur in the soil during an irrigation season. Let's go through an example. Suppose soil samples were taken in the fall of 1980 and ESP's on the 20 plot at the 30 cm depth were 6.7% (Table 14). Then samples were again taken in the spring of 1982 and ESP's were 11.1%. According to the soil samples taken in the fall of 1982 the ESP's were almost 16% and they may have been higher yet after a particular hot spell during the wetting and drying cycle of that summer, something I will call a "critical period". Soil dispersion may have occurred during this critical period with soil clay particles moving downward to eventually clog pore spaces and reduce permeabilities. The ESP may have approached 20 or even 40 for that interval which caused the damage, however, the only

Table 14. Chemical soil analysis 1980-1982. Average of 2-3 sites per plot per depth.

Trea	t Depth		CEC	(me/]	(p00_		Exc	h angea	ble Na	(me/l				ESP				SAR of	soil	solutio	
≡e nt	CDB	1*	2	3	4	5 	1	2	3	4	5	1	2	3	4	5	1	2	3	4	5
20	0-3 0-15 15-30 0-30 30-60 60-90 90-120	14.1	15.6 11.5	13.5		24.6 22.4 23.0 19.0 14.0 13.5	0.4 0.2 0.4 0.5	1.4 0.5 0.5 1.1	3.2 1.5 1.6 1.1	2.4 2.6	1.0 1.5 2.3 1.4 0.7 0.7	2.1 1.1 2.9 3.4	6.7 3.3 4.0 8.1	15.7 7.8 11.8 8.1	11.0	4.1 6.9 10.1 7.6 5.1 5.3	1.4 1.1 1.5 1.6	3.5 0.4 0.9 2.5	6.2 2.3 1.4 2.2	6.1 7.5	2.3 6.2 6.2 5.2 2.1 1.5
35	0-3 0-15 15-30 0-30 30-60 60-90 90-120	15.0 11.7	18.7 15.5 12.8 17.0	15.2 12.7		21.0 21.5 21.3 17.7 12.0 13.9	0.5 0.1 0.1	1.3 0.5 0.4 0.6	1.7 1.4 0.8 0.6	1.8	1.2 1.6 1.7 1.7 1.9	3.0 0.8 1.1 1.9	7.1 3.2 3.5 3.5	9.2 9.3 6.3 4.3	8.8 10.7	5.8 7.3 8.2 9.4 15.8 7.0	2.4 0.5 0.4 0.5	4.3 1.3 1.0 1.6	7.8 6.5 2.7 0.8	6.0 6.7	3.6 5.4 7.0 7.7 4.9 2.3
3 5G	0-3 0-15 15-30 0-30 30-60 60-90 90-120		16.8	19.6 18.4 13.5 12.9		25.1 21.0 20.8 19.6 17.8 12.9	0.4 0.2 0.4 1.3	0.3	2.2 1.3 0.7 0.5	1.6	1.0 1.6 1.9 1.7 1.6	2.3 1.3 2.9 7.9	1.6	11.0 6.9 5.3 4.0	7.4 10.5	4.0 7.5 9.0 8.9 9.3 8.1	1.6 0.4 1.0 2.4	0. 5	6.8 5.6 3.5 0.9	5.3 6.6	4.0 4.7 5.8 6.1 4.5 3.2
50	0-3 0-15 15-30 0-30 30-60 60-90 90-120	16.6 10.3	18.4 11.2 10.5 12.9	13.9 10.4		22.0 22.2 19.3 17.0 16.0 17.5	0.8 0.4 0.2 0.2	1.5 0.6 0.4 0.2	1.8 1.4 1.0 0.6	1.9	1.5 1.7 2.0 1.7 1.4 1.8	4.6 2.3 1.6 1.2	7.9 5.4 4.0 1.8	10.2 9.8 10.0 4.8	8.4 11.0	6.8 7.7 10.2 10.0 8.9 10.4	3.3 0.7 0.4 0.3	5.1 2.9 1.3 0.5	7.9 7.9 4.6 4.2	6.2 6.8	5.6 5.6 6.8 7.1 6.3 5.0
20G	0-3 0-15 15-30 0-30 30-60 60-90 90-120				22.5 19.1					2.0	0.8 1.4 2.2 1.4 1.0				8.7 10.4	3.1 6.1 9.8 9.5 6.7 5.5				6.3 7.7	2.1 3.6 6.2 4.5 2.6 2.0

Table 14 (continued).

	t Depth			ble Mg	(me/l			hangea	ble Ca	(me/l			P	H (past	e)			BC Sat	Ext	. (us/c	
ment	Cm	1*	- -	- -		5	1									5	1	2	3		5
20	0-3 0-15 15-30 0-30 30-60 60-90 90-120	5.3 6.5 12.0 13.7	6.8 8.9 8.8 13.8		5.1	8.9	20.8 39.7 52.6 47.7				17.4 17.0 17.3 45.4 45.9 44.3	7.0 7.3 7.9 7.7	7.5 7.6 7.7 8.0	7.2 7.6 7.8 8.0	6.4	7.1 7.3 7.4 7.6 7.8 7.7	960 851 2815 2416	2148 1453 2746 3783	3158 3857 2257 1169	1724 2092	579 788 876 1652 2643 4956
35	0-3 0-15 15-30 0-30 30-60 60-90 90-120	3.9 4.7 5.7 8.2	5.4 8.1 10.8 12.3		4.7	8.6	17.3 34.7 44.1 38.5	51.6		14.2 15.5		6.9 7.5 7.9 7.9	7.2 7.6 7.6 7.6	7.4 7.5 7.7 7.6	6.7 6.7	7.6 7.2 7.4 7.9 7.9 7.8	1066 788	1694 2429 3584 5187	2665 3393 2798 5086	1572 1331	903 1399 1407 1471 1927 2836
35G	0-3 0-15 15-30 0-30 30-60 60-90 90-120	4.7 6.2 7.6 13.6	7.8		4.3	8.8	24.0 50.0 49.9 127.3	22.4		16.2 16.2		7.0 7.3 7.9 7.9	7.6	7.1 7.4 7.6 7.8	6.7	7.5 7.2 7.2 7.7 7.7 7.7	1233 655 2001 8332	1684	3900 3582 2903 4476	2753 2158	
50	0-3 0-15 15-30 0-30 30-60 60-90 90-120	3.8 4.0 4.9 9.5	4.3 4.1 5.1 11.0		5.3 5.1	3.8	16.2 27.7 40.8 38.0	34.4 40.7		14.6 15.3		7.0 7.8 8.1 8.1	6.9 7.5 7.7 7.8	7.2 7.5 7.9 7.7	6.8 6.7	7.3 7.2 7.4 7.7 8.0 7.9	1314 869 859 850	1880 1404 1341 1180	1925 2298 2277 2367	1808 1746	
20G	0-3 0-15 15-30 0-30 30-60 60-90 90-120				5.5 4.0	4.5 3.7 4.8 5.8 9.5 14.5				15.9 16.2					7.0 6.3	7.2 7.0 7.0 7.3 7.7 7.8				1449 1494	

^{*}Sampling dates: 1=Spr'80, 2=Fall'80, 3=Fall'81, 4=Spr'82, 5=Fall'82

data available to justify the dispersion damage is an ESP level between 6.7 and 11.1%.

A possible reasoning for the potentially higher ESP assumption If a farmer is applying irrigation water to the soil during a season to supply the crop with its moisture demands, usually very little leaching, if any, is taking place over a 3 or 5 month period. In some cases, new irrigators may be wetting only the top 30-45 cm of soil with each irrigation. After an irrigation event, suppose the top was wet to field capacity and ET began to draw moisture back out to the surface. As the water volume decreases in the soil, the concentration of each ion increases. The first ions which tend to precipitate are the least soluble inorganic compounds such as CaCO3 and MgCO3 (high bicarbonates are reduced to carbonates as concentration increases) and the last ions to precipitate during drying are the Na, Cl, and SO4. During this process, the SAR of the soil solution increases with decreasing soil moisture volumes. Therefore, it is quite important to thoroughly wet the soil to greater depths to distribute salts more evenly and then try to keep the soil from completely drying out near the soil surface. If the soil surface does dry out and the soluble calcium is precipitated in the form of CaCO3, unless soil pH values are below 7.8 (Table 15), very little calcium will come back into solution upon rewetting. It's important to remember that at each irrigation additional amounts of Ca, Mg, and Na are moved into the soil solution and that the above potential exists throughout the irrigation season.

Table 15. Solubilities of CaCO3 at various pH's. (Taken from the U.S.D.A. Handbook No. 60.) (Atmospheric pCO2).

pH value of CaCO3 saturated solution	Solubility of CaCO3 (me/1)
6.21	19.30
6.50	14.40
7.12	7.10
7.85	2.70
8.60	1.10
9.20	0.82
10.12	0.36

By looking at the ESP levels of the several treatments from Table 14, it appears that the plot with the least amount of water or sodium applied to it, had the highest levels of exchangeable sodium in the soil profile. In the first year of irrigation, penetration of the water on plots 50, 35, and 35G was sufficient to move some sodium deeper in the soil profile. The soil was very dry prior to initiation of the project, consequently, the soil readily accepted and moved water quickly deeper in the soil profile. Near the end of the second year, water movement downward became less and run-off increased on the 50 treatment. For these two circumstances, there are two different results in ESP values.

Each of the plots received the same <u>frequency</u> of irrigation but different amounts each time. At the end of the first and second year, plot 20 had more exchangeable sodium in the top 120 cm than the other treatments. In 1982, water table problems were evident on the 35G and 50 plots. This caused a restriction in downward water movement when irrigation and higher rainfall amounts came. Thus, plot 20 total soil exchangeable sodium dropped and the other treatments increased.

It was evident that the exchangeable sodium levels at the surface 30 cm dropped on all treatments from 1981-1982, probably due to the dilution of increased rainfall.

According to the ESP values, no differences were evident between the gypsum and non-gypsum plots either for two annual applications or a one-time heavy application. Keren and O'Connor in 1982 (18) concluded that for sodic soil reclamation (exchangeable sodium removal), by increasing the soil water velocity, the gypsum dissolution rate is decreased. Also, they said that the calcium concentration in solution is dependent on both the dissolution rate coefficient and the contact time between an elemental volume of water (soil water velocity) and a unit of surface area of gypsum fragments. Non-incorporated large fragments of gypsum, then, would not be as effective in sodium removal as well-incorporated powdered gypsum. They also found that the efficiency of replacing Na by Ca in soil of ESP = 20 was a function of soil water velocity and that realistic values for Na removal were between 52 and 81% for various soil water velocities. The water velocities they were working with were 13.5, 2.9, and 1.16 cm/hr.

This reclamation study would certainly indicate that trying to remove exchangeable sodium with high annual rates of wastewater would be quite inefficient for gypsum utilization in addition to adding heavy amounts of magnesium sulfate to the ground waters (refer to observation well water quality, Appendix G). The obvious answer to this type of problem would be to mix the gypsum into the irrigation water prior to application and prevent sodium attachment. Ground waters would still

be receiving magnesium sulfates but because gypsum utilization efficiencies would be higher, the amount necessary to add would be less to accomplish the same effects.

One significant point that should be mentioned is the difference in SAR of the soil solution between the 20 and 20G plot for the 0-15 cm depth (Table 14). The Ca⁺⁺/Na⁺ ratio for that depth on the 20G plot is 3.7 times higher than for the same treatment without gypsum (plot 20) in September 1982. The SAR's for that same depth in the spring 1982 (before gypsum) were 6.1 for the 20 and 6.3 for the 20G plot. This indicates that a non-equilibrium condition exists. When the ESP>SAR, there is a gradient and a tendency for the ESP to drop and for the SAR to increase. Consequently, in time, one would expect the exchangeable sodium to be reduced. This condition is caused by the increased concentration of Ca⁺⁺ due to the dissolution of the gypsum. Saturated Hydraulic Conductivity

Usually, the soil ESP and electrolyte concentration are used as a measure to indicate soil permeability. The relationship between these two parameters and saturated hydraulic conductivity ($K\Theta_s$) on South Dakota soils is currently being studied.

The basic concern in using this type of wastewater for irrigation is to maintain soil permeability and infiltration capacity for perhaps 20-25 years. This is an absolute necessity for wastewater acceptance and subsequent treatment. Consequently, it became necessary to try to evaluate the permeability differences between the soils in each treatment and the check.

First of all, sprinkler or double-ring infiltrometers were suggested

to obtain the results desired. However, a water table was present within .67 meters (2.2 ft) of the surface on the 50 plot and 1.2 meters (4 ft) on the 35G plot. Because of this, it was felt that the saturated conditions would quickly slow down the infiltration curve on those plots and a comparison of that data to the data on the other plots would be difficult. In addition to this, a check on the permeability of the soil surface was desired without the presence of a restricting boundary beneath. Therefore, it was decided to use small undisturbed surface cores to test in the laboratory under similar environments.

A shortage of brass sleeves and time prevented the collection of 12 replications from every treatment; however, a sufficient number of samples was obtained for comparison purposes. The $K(\Theta_S)$ data on all the cores is presented in Table 16. (Refer to Figures 10 and 11 for the equipment used to obtain the values.) Deionized water was used to pump through the cores from the bottom to the top to reduce air entrapment in the cores. Mercuric chloride was put in the water to inhibit bacterial growth during the test.

The variability within a treatment among observations was very high. In fact in almost every case, the standard deviation exceeded the mean. The analysis of variance, presented in Table 17, basically says that there is no difference between treatment means at the .05 level of significance. However, there is an algebraic difference in the means with the check the fastest and 20G the slowest. Dunnett's test (Table 18) was used to compare the check mean against the treatment mean for $K(\Theta_S)$; however, no significant difference at

Table 16. Replications of saturated hydraulic conductivity measurements for the top 3 cm for the various treatments. Values are averages for the first six hours (units are cm/hr).

		-	Treatm	ent		
	Check	50	<u>35G</u>	35	20	20G
	0.0254	0.5801	0.0758	0.2043	.5070	.1608
	0.1858 0.1461	0.2865 0.0001	0.0198 0.1602	0.0118	.0078 .0336	.0031 .0113
	0.2371	0.1905	0.1504	0.0079	.0239	.0285
	0.2272	0.0069	0.3761	0.0129		.0134
	1.0517 0.0239	0.0547 0.0108	0.3309 0.3503	0.0708 0.0490		.0015
	0.2452	0.0100	0.3303	0.0935		
	0.0983	0.0218	0.0043	0.2387		
	0.1374 0.2905	0.0172 0.6363	0.1844 0.1738	0.0023 0.0113		
	0.6427	0.0905	0.1736	0.0212		
Total	3.3110	1.9625	2.0056	0.7237	.5723	.2186
Mean	0.2759	0.1635	0.1671	0.0658	.1431	.0364
S.D.	0.2929	0.2247	0.1287	0.0826	.2428	.0617
N	12	12	12	11	4	6
Std error	0.0564	0.0564	0.0564	0.0589	.0976	.0797

Table 17. Analysis of variance for laboratory saturated hydraulic conductivity measurements of the surface 3 cm at the completion of the project.

	DF	SS	MS	<u>F*</u>	
Total	56	2.2958	.0410		
 Treatments	5	0.3506	.0701	1.84	
Error	51	1.9452	.0381		

^{*}Critical value for F.05 (5,51) >2.40.

Table 18. Dunnett's test of the check mean vs. treatment means for saturated hydraulic conductivities of the top 3 cm of soil.

Check vs 50	1.41	
Check vs 35G	1.36	
Check vs 35	2.52	
Check vs 20	0.96	
Check vs 20G	2.12	

^{*}Critical value for $\alpha = .05$ is $d_{.025}(5,51) = 2.60$.

the .05 level was determined. There appeared to be too much variability within each treatment for differences in $K(\theta_s)$ to be significant.

Some of the differences may be significant, however, because of two important factors. First, in determining the $K(\Theta_S)$ values, pressure heads between treatments were not constant. Table 19 shows the variation in head between treatments and between groups of tests.


Table 19. Variation in pressure heads (cm) used to calculate $K(\Theta_{\mathbf{S}})$ according to Darcy's law.

		Treatments					
	Check	50	35G	35	20	20G	
1st set	20-25	45-60	104-122	45-50	25 - 35	200-1000*	
2nd set	20-25	40-45	37-40	30-35			

^{*}One core on the channel of six dropped drastically in volume during the 6 hour test causing the marked increase in pressure.

They vary from 20-25 cm for the check plot to 200-1000 cm for the 20G plot. Darcy's law, when pressure heads change, does not hold to be linear using these cores with this type of apparatus. There are other factors which cause hysteresis in the theory. Figure 17 shows two treatments with 6 replications each and the subsequent $K(\theta_{\rm S})$ values every 15 minutes for 6 hours. All six cores were on one channel with the pump delivering a constant flow rate. When one or two channels were clamped off because of blow-outs or severe channeling, the pressure head went up on the remaining cores. All precautions were taken to insure similar pressures to all cores throughout the test, however, channeling or blow-out's could not be predicted.

Second, the 20 and 20G plot showed severe dispersion when water was delivered to the cores. The first few drops of effluent were totally






Figure 17. Graphical depiction of the change of $K(\Theta_{\mathbf{S}})$ with increasing pressure heads on two treatments.

black indicating that the particles were dispersed prior to wetting by the water. This occurred on every core tested in the 20 and 20G plots, but no more than slight amber discoloration of the effluent was evident on the other treatment cores tested. Table 19 shows the amount of dispersed residue which was lost from each core during the test as the por volumes increased. In all replications, dispersed residue decreased with increasing pore volumes. Table 14 gives the soil chemical analysis for the 0-3 cm depth for each treatment.

Two theories are offered to explain the difference in dispersion between treatments. First, perhaps only the 20 plot had ESP's high enough to cause the release of dispersed soil particles (they had ESP's which approached 16 at the 0-30 cm depth).

Second, the dispersed soil particles, if any were present, on the other treatments may have been washed below the 3 cm level, whereas the 20 plot, with its lower leaching and applications of wastewater, may have dispersed soil particles still remaining in the top 3 cm. If the first theory is true, clay particles must have become dispersed during the 1981 season when little rainfall came and ESP's were 16 or higher. The $K(\Theta_S)$ tests on that soil after one year indicate dispersed soil particles with ESP's ranging from 3-4.8 on the test cores. This may mean that if a "critical period" (ESP levels equal soil dispersion) occurs in the field perhaps in a dry, hot spell, dispersed surface soil particles may stay dispersed for long periods of time even though the subsequent ESP levels would indicate that there is no danger of soil dispersion. This theory should be investigated further to determine if this kind of thing occurs often. If it does, many irrigators may

Table 19. Dispersed residue lost through a 35 micron plastic filter during a six hour hydraulic conductivity test in a 3 cm \times 5.4 cm ID tempe cell using distilled water for various treatments and pore volumes, 1982.

Treatment	Rep.	effluent collected(ml)	Total residue(g)	Specific pore volume(ml)	<pre># of pore vol collected</pre>	Dispersed residue (g/cm²/pore volume)
20G''	1	500	.2123	29	17.2	.159
(ESP=3.22)		500	.0418	11	17.2	.031
		160	.0226	11	5.5	.005
	2	93	.0783	11	3.2	.011
	3	160	. 4848	11	5.5	.116
	4	436	.1435	11	16.7	.105
	5	256	.1696	11	8.8	.065
	6	41	.0435	11	1.4	.003
0"	1	500	.1729	34	14.7	.111
(ESP=4.55)		101	.0092	11	3.0	.001
	2	49	.1209	**	1.4	.007
	3	500	.0926	11	14.7	.059
		500	.0382	11	14.7	.025
		89	.0027	***	2.6	.0003
	4	82	.1428	11	2.8	.017
	5	371	.2240	11	10.9	.107

eventually have serious permeability problems which may not be easily reversed.

Drainage Water Quality

From suction tensiometers

Suction tensiometers were installed at depths of 30, 45, 60, 90, 120, and 150 cm on each plot for the purpose of monitoring soil water before it would move below the tip of the root zone. In 1981 a second set of tensiometers was installed on plot 50 and was, subsequently, called 50A. A lot of the concern in wastewater treatment by the soil is that the groundwaters might become contaminated. This second set of tensiometers was installed to obtain data from a second replication on the high annual application plot to better identify any potential contamination problems.

The parameters which were analyzed were EC, HCO3, C1, Na, NH3, total PO4, pH, and NO3. The data which was collected and analyzed is given in Appendix A (1980), B (1981), and C (1982). A few color graphs have been made and will be presented under the appropriate parameter which is discussed.

From observation wells

Observation wells were installed at the center of each plot to monitor groundwater quality and water table changes. The parameters which were analyzed were similar to the suction tensiometers. Spot checks of Ca, Mg, K, and SO_4 were added to the list to obtain information which might be pertinent relative to the concentration of the same parameters of the applied water.

Figures 18, 19, 20, and 21 are graphical representations of the changes in EC, Na, Cl, and NO3 of the observation wells with time by year by treatment. Tables of the data from the observation wells are presented in Appendix G. These figures will be referred to occasionally in discussion of that particular parameter in the drainage water.

Nitrogen as nitrates

Nitrate groundwater contamination tends to be a major concern in wastewater disposal on soils because the ion is so readily leachable. First of all, nitrate levels in the effluent were not found to be very high except during late June and July when total organic nitrogen and ammonia were converted to nitrates. The levels at this time were not in excess of 15 ppm, however. This appeared to be the same time when higher levels were evident in the soil. The maximum level of nitrate concentration in the soil on any plot was 150 ppm. This was at the 45 cm depth on plot 50, 1981 (Figure 22). These levels were concurrent with the higher levels in the wastewater. At no time did the nitrate level in the samples taken exceed 10 ppm below 120 cm on any plot.

Nitrate levels from the observation wells were below 1 ppm for the 50 and 20 plots (Figures 18 and 21) for the entire project. Nitrate levels in plot 35 and 35G were higher (2-10 ppm) (refer to Figures 19 and 20). Some of the explanation for these differences can be seen in Figure 2, the boring logs of the various plots. Plot 50 had a layer of heavy clay loam below the 2 meter depth, whereas plot 35 had a layer of pure sand below 1 meter with sand and clay loam intermixed below

____ 1988 1991 --- 1982 PLOT 50




Figure 18. Changes in observation well water quality with time for plot 50.

____ 1988 1981 --- 1982 PLOT 95G





Figure 19. Changes in observation well water quality with time for plot $35\mathrm{G}.$






Figure 20. Changes in observation well water quality with time for plot 35.

____ 1988 1991 --- 1992 PLOT 28




Figure 21. Changes in observation well water quality with time for plot 20.




Figure 22. Nitrate levels at various times and depths in the soil solution from plot 50, 1981.

that layer. Since these holes were cased and packed with sand around the casing close to the surface, it is conceivable that horizontal water movement in the sand layer (plot 35) may have occurred.

Total phosphates and ammonia

Total phosphates and ammonia were higher in the soil when the levels in the wastewater were higher. Levels in the soil for T-PO₄ did not exceed 1 ppm below the 120 cm depth. Ammonia levels appeared to increase with depth in the soil. Levels usually ranged from 0-2.50 ppm at the 120 and 150 cm depths. Again, the higher levels of NH₃ in the soil correlated with the higher levels in the wastewater, which was mainly in the spring and early summer.

EC

At the beginning of the project, for most plots, the EC for the upper 60 cm usually was higher than the EC of the deeper soils. This was because the water and salts had not penetrated very deep the first season. The exception to this was plot 20; it had EC values near the end of the season at the 150 cm depth of 7500-10,000 µSiemens/cm. EC values may have continued to increase on that plot in subsequent years; however, extracts could not be obtained to determine this. Sodium and chlorides were the main contributers to these high EC's (refer to Appendix A--1980 field soil extracts).


As the years of irrigation increased, the EC values below 60 cm for all plots became higher than the EC above 60 cm. This is mainly due to movement of concentrated salt solutions below the area of highest plant root densities. Figure 23 shows the effect that a heavy (7.5 cm) rainfall can have on the soil profile in regard to EC. On August 1, 1981

Figure 23. Effect of a heavy rainfall on the salinity in the soil profile for plot 50, 1981.

the only significant rainfall came between two soil extract sampling dates. The salinity at all depths was reduced even though the soil was saturated below 90 cm. The sodium and chloride values show the same type of pattern indicating that they were major constituents which contributed to the lower EC value. This "decrease" in salinity was due mainly to dilution rather than leaching. Notice in Figure 22 that the nitrate concentration from the 30 and 45 cm depth dropped after that rain, also. Figure 24 shows the EC of the 35G plot in 1981. Apparently the gypsum must have exchanged with Mg and Na to cause higher electrolyte concentrations (8000) in the lower depths. The pattern very closely resembles the chloride concentration for that same plot and year.

The EC in the observation wells varied from 3000-5000 µSiemens/cm over the experiment for 20, 50 and 35 plots. However, the EC on plot 35G ranged from 8800-13,000 µS/cm. The spot check analysis of this water quality showed magnesium and sulfates to be the dominant ions. Magnesium levels were four times higher than the other wells and sulfates were 4-8 times higher than the other wells. Sodium levels were also higher—in the range of 2 to 5 times higher than the other wells. Calcium levels were normal to the levels in the other wells (400-550 ppm). It's interesting to note that the peak of sodium levels in the 35G well came just three days after the application of gypsum for that year. But, only two light rainfalls occurred in the interim time period, hardly sufficient time for the groundwater to be affected by that event. Apparently the calcium in the gypsum is exchanging with magnesium and sodium on the soil exchange complex. It must be occurring





below 1.2 meters, however, because ESP values from soil samples don't seem to reflect the change above that level.

pH and bicarbonates


Figures 25 and 26 show the pH changes in the soil with time and depth for the 50 plot for 1981 and 1982. In 1980 the pH at all depths was in a range of 7.8-8.3 with little difference in pH between depths. In 1981 the pH of the upper 60 cm was much higher than the lower depths. As the season progressed, the pH of the lower depths tended to increase while the pH in the upper 60 cm stayed relatively constant. In 1982 the pH at all depths was very responsive to changes in the pH of the applied irrigation water. The pH at the beginning of the irrigation season, however, had dropped from the previous fall, as would be expected. After irrigation continued with the higher pH water, pH values in the soil tended to equilibrate with that of the irrigation water. Many times those values were over 8.4. This occurred on the other plots also. The high pH of the irrigation water is hazardous to the structure of the soil for two reasons.

First, beginning at a pH of ~8.2, bicarbonates (HCO₃⁻) in the irrigation water, begin to be converted to carbonates(CO₃⁻). The driving force which causes the high pH is the uptake of CO₂ by the algae in the wastewater. The algae need CO₂ for photosynthetic activity and the resultant reactions in the water are

2HCO3⁻≠CO3⁻+H2O+CO2

 $CO3^{=}+H_{2}O \neq 2OH^{-}+CO_{2}$

Consequently, as the algae growth increases, the demand for CO₂ increases and the equilibrium alkalinity situation shifts from bicarbonates



.1891 Changes in pH in the soil with depth and time for plot 50, Figure 25.




Figure 26. Changes in pH in the soil with depth and time for plot 50, 1982.

to carbonates to hydroxide, thus causing an increase in pH. When the carbonate ion concentration increases, if calcium ions are present, the solubility product of CaCO₃ may be exceeded to the point of causing precipitation by the following equation,

Ca⁺⁺+CO₃=≠CaCO₃

This reaction can readily take place between pH levels of 8.3 to 10. Because of this phenomenon, SAR_{iw} is consequently increased because of the removal of the divalent cation. As mentioned earlier, higher SAR waters tend to cause poor structure to the soils on which they are applied. There are some surface waters in the state which have algae blooms such as the above and have higher pH values because of this. The Shadehill Reservoir in northwestern South Dakota is one example.

The second reason the high pH waters are hazardous is due to the suppression of the release of natural Ca⁺⁺ from the soil in the form of CaCO3. Table 15 showed that the solubility of CaCO3 was quite low at pH values above 8.0. When high rates of wastewater are applied after a few years the soil tends to equilibrate with the pH of the irrigation water. Those pH values are usually above 8.0 during the irrigation season as Figures 25 and 26 show. Figure 27 shows the bicarbonate ion concentration in the soil which coincides with the pH values from plot 50, 1982. Notice the drastic reduction in HCO3⁻ concentrations both in the soil and in the water when the pH_{1w} went up sharply.

Drainage Water Quantity

This part of the study was the most difficult aspect to obtain




Figure 27. Bicarbonate ion concentration in the soil with depth and time in plot 50, 1982.

real absolute numbers for. The application of water to the 50 and 35G plots caused water table problems at the end of the 1981 irrigation season. The rates of 50, 89, and 127 cm were in addition to the precipitation received. Figure 28 shows the precipitation departures from the normal for the 3-year period of the experiment. 1981 was an exceptionally dry year and 1982 began with plenty of moisture, therefore, the full range of rainfall patterns was tested with this type of irrigation management. Table 5 gives cumulative irrigation and rainfall plus the total for each plot. As mentioned earlier, above normal rainfall and high water tables prevented the application of the desired amounts of wastewater to the plots for 1982.

The observation wells were used for obtaining water quality samples in addition to recording water levels. When a sample was taken on plot 50, the rate of rise of the water level was constant and very slow (Figure 29). The actual water table level could not be determined from this well because of the slow water movement. When irrigation first began, most of the applied water in excess of ET demands went to filling the pore spaces of the unsaturated soil. As those pore spaces became filled, the ability of the soil to accept more water dwindled and run-off increased. Visual signs of excess water were evident at the end of the second year. Alfalfa plants in the lower areas were yellowing and lost either to poor aeration or disease or both. The situation worsened the next year (1982) and 15-20% of the alfalfa stand was estimated to have been lost to water logging problems.

Based upon the recharge in the well from the recording information, plot 50 in 1981 had a .033 cm/hr water level rise rate. When soil

HURON PRECIP DEPARTURES 1980, 81, 82




Figure 28. Cumulative precipitation departures from the 1941-1970 average normal of 40.6 cm (16 inches) for Huron, S.D. 1980-1982.




Figure 29. Water table fluctuations obtained from observation wells during the 1981 season for the various treatments.

moisture readings were taken on each plot, water first appeared in the neutron access tubes on both plot 50 and 35G on May 26, 1981. Water levels were taken periodically in those tubes and were assumed to be the actual water table level, assuming there was a hydraulic connection from there to the bottom of the observation well (4.5 meters). When the tube was evacuated of water, it always reappeared. At the end of the 1981 season the water level was within 1.1 meters of the surface on plot 50 and 1.2 meters on plot 35G.

Over the '81-'82 winter the water level in the access tube dropped 40 cm, but was still present in the tube after 215 days of no irrigation. Precipitation during that interval was 9.8 cm and the ET was estimated at 12.7 cm. At the end of the 1982 irrigation season, the water level in the neutron access tube on plot 50 was within .67 meters of the soil surface. The run-off appeared to increase as years of irrigation increased. It was evident, then, that the plot was hydraulically overloaded and with continued years of irrigation using this kind of management the run-off would be severe, the water table would reach the surface, and, eventually, the entire crop would be lost.

Over the winter ('81-'82) the level in the well on plot 35G dropped 1.0 meter. The 35G plot started 1982 (April 27) with water in the well at 2.18 meters below the surface but by September 20 the water table had risen to .76 meters below ground level, higher than any previous year.

This occurred even though the total water received on the plot was 11 cm less than in 1981. Again, it appeared that plot 35G was receiving too much moisture to safely allow that annual hydraulic

loading rate. A plow furrow which ran the length of the plot displayed yellowing alfalfa before the harvest of the 4th cutting of alfalfa.

If this loading rate were to continue, problems with a water table and plant losses would soon be evident.

Plot 35 had increases in the water level in the well, also (from 2.77 to 2.09 meters in 1982), however, the water was not as near to the surface as plot 50 and 35G. There may have been more lateral water movement on this plot because of the sand layer below 1 meter, thus, the lower water levels.

Plot 20 had a water table at 5.60 meters below the surface on June 8, 1981. The level began to rise over the irrigation season and peaked out at the last irrigation on September 29, 1982 at 4.7 meters (a rise of .90 meters). The level then began to drop to 5.31 meters beginning a new irrigation season in 1982 (April 27, 1982). From that date the level, again, went up over the irrigation season and was still rising on September 20, 1982 (last records available). On that date the level was 4.57 meters below the surface. For comparison purposes, the 1981 total water (irrigation plus rainfall) on plot 20 was 70 cm while the 1982 total was 75 cm.

If a drainable porosity index of .05 is used to calculate the depth of water leached which would contribute to a 13 cm rise in the water table (from September 29, 1981 to September 20, 1982), then, assuming steady state conditions,

13 cm \times .05 = .65 cm (water lost to leaching)

This means that if .65 cm of water was leached to the groundwaters it would cause a 13 cm rise in the water table. This amount is smaller

than the error which could easily occur in estimating the ET. Therefore, on the basis of this information, it is conceivable that annual applications of 50 cm per year of effluent could be applied to this soil for a 20-25 year time frame without causing any serious water table problems when growing alfalfa in this climate.

SUMMARY AND CONCLUSIONS

The feasibility of using land treatment by irrigation as an alternative for disposal of municipal effluent from Huron's unchlorinated stabilization ponds has two main problems.

The first problem is that the high sodium adsorption ratio in the effluent, which will cause soil dispersion and decreased soil permeability, must be decreased. This can be achieved either of two ways. First, the amount of sodium in the effluent can be reduced. This is not an easy solution. However, if the city is considering land treatment as an alternative, the feasibility of reducing the sodium hazard of the effluent should be investigated. Also, the economic benefit to a community of increased production because of irrigation has to be considered in the cost-benefit analysis. Second, a source of soluble calcium could be mixed with the wastewater just prior to irrigation to reduce sodium adsorption by the soil exchange complex. However, this would increase the total salt load of the effluent. The resultant increase in total salt would require crops considered as moderately tolerant-tolerant to salt.

The second problem is that the hydraulic conductivity of the subsoil is too low to allow leaching fractions higher than 8-10%, yet higher amounts are necessary to control the sodium dispersion hazard. The alternative to this would be to install subsurface drain tile on the land area involved. Drain tile effluent would then have to be discharged to some point.

For the years 1980, 1981 and 1982, no significant differences of

dry matter alfalfa yields were found between 50, 89, and 127 cm of annual applications of wastewater in addition to rainfall. Plant population reductions were beginning to appear on both 50 and 35G because of water table problems. During a dry precipitation year (1981) there was a significant reduction in dry matter alfalfa yield on plot 20 (50 cm effluent).

Average three year leaching fractions of the treatments, based on total water applied (plus rainfall) and evapotranspiration estimates, are 0.085 (treatment 20), 0.30 (treatments 35 and 35G), and 0.45 (treatment 50). However, much of the excess water on the two high rate plots went to filling pore spaces and raising the water table. In addition to this, the highest rate plot (127 cm effluent) had significant amounts of run-off in the latter part of the last two irrigation seasons.

Treatments 20 and 50 had the lowest nitrate levels (0-1.3 ppm) in the observation wells. Treatments 35 and 35G had the highest levels (.1-10.1 ppm) of nitrates appearing in the wells. The plot with the most amount of sand in the subsoil (plot 35) had the highest consistent level of nitrates of any of the plots.

Un-incorporated annual autumn gypsum applications to the soil caused no significant reduction in exchangeable sodium percentage (ESP) over the untreated plots. This was based on two applications to plot 35G and one application to half of plot 20 (plot 20G). However, higher concentrations of sodium and magnesium were evident in the observation well from plot 35G. This indicates that the calcium is exchanging with some sodium and magnesium, keeping it off the exchange complex at lower depths in the soil.

No significant difference was found among treatments for the saturated hydraulic conductivity $(K(\Theta_S))$ of the surface 3 cm of soil. However, dispersion of soil particles from test cores was clearly evident on plot 20 but not on the other treatments.

When comparing treatment soil $K(\Theta_S)$ by laboratory methods, identical pressure heads should be used to arrive at hydraulic conductivity value. Hysteresis, variable channeling, and variations of physical distortions of soil particles do cause the relationship in Darcy's law to deviate from linearity in dealing with large pressure head differences.

There were differences in bulk densities at the 0-3 cm depth between the irrigated soils and the check plot. Significant differences between the check and plot 50 and between the check and plot 20G were found at the .05 level. Bulk densities were higher on treatments 20G and 50 than on the check plot. Plot 35 had significantly higher bulk densities than the check at the .01 level.

Bulk density samples and laboratory saturated hydraulic conductivity cores for testing should total at least 12 to obtain reliable information in determining differences between treatments. Soil variability of these two soil characteristics are usually quite high. Therefore, sampling quantities should increase according to natural variability.

REFERENCES

- 1. "Process Design Manual for Land Treatment of Municipal Wastewater", U.S. Environmental Protection Agency, U.S. Army Corps of Engineers, U.S. Department of Agriculture, October 1977.
- 2. "Suitability of Lagoon Effluents for Irrigation in South Dakota", Completion report, September 1976, OWRT Agreement No. 14-34-0001-6043, Project No. A-052-SDAK.
- 3. Rhoades, J. D. "Leaching Requirements for Exchangeable Sodium Control". Soil Sci. Soc. Amer. Proc. 32:652-656. 1968.
- 4. McNeal, B. L., D. A. Layfield, W. A. Norvell, and J. D. Rhoades. "Factors Influencing Hydraulic Conductivity of Soils in the Presence of Mixed-Salt Solutions", Soil Sci. Soc. Amer. Proc., Vol. 32, 1968.
- 5. Quirk, J. P. and R. K. Schofield, "The Effect of Electrolyte Concentration on Soil Permeability". Journal of Soil Science, Vol. 6, No. 2, 1955.
- 6. McNeal, B. L., and N. T. Coleman, "Effect of Solution Composition on Soil Hydraulic Conductivity", Soil Sci. Soc. Amer. Proc., Vol. 30, 1966.
- 7. Marten, C. G., C. E. Clapp, and W. E. Larson. "Effects of Municipal Wastewater Effluent and Cutting Management on Persistence and Yield of Eight Perennial Forages", Agron. Journ. Vol. 71, July-Aug. 1979, pp. 650-658.
- 8. Clapp, C. E., D. R. Linden, W. E. Larson, C. G. Marten, and J. R. Nylund. "Nitrogen Removal from Municipal Wastewater Effluent by a Crop Irrigation System". Proc. of the 1976 Cornell Agricultural Waste Management Conference.
- 9. Clapp, C. E., A. J. Palazzo, W. E. Larson, G. C. Marten, D. R. Linden. "Uptake of Nutrients by Plants Irrigated with Municipal Wastewater Effluent". Intern. Symposium, Proc. Land Treatment of Wastewater, Hanover, New Hampshire, Aug. 20-25, 1978, Vol. 1.
- Marten, G. C., W. E. Larson, and C. E. Clapp. "Effects of Municipal Wastewater Effluent on Performance and Feed Quality of Maize vs. Reed Canarygrass". Jour. of Envir. Qual. Vol. 9, No. 1, Jan.-Mar. 1980.
- Karlen, D. L., M. L. Vitosh, and R. J. Kunze. "Irrigation of Corn with Simulated Municipal Sewage Effluent". J. Environ. Qual., Vol. 5, No. 3, 1976.

- 12. Adriano, D. C., L. T. Novak, A. E. Erickson, A. R. Wolcott, and B. G. Ellis. "Effect of Long Term Land Disposal by Spray Irrigation of Food Processing Wastes on Some Chemical Properties of the Soil and Subsurface Water". J. Environ. Qual., Vol. 4, no. 2, 1975.
- 13. Bole, J. B., and R. G. Bell. "Land Application of Municipal Sewage Wastewater: Yield and Chemical Composition of Forage Crops". J. Environ. Qual., Vol. 7, no. 2, 1978.
- 14. Ellis, B. G., and A. E. Erickson. 1971. "The Nutrient Content of Drainage Water from Agricultural Land". Res. Bull. No. 31. Michigan State Agric. Exp. Stn., Michigan State Univ., East Lansing, Mich. 16 p.
- 15. U.S. Salinity Laboratory Staff. 1954. <u>Diagnosis and improvement of saline and alkali soils</u>. U.S. Dept. Agr. Handbook 60, 160 p.
- 16. Brosz, D. D. and J. L. Wiersma, "Scheduling Irrigations Using Average Climatic Data". 1970 North Central Region American Society of Agric. Engineers Proc., Paper No. NC70-201.
- 17. Van Schilfgaarde, J. <u>Drainage for Agriculture</u>. Am. Soc. of Agronomy Monograph No. 17, 1974.
- 18. Keren, R. and G. A. O'Connor. "Gypsum Dissolution and Sodic Soil Reclamation as Affected by Water Flow Velocity". Soil Sci. Soc. Amer. Proc., Vol. 46, 1982.
- 19. Black, C. A., D. D. Evans, J. L. White, L. E. Ensminger, and F. E. Clark. <u>Methods of Soil Analysis</u>: Physical and Mineralogical Properties, Including Statistics of Measurement and Sampling. American Society of Agronomy No. 9. 1965.

APPENDIX

Appendix A. Laboratory-determined parameters of field soil water extracts 1980.

Nitrate
pH
Total Phosphate
Ammonia
Sodium
Chloride
Bicarbonate
Electrical Conductivity

SOIL EXTRACT ANALYSIS 1980-1982

NITRATE	(as N)	-noc-		PLOT 50	1980	
DATE	3.0	45	DEPTH 60		120	150
800829 800911 800917 800926 801003	0.10 0.10 12.50 0.07	1.95 1.60 8.00 2.70	0.75	4.90 0.04 0.31 1.14		4.25 2.40 1.76 1.21 0.80
NITRATE	(as N)	-mċċı-		PLOT 35G	1380	
DATE	30	45	DEPTH		120	150
800814 800829 800911 800917 800926	3.90 0.07 0.27 14.55 19.00 3.68 9.00	16.75 1.14 0.37 0.75	0.16 0.05		0.03 0.03 0.03 0.03 0.06 0.02 0.09	29.00 9.00 1.40 0.01 0.02 0.00 0.83
NITRATE	(as N)	-maga-		PLOT 35	1980	
DATE	3)	45	DEPTH 60	(cm) €0	120	150
800820 800814 800829 800911 800917 800926 801003 801008 801023 801104	0.10 0.04 0.01 2.40 0.95 1.21	3.70 0.04 0.03 5.50 1.00	1.10 0.23 0.04 2.04 1.75 1.48	17.50 12.38 0.14 2.20 0.00	13.92 9.62 11.35 2.76	

NITRATE	(as N)	-wac-		PLOT 20	1980	
DATE	30	45	DEPTH(90 	120	150
800820 800814 800829 800911 800917 800926 801003 801008 801023 801104		0.38	0.10	0.00	0.04	14.38 16.12 14.00 14.30 14.50
		PH		PLOT 50	1980	
DATE	30	45	DEPTH (em) 90	120	150
800820 800814 800829 800911 800917 800926 801003 801008 801023 801104	8.15 8.25 8.17 3.31 8.30 8.16 8.30	3.25 8.20 8.26 8.15 8.20 3.28	8.00 8.10 3.02 7.92 8.19 3.50 8.31	8.30 8.06 8.35 8.31 8.19	8.59 8.09 8.31 3.30 8.25 8.18	8.35 8.28 8. 43 8.40 3.36
		РН		PLOT 35G	1980	
DATE	30	45	DEPTH(90	120	150
800820 800814 800829 800911 800917 800926 801003 801008 801023 801104	8.60 7.58 8.23 8.25 3.22 8.51	8.19 8.19 8.12 7.99	8.04 7.32 8.18 8.15 8.09 8.09 8.09	8.05 8.04 8.64 7.61 8.63 8.40 3.65 8.59 8.50	8.38 9.88 8.19 8.39 8.80 8.80	8.13 8.16 8.92 8.90 3.90 8.85 8.80

		ьH		PLOT 35	1980	
DATE	30	45	DEPTH (60	cm) ∂0	120	150
800820 800814	1.90	8.50	8.12			
800829 800911 800917	8.00	7.30	7.89			
800926 801003	8.30	3.10		8.32 8.23	3.23 8.30	
801003 801023 801104	3.01 8.01	8.15	8.03 7.92 7.72	8.30 8.30 8.40	3.22	
		PH		PLOT 20	1980	
DATE			DEPTH (C:T)		
	30	45	60) 0	120	150
800320 800314						
800329		3.04	8.30			
300911 300917						
800926 801003						8.00 3.12
801003						3.12
801023 801104			8.00	8.65 8.70		3.13 3.18
	т-РО4 аз Р -	-mca-		PLOT 50	1980	
DATE	30	45	DEPTH(60	90 90	120	15)
800320	0.03	0.02	0.04	0.30	0.05	0.03
800314 800329	0.14	0.04 0.01	0.09 J.02	0.10	0.03	0.01
800911						
800917 800925	0.03		0.01	0.01		
801003	0.00	0.02		0.01	0.02	0.00
301008		0.02			J. Ú2	0.02
901023 801104	0.02 0.16	0.23			0.00 0.06	0.31

	T-P0)4 as P	-man-	[PLOT 35G	1930	
DATE		30	45	DEPTH(0	em) 30	120	150
300820 800814 800329 800911 300917 300925 801003 801008 801023 801104		0.23 0.09 0.04 	0.05 0.04	0.02	0.00 0.00 0.00 0.01 0.03	J.01 0.01 0.02 0.03 0.03	0.01 0.02
	T-P0	04 as P	-mag-	ĺ	PLOT 35	1930	
DATE		3.)	45	DEPTH(6		120	150
300320 800814 800829 900911 800917 800926 801003 801008 801023 801104		0.12	0.25	0.05 J.00 J.02 J.02 J.02 J.03	0.10	0.02	
	T- P0)4 as P	-m.q.a-	1	PLOT 20	1930	
DATE	_	30	45	DEPTH(0	cm) 90	120	150
300320 800314 800829 300911 800917 800926 801003 801008 801023 801104	-			0.05	0.07		0.00

	NH3 as (1)	- maa -	Ε	PLOT 50	1930	
DATE	3)	45	DEPTH(0		120	150
800320		0.00	0.30	ე.3ე	0.30	0.00
300814	0.40	0.50	0.00			
300829	0.50	0.00	0.30	0.50	0.00	0.00
300911	0.00	0.00	0.00	0.10	0.00	
·800917 800326	0.50	0.00	0.00	0.00		
801003	0.50			0.00		
801003		0.00			0.00	
301023	0.00				J.00	
	0.00		0.00		0.00	
	NIB as V	- man-	[PLOT 35G	1930	
DATE	30	45	DEPTH (c	30 cw)	120	150
300320	0.50			0.10		0.00
800914	2 50		2 20	2.22		2 22
800329	0.50 0.00		0.30	0.20 0.20		
800911 800917	9.00	0.10	0.13).70	0.00	0.30
800325	0.20	0.10	0.20			
301003	0.10	0.00	0.10	3.13	0.00	0.10
801003	0.10		0.00	0.00		0.00
301023	0.20	0.00	0.00	0.00	0.00	0.20
801104		0.50		0.20	0.00	0.00
	NH3 as 4	-mac-	f	PLOT 35	1990	
D.) mn				>		
DATE	3)	45	DEPTH (c	em) 	120	150
300320	0.40	1.00	1.00			
800814						
800929	0.10	1.00	1.20			
300911	0.00	0.00	0.10			
800917						
800926	0.10	0.00		0.50	0.20	
801003	0.10	0.00	0.00	0.00	0.10	
301003 801023	0.00 0.00	0.00	0.00	0.00	0.10 0.00	
301104	0.00		0.00	0.00		

	NH3 33 N	-maa-		PLOT 20	1980	
DATE	3.)	45	DEPIH(30 30	123	150
300320 300814 300829 300911 800917 800926 301003 801008 801023 801104	J.00	1.30	0.60	1.00	0.00	0.00
	SODIUM (Na)	-maa-		PLOT 50	1930	
DATE	30	45	DEPTH (60	cm) 30	120	150
300820 800814 300829 800911 300917 800925 301003 801003 801023 801104	131.0 170.0 99.0 277.0	53.0 118.0 138.0 200.0 261.0 377.0	186.0 93.0 195.0 210.0 297.0 725.0 430.0 1620.0	24.0 10.0 14.0 13.0 26.0 	38.0 35.0 37.0 73.0 51.0 53.0 61.0	21.0 11.0 24.0 42.0 46.0
	SODIUM (Na)	-mac-		PLOT 35G	1930	
DATE	3.)	45	DEPTH (60	30 30	120	150
800820 800814 300829 300911 800917 800926 801003 801003 301023 801104	253.0 231.0 224.0 353.0 433.0 430.0 530.0	224.0 254.0 348.0 109.0 420.0	230.0 279.0 294.0 449.0 423.0 460.0 630.0	45.0 23.0 17.0 35.0 45.0 37.0 47.0 59.0 53.0	30.0 27.0 25.0 26.0 34.0 39.0	61.0 45.0 52.0 59.0 36.0 66.0 52.0

	SODIUM (Na)	-המכי		PLOT 35	1930	
DATE	3.)	45	DEPTH ((cm) 90	120	150
300320 800814	237.0	136.0	147.0			
800829 800911 -800917			167.0 205.0			
800926 801003 801003 301023	 540.0	251.0 640.0	322.0 321.0		28.0 24.0 42.0 150.0	
801104	1039.0		450.0	34.0		
	SODIUM (Na)	-かい畑-		PLOT 20	1980	
DATE	33	45	DEPTH ((cm) 90	120	150
800320 800814						
800829 800911 800917		40.0	25.0 35.0		130.0	
800926 801003						690.0 780.0
801003 301023 801104	12200.0		450.0	137.0 109.0		2360.0 1590.0 1350.0
C	HLORIDE (C1)	-maa-		PLOT 50	1980	
DATE	30	45	DEPTH((cm) 90	120	150
800820 800814	440.0 505.0	435.0 413.0	670.0 340.0	370.0	405.0	430.0
800329 800911 800917	315.0	305.0 525.0	388.0	432.0 600.0	415.0	385.0
800926 801003	739.0	1075.0 710.0	1050.0	650.0 630.0	680.0	623.0
801003 801023 801104	690.0 510.0 540.0	550.0 480.0	1060.0 805.0 1630.0		770.0 760.0 720.0	530.0 570.0

	CHLORIDE (C1)	-ppm-		PLOT 35G	1980	
DATE			DEPTH	(cm)		
	30	45	60	90	120	150
800820			590.0	305.0		
800814 800829			522.0	326.0	340.0	222.0
800911			525.0		412.0	300.0
800917				400.0	575.0	
800926				400.0		
801003				460.0		390.0
801008		7100		520.0 540.0	570 0	430.0
801023 801104		710.0 760.0	1160.0	545.0	570.0 550.0	
301104		700.0		343.0	330.0	400.0
	CHLORIDE (C1)	-mag-		PLOT 35	1930	
DATE			DEPTH	(cm)		
	30	45	60	30	120	150
300320		615.0				
800814						
800829			408.0			
800911			675.0			
800917 800926				475.0		
801003		910.0			505.0	
801003					710.0	
801023	1000.0			420.0	1850.0	
301104			780.0	390.0		
	auroping (all			DI OM 20	1000	
	CHLORIDE (C1)	-ppm-		PLOT 20	1980	
DATE			DEBLY			
	30	45 	60 	90	120	15J
800820						
800914						
300829		715.0	2102		252.2	
800911			2100.0		250.0	
800917 800926						177 =
801003						177.5 180.0
801003						120.0
801023				505.0		145.0
801104			1600.0	635.0		118.0

BICARBONATE	(ECOI)	-גימק-		₽ЬОТ 50	1380	
DATE	3.)	45	DEPTH ((cn) 90	120	150
300820 300314	49.0		117.0	244.0		
800829 800911 800917	33.0	102.0	163.0	177.0	289.0	402.0
800926 801003	120.0	60.0	60.0	96.0 38.0	112.0	123.0
301008 801023 801104	90.0 50.0 120.0	30.0 136.0	30.0 210.0 240.0		103.0 103.0 120.0	124.0
				DIOM 25 C		
BICARSOATE	(HCO3)	-004-		PLOT 35G	1980	
DATE	30	45	DEPTH (120	150
800820 800814	288.0		532.0	535.0		839.0
80032) 800911	77.0	100.0	334.0	432.0 130.0	562.0 403.0	548.0 454.0
300917 800926	36.0	33.0	34.0	635.0 172.0	608.0	
801003	90.0		100.0	130.0		360.0
	30.0 240.0	92.0			293.0	354.0 332.0
801104		100.0		172.0	304.0	303.0
BICARBONATE	(HCD3)	-non-		PLOT 35	1930	
DATE	30	45	DEPTH 60	(cm)	12)	15)
300320	146.0	232.0	101.0			
800814 800329	233.0	244.0	195.0			
300911						
800917				143.0	105.0	
800926 801003	120.0	100.0		120.0	100.0	
301003		60.0	60.0	120.0	100.0	
801023	80.0		74.0	110.0		
801104	120.0		80.0	220.0		

BICARSONATE	(HCO3)	-παα-		PLOT 20	1930	
DATE	30	4 5	DEP r H (0	cm) 90	12)	150
300820 800814 800329 300911 300917 800926 801003 801008 801023 301104		200.0	150.0	235.0		104.0 40.0 12J.0 103.0 140.0
CONDUCTI	VITY -	ns/cm-		PLOT 50	1930	
DATE	3.)	45	ÐЕРТН (60	cm) 90	120	15)
300320 800314 900829 300911 800917 900926 801003 801003 801003			2.9 3.7 2.4 3.6 3.5 3.5 3.7	2.1 2.4 3.1 2.1 2.6	1.3 2.4 2.5 2.9 3.0 2.9	2.3 2.5 1.7 2.5 2.5
CONDUCTI	VITY -	nS/cm-	1	PLOT 35G	1980	
DATE	3)	45	DEPTH(6	cm) 90	120	150
800820 800814 800329 800911 800917 800926 801003 801008 801023	2.1 1.9 3.5 2.3 3.1	3.1 3.4 3.5	3.4 3.5 3.7 3.9 4.4 4.5 4.8	2.5 2.4 2.0 2.6 2.0 1.0 2.2 2.2 2.5	2.5 2.5 2.6 2.3 2.5 2.5	2.3 2.0 2.2 2.1 2.1 2.2 2.2

SOIL EXTRACT ANALYSIS 1980-1932

CONDUCTI	VITY -:n.	3/cm-	وَ	LЭТ 35	1930	
DATE	3.)	45	DEPTH(c	m) 	120	150
800820 800814 800829 300911 800917 800926 301003 801008 801023 801104	2.8 2.6 3.4 5.4 3.5 4.3	3.5	3.1 2.3 3.9 3.1 3.5 3.5	1.3 2.5 2.5 1.7	2.4 2.2 2.7 2.3	
CONDUCTI	VITY -m	S/cm-	ö	LOT 20	1930	
CONDUCTI DATE		S/cm- 45	P DEPTH(C 60		1930	150

Appendix B. Laboratory-determined parameters of field soil water extracts 1981.

Sodium
Chloride
Bicarbonate
Electrical Conductivity
Nitrate
pH
Total Phosphate
Ammonia

	SODIUM (Na)	-mqq-		PLOT 50 A	1981	
DATE			DEPTH ((cm)		
	30	45	60	90	120	150
810615						72.00
810622						82.00
810629						86.00
810708						72.00
810715						115.00
810722						121.00
810728						106.00
810805				660.0	110.0	105.00
810812				540.0	106.0	113.00
810819	470.0		550.0	540.0	140.0	113.00
810827	590.0		640.0	840.0	177.0	150.00
810904	920.0		600.0	650.0	176.0	105.00
810929 811007	570.0			600 0	250.0	92.00
811015	370.0			690.0 360.0	232.0	96.00
811013				300.0	190.0	88.00
	SODIUM (Na)	-mממר-		PLOT 50	1981	
рате	SODIUM (Na)	-mממ-	DEPTH		1981	
DATE	SODIUM (Na)	-nnm- 45	DEPTH 60		1981 120	150
DATE 810615	, ,			(cm)		150 66.00
	30	45 312.0 394.0	60 452.0	90 183.0 220.0	120 51.0 109.0	
810615 810622 810629	30 373.0 630.0 	45 312.0 394.0 540.0	60 452.0	90 183.0 220.0 293.0	120 51.0	66.00
810615 810622 810629 810708	30 373.0 630.0	45 312.0 394.0 540.0 480.0	452.0 468.0	90 183.0 220.0 293.0 342.0	120 51.0 109.0 95.0 90.0	66.00 262.00 234.00 180.00
810615 810622 810629 810708 810715	30 373.0 630.0 531.0	45 312.0 394.0 540.0 480.0 460.0	452.0 468.0	183.0 220.0 293.0 342.0 430.0	120 51.0 109.0 95.0 90.0 71.0	66.00 262.00 234.00
810615 810622 810629 810708 810715 810722	30 373.0 630.0 531.0 570.0	45 312.0 394.0 540.0 480.0 460.0 590.0	452.0 468.0 580.0	183.0 220.0 293.0 342.0 430.0 382.0	120 51.0 109.0 95.0 90.0 71.0 76.0	66.00 262.00 234.00 180.00 158.00 170.00
810615 810622 810629 810708 810715 810722 610728	373.0 630.0 531.0 570.0 650.0	45 312.0 394.0 540.0 480.0 460.0 590.0 650.0	452.0 468.0 580.0	183.0 220.0 293.0 342.0 430.0 382.0 470.0	120 51.0 109.0 95.0 90.0 71.0 76.0 149.0	66.00 262.00 234.00 180.00 158.00 170.00 213.00
810615 810622 810629 810708 810715 810722 610728 810805	30 373.0 630.0 531.0 570.0 650.0 445.0	45 312.0 394.0 540.0 480.0 460.0 590.0 550.0	452.0 468.0 580.0	90 183.0 220.0 293.0 342.0 430.0 382.0 470.0 510.0	120 51.0 109.0 95.0 90.0 71.0 76.0 149.0 193.0	66.00 262.00 234.00 180.00 158.00 170.00 213.00 220.00
810615 810622 810629 810708 810715 810722 610728 810805 310812	30 373.0 630.0 531.0 570.0 650.0 445.0 356.0	45 312.0 394.0 540.0 480.0 460.0 590.0 550.0	452.0 468.0 580.0	90 183.0 220.0 293.0 342.0 430.0 382.0 470.0 510.0 427.0	120 51.0 109.0 95.0 90.0 71.0 76.0 149.0 193.0 186.0	66.00 262.00 234.00 180.00 158.00 170.00 213.00 220.00 251.00
810615 810622 810629 810708 810715 810722 610728 810805 310812 310319	30 373.0 630.0 531.0 570.0 650.0 445.0 356.0 310.0	45 312.0 394.0 540.0 480.0 460.0 590.0 650.0 510.0 429.0	452.0 468.0 580.0	183.0 220.0 293.0 342.0 430.0 382.0 470.0 510.0 427.0 450.0	120 51.0 109.0 95.0 90.0 71.0 76.0 149.0 193.0 186.0 151.0	66.00 262.00 234.00 180.00 158.00 170.00 213.00 220.00 251.00 218.00
810615 810622 810629 810708 810715 810722 610728 810805 310812 310319 310827	30 373.0 630.0 531.0 570.0 650.0 445.0 356.0 310.0 317.0	45 312.0 394.0 540.0 480.0 460.0 590.0 650.0 610.0 429.0 570.0	452.0 468.0 580.0	183.0 220.0 293.0 342.0 430.0 382.0 470.0 510.0 427.0 450.0	120 51.0 109.0 95.0 90.0 71.0 76.0 149.0 193.0 186.0 151.0 149.0	66.00 262.00 234.00 180.00 158.00 170.00 213.00 220.00 251.00 218.00 235.00
810615 810622 810629 810708 810715 810722 610728 810805 810812 810819 310827 810904	30 373.0 630.0 531.0 570.0 650.0 445.0 336.0 310.0 317.0 383.0	45 312.0 394.0 540.0 480.0 460.0 590.0 650.0 510.0 429.0	452.0 468.0 580.0	183.0 220.0 293.0 342.0 430.0 382.0 470.0 510.0 427.0 450.0	120 51.0 109.0 95.0 90.0 71.0 76.0 149.0 193.0 186.0 151.0	66.00 262.00 234.00 180.00 158.00 170.00 213.00 220.00 251.00 218.00
810615 810622 810629 810708 810715 810722 610728 810805 310812 310319 310827 810904 310929	30 373.0 630.0 531.0 570.0 650.0 445.0 336.0 310.0 317.0 383.0 530.0	45 312.0 394.0 540.0 480.0 460.0 590.0 650.0 510.0 429.0 570.0 520.0	452.0 468.0 580.0	183.0 220.0 293.0 342.0 430.0 382.0 470.0 510.0 427.0 450.0	120 51.0 109.0 95.0 90.0 71.0 76.0 149.0 193.0 186.0 151.0 149.0 124.0	66.00 262.00 234.00 180.00 158.00 170.00 213.00 220.00 251.00 218.00 235.00
810615 810622 810629 810708 810715 810722 610728 810805 810812 810819 310827 810904	30 373.0 630.0 531.0 570.0 650.0 445.0 336.0 310.0 317.0 383.0	45 312.0 394.0 540.0 480.0 460.0 590.0 650.0 610.0 429.0 570.0	452.0 468.0 580.0	183.0 220.0 293.0 342.0 430.0 382.0 470.0 510.0 427.0 450.0	120 51.0 109.0 95.0 90.0 71.0 76.0 149.0 193.0 186.0 151.0 149.0	66.00 262.00 234.00 180.00 158.00 170.00 213.00 220.00 251.00 218.00 235.00

SOIL EXTRACT ANALYSIS 1980-1932

	SODIUM (Na)	- i5 i5:4-	1	PLOT 35G	1931	
מתעם			DEPTH (an)		
137.11.	30	4.5	60		120	150
810615		345.0		62.0	26.0	
810622		560.0		76.0	39.0	61.00
810629		435.0		109.0	46.0	
810708		490.0	1430.0	106.0	40.0	
810715	740.0	540.0	900.0	153.0	62.0	
810722		740.0	1090.0		65.0	52.00
810728	560.0	780.0	1030.0	90.0	60.0	77.00
810805	340.0	335.0	610.0	223.0	106.0	54.00
810812 810819		365.0	730.0 720.0	293.0	106.0 102.0	68.00
810819	490.0	530.0	600.0	336.0 520.0	143.0	78.00 71.00
810904	380.0	420.0	540.0	380.0	126.0	70.00
810929	300.0				120.0	86.00
811007			820.0	580.0	148.0	
811015		530.0	580.0	450.0	170.0	80.00
	SODIUM (Na)	-mag-		PLOT 35	1981	
DAME			משמשת (am l		
DATE	30	45	DEPTH (90	120	150
				90	120	130
810615						
810622		740.0	372.0			
OTOGEL		750.0	414.0			
810629		750.0 670.0				
810629 810708	520.0	750.0 670.0 780.0	414.0 560.0			
810629 810708 810715	520.0	750.0 670.0 780.0 540.0	414.0 560.0 			
810629 810708 810715 810722	520.0	750.0 670.0 780.0 540.0	414.0 560.0 			
810629 810708 810715 810722 810728	520.0 700.0	750.0 670.0 780.0 540.0 730.0	414.0 560.0 650.0			
810629 810708 810715 810722 810728 810805	520.0 700.0	750.0 670.0 780.0 540.0 730.0 467.0	414.0 560.0 650.0 470.0			
810629 810708 810715 810722 810728 810805 810812	520.0 700.0	750.0 670.0 780.0 540.0 730.0 467.0	414.0 560.0 650.0 470.0			
810629 810708 810715 810722 810728 810805 810812 810819	520.0 700.0	750.0 670.0 780.0 540.0 730.0 467.0 640.0	414.0 560.0 650.0 470.0 770.0			
810629 810708 810715 810722 810728 810805 810812 810819 810827	520.0 700.0 760.0	750.0 670.0 780.0 540.0 730.0 467.0 640.0 870.0	414.0 560.0 650.0 470.0 770.0 920.0			
810629 810708 810715 810722 810728 810805 810812 810819 810827 810904	520.0 700.0	750.0 670.0 780.0 540.0 730.0 467.0 640.0	414.0 560.0 650.0 470.0 770.0			
810629 810708 810715 810722 810728 810805 810812 810819 810827	520.0 700.0 760.0	750.0 670.0 780.0 540.0 730.0 467.0 640.0 870.0	414.0 560.0 650.0 470.0 770.0 920.0			

	CHLORIDE	(C1)	-mqq-		PLOT 50A	1981	
DATE	,	0.0	4 F	DEPTH (120	150
		30 	4 5	60 	90	120	150
81061	5 -						625.00
81062	2 -						660.00
81062							575.00
81070					,		610.00
81071							630.00
81072							610.00
81072							555.00
81080					940.0	310.0	570.00
81081				013 0	930.0	840.0	570.00
31081		20.0		910.0	925.0	840.0	550.00
81082 81090		25.0 05.0		800.0 580.0	940.0 740.0	370.0 860.0	560.00
31090		15.0		580.0	740.0	350.0	530.00
81100		0.00			1070.0	360.0	460.00
81101					1212.0	940.0	490.00
01101	3				1212.0	340.0	400.00
	CHLCRIDE	(C1)	−ຍຄພ−		PLOT 50	1981	
D y mr.				DEPTH	(cm)		
DATE	-	3 ()	45	60	90	120	150
81061	5 50	0.0	515.0	496.0	635.0	635.0	655.00
81062		LÚ.O	707.0		700.0	690.0	770.00
81062	9 -		750.0	562.0	745.0	720.0	770.00
81070	8 51	0.08	710.0		340.0	830.0	330.00
31071	5 -		710.0		910.0	320.U	830.00
81072		0.0	700.0	1000.0	950.0	790.0	370.00
81072		10.0	900.0		965.Û	718.0	940.00
81080		50.0			970.0	770.0	950.00
81081		95.0	590.0		1030.0	730.0	810.00
81081		40.0	395.0		1035.0	760.0	315.00
81082		45.0	410.0			770.0	820.00
81090		30.0	660.0			790.0	690.00
81092					1115.0		
81100 81101		L5.0 40.0	990.0		1112.0	780.0	
OTTOT	J 15	7 () • ()	770.0			700.0	

SOLE EXTRACT ANALYSIS 1980-1982

	CHLORID	T (C1)	-200-		PLOT 35G	1981	
	OH CORTE	(03.)	7 3.11		1601 553	1702	
DATE				DEPTH	(Cm)		
		30	45	60	90	120	150
81061	- 5		502.0		300.0	705.0	
81062			790.0			860.0	600.00
81062			1000.0		970.0	1040.0	
81070	8		1130.0	1680.0	1060.0	1170.0	
81071	5	800.0	880.0	1145.0	1120.0	1450.0	
81072	2		1130.0	1310.0		1590.0	750.00
81072	8	625.0	1030.0	1100.0	900.0	1715.0	780.00
81080	5	415.0	550.0	780.0	1012.0	1680.0	890.00
81081	2			880.0	880.0	1690.0	950.00
81081	9		450.0	830.0	1170.0	1650.0	930.00
81082	7	465.0	555.0	680.0	920.0	1670.0	955.00
81090	4	450.0	455.0	548.0	762.0	1640.0	1050.00
81092	9						
81100	7		585.0	640.0	970.0	1650.0	
81101	5		750.0	770.0	1010.0	1630.0	1100.00
						,	
	CHLORIE	E (C1)	-mqq-		PLOT 35	1981	
D.1.000	CHLORIC	E (C1)	-mqq-	D.C.D.M.		1981	
DATE	CHLORIC		•	DEPTH	(cm)		150
DATE	CHLORIC	30	-ppm-	DEPTH		1981 120	150
DATE 81061	_	30	4 5		(cm)		150
	- 5 2	30	4 5	60	(cm)		150
81061	- 5 2	30	45 805.0	60 690.0	(cm)		150
81061 81062	- 5 2 9	30 700.0	45 805.0 935.0	60 690.0 805.0	(cm)		150
81061 81062 81062	- 5 2 9 8	30 700.0	45 805.0 935.0 1090.0	60 690.0 805.0 965.0	(cm)		150
81061 81062 81062 81070	- 5 2 9 8 5	30 700.0	45 805.0 935.0 1090.0 1020.0 675.0	60 690.0 805.0 965.0	(cm)		150
81061 81062 81062 81070 81071 81072 81072	5 2 9 8 5 2 8	30 700.0	45 805.0 935.0 1090.0 1020.0 675.0	60 690.0 805.0 965.0	(cm)		150
81061 81062 81062 81070 81071 81072	5 2 9 8 5 2 8	30 700.0	45 805.0 935.0 1090.0 1020.0 675.0	60 690.0 805.0 965.0	(cm)		150
81061 81062 81062 81070 81071 81072 81072 81080 81081	5 2 9 8 5 2 8 5 2	30 700.0 100.0	45 805.0 935.0 1090.0 1020.0 675.0 765.0 880.0	60 690.0 805.0 965.0 1100.0 1220.0	(cm)		
81061 81062 81062 81070 81071 81072 81080 81081 81081	5 2 9 8 5 2 8 5 2	30 700.0 100.0	45 805.0 935.0 1090.0 1020.0 675.0 765.0 880.0 865.0	60 690.0 805.0 965.0 1100.0 1220.0	90 	120	
81061 81062 81062 81070 81071 81072 81080 81081 81081 81082	5 2 9 8 5 2 8 5 2 9	30 700.0 100.0 930.0	45 805.0 935.0 1090.0 1020.0 675.0 765.0 880.0 865.0 780.0	60 690.0 805.0 965.0 1100.0 1220.0 1020.0 1080.0	90 	120	
81061 81062 81062 81070 81071 81072 81080 81081 81081 81082 81090	5 2 9 8 5 2 8 5 2 9 7	30 700.0 100.0	45 805.0 935.0 1090.0 1020.0 675.0 765.0 880.0 865.0	60 690.0 805.0 965.0 1100.0 1220.0	90 	120	
81061 81062 81062 81070 81071 81072 81080 81081 81082 81092	5 2 9 8 5 2 8 5 2 9 7 4	30 700.0 100.0 930.0	45 805.0 935.0 1090.0 1020.0 675.0 765.0 880.0 865.0 780.0	60 690.0 805.0 965.0 1100.0 1220.0 1020.0 1080.0	90 	120	
81061 81062 81062 81070 81071 81072 81080 81081 81081 81082 81090	5 2 9 8 5 2 8 5 2 9 7 4 9	30 700.0 100.0 930.0	45 805.0 935.0 1090.0 1020.0 675.0 765.0 880.0 865.0 780.0	60 690.0 805.0 965.0 1100.0 1220.0 1020.0 1080.0	90 	120	

SOIL EXTRACT ANALYSIS 1980-1982

BICARBONATE	(HCO3)	-mqq-		PLOT 50A	198 1	
DATE	30	45	DEPTH (60	30 cm)	120	150
810615 810622 810629 810708 810715 810722 810728 810805 910812 810819 810827 810929 811007 811015	317.0 231.0 122.0		354.0 171.0 146.0	610.0 494.0 559.0 659.0 671.0	726.0 396.0 610.0 647.0 494.0 379.0 671.0 403.0	800.00 112.00 910.00 659.00 391.00 708.00 921.00 927.00 952.00 976.00 330.00 932.00 775.00 586.00
BICARSONATE	(HCO3)	-ngm-		PLOT 50	1931	
DATE	30	45	DEPTH((cm) 90	120	150
810615 810622 810629 810708 810715 810722 810728 810805 810812 810819 810827 810904 810929 811007 811015	244.0 234.0 146.0 195.0 183.0 189.0 207.0 232.0 231.0 165.0 159.0 232.0	190.0 176.0 127.0 232.0 146.0 145.0 165.0 116.0 214.0 146.0 159.0	229.0 190.0 146.0	512.0 537.0 517.0 366.0 427.0 464.0 427.0 231.0 451.0 476.0 134.0	566.0 571.0 576.0 451.0 537.0 438.0 525.0 438.0 354.0 350.0 256.0 183.0	664.00 664.00 578.00 537.00 586.00 390.00 708.00 726.00 665.00 769.00 695.00

SOIL EXTRACT ANALYSIS 1980-1982

BICARBONATE	(HCO3)	-ນວິພ-		PLOT 35G	1981	
DATE			DEPTH	(cm)		
DFIL	30	45	50	90	120	150
810615		300.0		649.0	771.0	
810622		293.0		822.0	839.0	717.0
310629		238.0		917.0	986.0	
810708		220.0	354.0	952.0	927.0	
810715	220.0	451.0	439.0	927.0	927.0	
810722		329.0	299.0		354.0	927.0
810728	232.0	365.0	427.0	427.0	695.0	1013.0
310305	231.0	598.0	476.0	360.0	366.0	1031.0
810312			244.0	703.0	366.0	1037.0
810819		439.0	403.0	805.0	610.0	1013.0
810827	220.0	354.0	403.0	595.0	703.0	1000.0
810904	263.0	342.0	415.0	522.0	573.0	988.0
810929					622.0	847.0
811007		220.0	232.0			
811015		183.0	366.0	708.0	366.0	1025.0
BICARBONATE	(HCO3)	-maq-		PLOT 35	1981	
ר א תור:			DEPTH	(cm)		
DATE	30	45	60	90	120	150
						150
810615	5	358.0	283.0			
810622		337.0	251.0			
810629	185.0	342.0	264.0			
310708		171.0				
810715		317.0				
810722						
810728	116.0	432.0	171.0			
810805		354.0	263.0			
310312		266.0	105.0			
810819	171.0	356.0	195.0			
810827	152.0	342.0	244.0			
810904	153.0	195.0	153.0			
810929						
811007						
811015						

SOIL EXTRACT ANALYSIS 1980-1982

CONDUCTI	VITY -m	S/cm-	P	LOT 50A	1981	
DATE	30	45		90	120	150
810615 810622 810629 810708 810715 810722 810728 810805 810812 810819 810827 810904 810929 811007 811015	3.23.22.8		5.3 4.0 3.7	5.3 5.5 5.6 5.8 5.1	4.5 4.3 4.6 4.3 4.5 4.7 4.5	3.2 3.3 3.2 3.3 3.5 3.2 4.1 3.6 3.7 3.7 3.6 3.3 3.3
CONDUCTI	m- YTIVI	S/cm-	P	LOT 50	1981	
DATE	30	4 غ	DEPTH(c		120	150
810615					120	150

SOIL EXTRACT ANALYSIS 1980-1982

CON	DUCTIVITY	-mS/cm-		PLOT 35G	1981	
DATE	30	45	DEPTH(60	(cm) 90	120	150
810615 810622 810629 810708 810715 810722 810728 810805 810812 810819 810827 810904 810929 811007 811015	4 2 2 2 2 2	3.3	5.4 5.6 5.4 4.7 4.2	4.0 4.6 5.2 5.7 4.2 5.7 4.9 6.8 5.4 4.9	3.4 4.2 4.5 5.1 5.9 6.4 7.5 8.2 7.8 8.2 7.4 7.1	3.1 4.0 4.3 4.9 5.3 5.1 5.5 5.4 5.0
CON	DUCTIVITY	/ -ms/cm-		PLOT 35	1981	
DATE	30	45	DEPTH 60	(cm) 90	120	150
810615 810622 810629 810708 810715 810722 810728 810805 810812 810819 810827 810904 810929 811007 811015	3 4 4	4.0 4.3 4.8 4.7 5.0 4.0 3.1 5.0 5.0 7.0 7.0 7.0 7.0 7.0 7.0 7.0 7	3.6 3.5 4.4 6.4 5.8 			

SOIL EXTRACT ANALYSIS 1980-1982

NITRATE	(as N)	-mao-		PLOT 50A	1981	
DATE	30	45	оертн (60	cm) 90	120	150
810615 810622 810629 810708 810715 810722 810728 310805 810812 810819 810827 810904 810929 811007 811015	 4.40 0.10 0.09 3.12	4 3	2.70 2.33 2.85	0.34 0.14 0.05 0.04 0.77	129 0.06 0.04 0.04 0.02 0.02 0.02 0.03 0.05	1.25 1.09 1.55 3.52 1.06 0.91 1.14 0.59 0.65 0.41 0.45 0.79 0.12 0.63 0.53
VITRATE	(as N)	-¤~m- 45	DЕРТН (60	PLOT 50 cm)	1981 120	150
810615 810622 810623 810703 810715 910722 810723 810805 810812 810819 810827 810904 810929 811007 811015	1.53 23.53 64.00 47.30 32.30 10.00 6.50 6.53 3.75 7.12 6.25 2.72 2.42	11.38 63.00 147.50 53.75 20.50 24.75 23.00 3.90 0.94 3.02 2.34 3.30	0.67 51.50 5.20 	0.04 0.04 1.32 24.75 43.00 22.00 20.25 23.25 22.75 11.12	0.16 0.06 0.07 0.26 0.05 0.13 0.10 0.57 0.35 0.42 0.14 0.07 0.12	150 0.02 0.04 0.04 0.06 0.04 0.06 0.04 0.06 0.04

SOIL EXTRACT ANALYSIS 1980-1982

NITRATE	(as 11)	−moa-	I	PLOT 35G	1981	
DATE	3:0	45	DEPTH (0	⊃m) 30	120	150
810615 810622 810629 810703 810715 810722 810723 810805 810812 810819 910827 310904 810929 811007 811015	10.52 16.50 9.75 1.33 3.70	0.14 0.09 0.17 1.50 13.75 3.75 5.00 2.60 3.70 2.30 4.35 2.50 2.42	0.60 10.75 5.35 5.00 3.60 1.30 2.65 6.70 10.12	0.04 0.05 0.05 0.05 0.14 0.49 0.86 0.06 0.10 0.04 0.15 0.05	0.03 0.05 0.02 0.03 0.06 0.04 0.05 0.04 0.05 0.06 0.02 0.04 0.05	2.05 0.45 0.26 0.19 0.27 0.13 0.13 0.06 0.22
NITRATE	(as N)	-m.q.c-	1	PLOT 35	1931	
NITRATE	(as N)	45	ОЕРТН (с 60		1931 120	150
			DEPTH (c	cm)		150

		РП	Ę	LOI 50A	1981	
DATE	30	45	DEPTH (C	m) 90	120'	150
810615 810622 810629 810708 810715 810722 810728 810805 810812 810819 810827 810929 811007 811015	6.29 8.13 7.80		7.75 7.99 8.20	7.48 7.48 7.82 7.15 7.45 7.41	 8.21 8.18 7.73 7.56 7.99 7.60 7.89 8.19	8.00 7.90 7.50 8.08 7.25 8.05 8.00 7.70 7.65 7.45 7.50 8.23 8.40 8.88
		PH	F	PLOT 50	1981	
DATE	30	45	DEPTH(c	m) 90	120	150
810615 810622 810629 810708 810715 810722 810723 810805 810812 910819 810827 810904 810929 811007 811015	8.31 8.28 8.48 8.28 8.30 8.40 3.50 8.42 8.25 8.22 8.51 8.32 8.35	8.10 8.00 8.01 8.15 7.95 8.13 8.15 8.30 8.22 8.23 8.45	7.91 8.23 8.42 	7.80 7.30 7.05 7.58 7.20 7.32 7.49 7.81 7.61 7.49 8.10	7.30 7.28 7.21 7.77 7.62 7.68 7.70 7.81 7.91 3.10 7.33 8.22	7.35 7.40 7.20 7.60 7.51 7.89 7.58 7.37 7.70 7.35 7.48 8.03

SOIL EXTRACT ANALYSIS 1980-1982

		РН	E	PLOT 35G	1981	
DATE	3:)	45	DEPTH(C	em) 90	120	150
810615 810622 810629 810708 810715 810722 810728 810805 810812 810819 810827 810904 810929 811007 811015	8.38 8.38 3.31 8.45 3.33 3.79	7.60 7.82 7.75 7.22 7.31 7.75 7.60 7.53 7.85 7.82 8.30 8.09 8.20	7.65 7.12 8.05 7.70 7.59 7.94 7.85 7.60 8.00	7.56 7.71 6.88 7.78 7.22 8.42 7.20 7.69 7.11 7.37 8.05 7.78 7.80	7.71 8.15 7.91 8.08 8.38 8.08 8.26 8.00 8.21 7.98 7.95 3.05 7.92 8.38 8.35	3.30 7.88 7.68 7.66 7.60 7.44 3.08 8.12 8.05
		БH	Ė	ъът 35	1981	
DATE	30	45	DEPTH(c	em) 90	120	150
810615 810622 810629 810708 810715 810722 810728 810805 810812 810819 810827 810904 810929 811007 811015	8.20 8.20 8.08 8.30 8.19	7.54 7.92 7.65 7.78 7.75 7.71 7.80 7.86 7.78 8.25	7.58 7.87 7.92 8.00 7.92 8.08 7.81 8.25			

SOIL EXTRACT ANALYSIS 1980-1982

T-F04-F	(HCO3)	-pnm-		PLOT 50A	1981	
DATE	3.)	4.5	DЕРТН (60		120	150
810615 810622 810629 810708 810715 810722 810728 810805 810812 810819 810827 810904 810929 811007 811015	0.15			0.15	0.25	0.03 0.02 0.02 0.05 0.02 0.01 0.05 0.01
T - P	04 as P	-ppm-		PLOT 50	1981	
DATE	30	45	DEPTH (60	90	120	150
810615 810622 310629 810708 810715 810722 810728 810805 810812 810819 810827 810904 810929 811007 811015	0.23 0.14 0.21 0.14 0.04 0.05	0.03 0.05 0.02	0.02	0.04 0.05 0.02 0.02 0.08 0.05 0.04 0.04	0.01 0.10 0.01 0.04 0.02 0.03 0.02 0.02	0.07 0.09 0.03 0.04 0.04 0.03 0.04 0.02

	T-PO4 as P	-mqq-	P	LOT 35G	1981	
DATE			DEPTH (c	m)		
,	30	45	60	90	120	150
810615		0.04			0.01	
810622		0.02		0.06	0.02	0.05
810629		0.02		0.02	0.05	
810708		0.04	0.06	0.02	0.07	
810715	0.20	0.07	0.12	0.11	0.21	
810722		0.03	0.02		0.13	0.02
810728	0.06	0.02	0.02	0.03	0.03	0.04
810805	0.03	0.06	0.02	0.02	0.01	0.03
810812						0.01
810819				0.02		
810827						
810904	0.12					
810929		3			0.01	0.02
811007				0.01		
811015				0.03		
	T-PO4 as P	-ppm-	P	LOT 35	1981	
DATE	T-PO4 as P	-mgg-	P DEPTH (c		1981	
DATE	T-PO4 as P	-ppm- 45			1981 120	150
DATE 810615			DEPTH (c	m)		150
810615 810622	30	45 0.03 0.02	DEPTH (C 60 	m)		150
810615	30	45 0.03 0.02 0.01	DEPTH (C 60 0.03	m)		150
810615 810622 810629 810708	30	45 0.03 0.02 0.01 0.04	DEPTH (C 60 	m)		150
810615 810622 810629 810708 810715	30 0.09 	45 0.03 0.02 0.01	DEPTH (C 60 	m)		150
810615 810622 810629 810708 810715 810722	30 0.09 	45 0.03 0.02 0.01 0.04 0.02	DEPTH (0 60 0.03 0.04 	m)		150
810615 810622 810629 810708 810715 810722 810728	30 0.09 	45 0.03 0.02 0.01 0.04 0.02	DEPTH (0 60 0.03 0.04 0.11	m)		150
810615 810622 810629 810708 810715 810722	30 0.09 	45 0.03 0.02 0.01 0.04 0.02	DEPTH (0 60 0.03 0.04 	m)		150
810615 810622 810629 810708 810715 810722 810728 810805 810812	30 0.09 0.05	45 0.03 0.02 0.01 0.04 0.02 0.02	DEPTH (0 60 0.03 0.04 0.11	m)		150
810615 810622 810629 810708 810715 810722 810728 810805 810812 810819	30 0.09 0.05	45 0.03 0.02 0.01 0.04 0.02 0.02	DEPTH (c 60 0.03 0.04 0.11 0.01	m)	120	
810615 810622 810629 810708 810715 810722 810728 810805 810812 810819 810327	30 0.09 0.05	45 0.03 0.02 0.01 0.04 0.02 0.02	DEPTH (0 60 0.03 0.04 0.11 0.01	90 	120	
810615 810622 810629 810708 810715 810722 810728 810805 810812 810819 810327 810904	30 0.09 0.05	45 0.03 0.02 0.01 0.04 0.02 0.02	DEPTH (0 60 0.03 0.04 0.11 0.01	90 	120	
810615 810622 810629 810708 810715 810722 810728 810805 910812 810819 810327 910304 810929	30 0.09 0.05	45 0.03 0.02 0.01 0.04 0.02 0.02	DEPTH (0 60 0.03 0.04 0.11 0.01	90 	120	
810615 810622 810629 810708 810715 810722 810728 810805 810812 810819 810327 810904	30 0.09 0.05	45 0.03 0.02 0.01 0.04 0.02 0.02	DEPTH (0 60 0.03 0.04 0.11 0.01	90 	120	

SOIL EXTRACT ANALYSIS 1980-1982

		NH3	-mgg-		PLOT 50A	1981	
DATE				DEPTH (cm)		
	4	30	45	60	90	120	150
810615							
810622							
810629							0.30
810708							0.20
810715							1.40
810722							
810728							0.60
810805					1.00	2.20	0.10
810812					0.10	0.10	
810819 810827		1.10		$1.10 \\ 1.00$	0.10		
810927		1.50		1.10	0.10	0.10	0.90
810929		1.50			0.10	0.00	0.30
811007		0.80					
811015						0.50	0.30
		ин3	-wda-		PLOT 50	1981	
DATE				DEPTH (cm)		
	_	30	45	60	90	120	150
810615		1.90	0.80	1.10	0.20	1.10	0.40
810622		0.50	0.30		0.30	0.30	1.40
810629			0.20	0.30	0.20	0.20	0.30
810708		0.30	0.50			0.30	0.70
810715			3.00		0.30	0.80	1.40
810722		0.50	0.60	0.60	0.50	0.50	1.20
810728		2.40	1.80			0.60	1.00
810805		0.30			0.20	0.70	1.40
810812		0.10	0.60		0.10	0.10	3.00
810819		0.10	0.04		0.10	0.10	0.60
810827 810904		0.20	0.20			0.20 0.10	1.20
810904		0.10	0.10			0.10	0.80
811007					0.80		
811015		0.20				0.70	
~ ~ ~ ~ ~ ~ ~		0 1 2 0				0.,0	

	ин3	-maga-	F	PLOT 35G	1981	
DATE	30	45	DEPTH(c	em) 90	120	150
810615 810622 810629 810708 810715 810722 810728 810805 810812 810819 810827 810929 811007 811015	1.00 1.20 0.30 0.30 0.60	0.40 0.30 0.20 0.20 0.30 0.60 0.30 0.60 0.70 0.40	0.40 1.00 0.80 0.10 0.60 0.10 0.30 0.30 0.30	0.10 0.30 0.20 2.20 0.30 0.10 0.10 0.30 0.60	0.30 0.40 0.20 1.70 0.10 0.30 0.40 0.10	1.00 0.50 1.30 0.20 0.30
	ин3	-mqq-	É	PLOT 35	1981	
DATE	30	45	DEPTH(c	em) 90	120	150
810615 810622 810629 810708 810715 810722 810728 810805 810812 810819 810827 810904 810929	2.00 3.00 1.70	0.20 0.40 0.20 0.30 1.20 1.90 0.50 0.20 0.30 0.10	0.70 0.20 1.00 0.90 0.20 0.40 0.30			
811007 811015						

Appendix C. Laboratory-determined parameters of field soil water extracts 1982.

Sodium
Chloride
Bicarbonate
Electrical Conductivity
Nitrate
p
Total Phosphates
Ammonia

	SODIUM (Na)	-mqq-		PLOT 50A	1982	
DATE	_ 30	45	DEPTH(cm) 90	120	150
820619 820625 820630 820703 820725 820804 820810 820820 820825	332.0 233.0 353.0 392.0 426.0 425.0 440.0		409.0 450.0 630.0 510.0 530.0 370.0	1010.0 870.0 650.0 590.0 590.0 540.0 460.0	185.0 218.0 174.0 307.0 330.0 343.0 367.0 332.0 404.0	133.0 71.0 103.0 103.0 103.0 103.0 101.0 99.0
020023	SODIUM (Na)	-mqq-		PLOT 50	1982	<i>,,,</i> ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
DATE	30	45	DEPTH(90	120	150
820618 820625 820630 820708 820725 820804 820810 820820 820825	400.0 263.0 239.0 363.0 454.0 500.0 360.0 410.0	410.0 366.0 468.0 500.0 630.0	394.0 420.0 560.0 450.0 390.0	121.0 540.0 460.0 530.0 550.0 480.0 500.0 520.0	204.0 268.0 271.0 294.0 342.0 266.0 280.0 333.0	127.0 167.0 217.0 222.0 365.0 375.0
	SODIUM (Na)	-maga-		PLOT 35G	1982	
DATE	30	45	DEPTH(60	cm)	120	150
820618 820625 820630 820708 820725 820804 820810 820820 820825	303.0 342.0 	375.0 400.0 390.0	440.0 510.0 353.0 327.0 410.0 380.0	510.0 440.0 530.0 431.0 390.0 435.0	258.0 301.0 272.0 322.0 251.0 318.0 319.0	124.0 133.0 122.0 114.0 86.0 134.0 160.0 185.0

	SODIU	M (Na)	-mqq-		PLOT 35	1982	
DATE		30	45	DEPTH 60	(cm) 90	120	159
	-						
820518			560.0				
820625			400.0	610.0			
820630 820708			520.0	600.0			
820725		403.0		540.0		315.0	
820804			550.0	540.0			
820810			600.0			293.0	
820820		620.0	520.0	610.0		331.0	
820825			700.0	710.0		378.0	
_							
С	HLORID	E (C1)	-mga-		PLOT 50A	1982	
DATE				DEPTH	(cm)		
		30	45	60	90	120	150
020610	-					065 0	
820618 820625		200.0			1500.0	965.0 1010.0	407.0
820630		260.0			905.0	2180.0	430.0
820708		360.0		380.0	430.0	1065.0	430.0
820725		380.0		420.0	440.0	1010.0	450.0
820804		390.0		530.0	495.0	846.0	410.0
820810		395.0		490.0	450.0	745.0	420.0
820820		470.0		495.0	400.0	740.0	465.0
820825		500.0		462.0	335.0	670.0	440.0
С	HLORIC	E (C1)	-mqq-		PLOT 50	1982	
DATE				DEPTH	(cm)		
		30	45	60	90	120	150
020610	-	AGE 0			355.0	765.0	0.75 0
820618 820625		465.0 120.0			865.0	800.0	875.0 770.0
820630							770.0
820708		210.0	450.0	260.0	505.0	820.0	710.0
820725		380.0	325.0	375.0	705.0	940.0	760.0
820304		450.0	530.0	425.0	540.0	895.0	605.0
820810		580.0		400.0	510.0	820.0	610.0
820820		430.0	580.0	430.0	510.0	860.0	
820825		480.0	565.0	415.0	520.0	875.0	

CHLORIDE (C1) -onn-				PLOT 35G	1932	
DATE			рергн	(cm)		
	30	45	60	€000	120	150
320618						
320625		230.0	360.0	1115.0		370.0
820530			277)		930.0	990.0
320703 320725	295.U		275.0	375.0	1050.0	955.0 990.0
320723	200.0		230.0		960.0	920.0
320810				310.0		375.0
820820	237.0	378.0		725.0	1025.0	330.0
320325		375.0		670.0		765.0
QUI ODĪ	DE (C1)	- 0.0.7		РЬОТ 35	1222	
SUPORT	DE (CI)	_(J,J'((-		FLO1 33	1932	
DATE			DEPTH	(cm)		
	3)	45 	60	9 0	120	150
320613	§	290.0				
320625		70.J	379.0			
820630			222.2			
820708 820725	140.0	200.0 455.0	200.0 298.0		1550.0	
820804	110.0	440.0	410.0			
820810		440.0			1390.0	
820820	515.0	400.0	505.0		1410.0	
320825		455.0	385.0		1420.0	1111
BICARBONATE	(HCO3)	-mca-		PLOT 50A	1982	
	,					
DATE	2.0	4 -	DEPTH		1.2.2	
	30	45 	50 	90 	120	150
820618					515.0	
820525	216.0			30.0	248.0	475.U
820630	172.0		270.3	144.0	343.0	533.0
820703 820725	210.0 200.0		252.0 420.0	525.0 736.0	230.0	630.0
820804	145.0		170.0	280.0	590.0 110.0	792.0 330.0
820810	210.0		330.0	720.0	405.0	420.0
320820	130.0		250.0	460.0	380.0	400.0
820825	220.0		240.0	440.0	260.0	350.0

SOIL EXTRACT ANALYSIS 1980-1982

BICARBONATE	(HCO3)	-mqq-		PLOT 50	1982	
DATE			DEPTH	(cm)		
	30	45	60	90	120	150
820618	140.0			72.0	388.0	468.0
820625	146.0			248.0	336.0	382.0
820630 820708	153.0	150.0	402.0	344.0	350.0	372.0
820725	192.0	200.0	435.0	460.0	420.0	544.0
820804	120.0	180.0	140.0	135.0	110.0	150.0
820810	230.0				460.0	180.0
8 20 8 20 8 20 8 25		260.0		230.0 140.0	320.0 200.0	
020025	100.0	100.0	200.0	140.0	200.0	
BICARBONATE	(HCO3)	-maa-		PLOT 35G	1982	
DATE			DEPTH	(cm)		
	30	45	60	90	120	150
820618						
820625		208.0	120.0	140.0		556.0
820630			155.0		200.0	672.0
820708 820725	272.0		155.0 380.0	640.0	428.0 635.0	622.0 664.0
820804	250.0		200.0	120.0	220.0	140.0
820810				620.0	420.0	650.0
820820	230.0	240.0		440.0	350.0	460.0
820825		220.0	170.0	180.0	160.0	260.0
BICARBONATE	(HCO3)	-ppm-		PLOT 35	1982	
DAME				(cm)		
DATE	30	45	DEPTH 60	90	120	150
820618		468.0				
820625		344.0	144.0			
820630		275 0				
820708	476.0	375.0 496.0	210.0 420.0		160.0	
820725 820804	470.0	270.0	290.0		160.0	
820810		240.0			90.0	
820820	280.0	280.0	200.0		100.0	
820825		400.0	260.0		100.0	

CONDUCT	rivity -m	S/cm-	1	PLOT 50A	1982	
DATE			DEPTH (cm)		
	30	45	60	90	120	150
820 6 18	1 0			7.1	4.8	2 2
820625 820630	1.9 2.0			6.2	5.2	3.3
820708	2.3		2.9	4.6	5.7	3.3
8 20 7 25	2.4		2.3	3.9	5.2	3.3
820804	3.0		3.9	4.4	5.4	3.6
820810	3.0		3.9	4.0	5.1	3.6
820820	2.7		3.3	4.0 3.6 2.6	4.5	3.1
820825	2.8		2.0	2.0	3.3	2.7
CONDUCT	CIVITY -m	S/cm-	1	PLOT 50	1982	
DATE			DEPTH (cm)		
DITTE	30	45	60	90	120	150
820618	3.0				4.2	
820625	1.6			5.0	4.5	
820630 820708	1.9			2 7		2 0
820725		2.9	2.7	3.7 4.5	4.5	3.0 4.1
820804		3.2	3.3	4.1	4.7	3.9
820810	4.0			4.1		
820820	3.0		3.0		4.7	
820825	2.5	2.8	2.5	2.9	3.9	
CONDUCT	rivity -m	S/cm-		PLOT 35G	1982	
DATE			DEPTH (cm)		
	30	45	60	90	120	150
820618						
820625		3.1	3.2	5.1		5.5
820630			2 0		4.9	5.9
820708 820725	2.5		2.9 2.5	5.0	5.5 5.0	5.8 5 .4
820804	1.8		2.0	5.4	6.0	5.3
820810				6.0	6.6	5.9
820820	1.8	2.7	2.4	4.7	5.5	5.2
820825		2.8	2.5	3.7	4.6	4.1

CONDUCTIVITY -mS/cm- PLOT 35 1982								
DATE	30	45	DEPTH(em) 90	120	150		
820618 820625 820630 820708 820725 820804 820810 820820 820825	2.3	2.4	2.5		5.7 7.1 6.4 5.1			
NITRATE	(as N)	-maga-		PLOT 50A	1982			
DATE	3 J	45	DEPTH(cm) 90	120	150		
	13.40 5.50 1.25 0.04 0.06 0.06 0.05		5.65 0.05 0.24 0.03 0.05	0.16 0.04	1.82 1.68 0.92 0.45 0.43 0.09 0.01	1.76 1.50 2.20 2.00 1.75 1.70 1.65		
NITRATE	(as N)	-wċċ-		PLOT 50	1982			
DATE	30	45	DEPTH(cm) 90	120	150		
820618 820625 820630 820708 820725 820804 820810 820820 820825	8.75 36.10 18.60 2.65 0.54 0.62 0.72 0.46	4.75 2.00 1.65 0.32 0.53	4.12 2.13 0.82 0.66 0.61 0.40	6.40 35.90 12.20 4.85 0.03 0.04 0.02	1.98 2.35 1.30 0.46 0.20 0.03 0.01 0.02	3.28 2.25 5.48 1.14 0.10 0.03		

NITRATE	(as N)	-maq-		PLOT 35G	1982	
DATE	30	45	DEPTH(cm) 90	120	150
820618 820625 820630 820708 820725 820804 820810 820820 820825	20.60	13.20 12.80 3.75	1.78 1.75 1.93 3.16 3.58 3.20	0.13 0.01	0.21 0.10 0.06	0.98 1.80 1.31 0.65 0.60
NITRATE	(as N)	-maa-		PLOT 35	1982	
DATE	30	45	DEPTH ((cm) 90	120	150
820618 820625 820630 820708 820725 820804 820810 820820 820825	2.45	15.50 21.20 13.00 3.75 1.53 1.28 0.79 0.96	5.42 5.00 3.10 1.45 0.65 1.10		0.22 0.06 0.07 0.05	
		PH		PLOT 50 A	1982	
DATE	30	45	DEPTH ((cm) 90	120	150
820618 820625 820630 820708 820725 820804 820810 820820 820825	8.50 8.54 8.40 8.27 8.60 8.58 8.50 8.51		8.05 7.81 8.55 8.19 8.49 8.61	7.88 7.49 7.51 7.30 8.85 8.02 8.60 8.99	7.70 7.90 7.58 7.61 7.53 8.38 8.09 8.15 8.60	8.70 8.27 8.14 8.00 9.00 8.80 8.85 9.02

		PH		PLOT 50	1982	
DATE	30	45	DE PTH 60	(cm) 90	120	150
820810 820820	8.50 3.48	8.61 8.45	8.56 7.99 8.42	8.19 8.20	7.85 8.02	7.30 7.69 7.60 7.70 8.52 8.60
820825	3.48	8.42 PH				
DATE	30	45	DEP'IH	(cm) 90	120	150
820618 820625 820630 820708 820725 820804 820810 820820 820825	8.29 8.72 		8.30 8.33 7.98 8.70 8.52 8.58	7.30 8.35 7.60 8.01 8.49	8.42 8.36 7.89 8.52 8.21 8.48 8.72	7.88 8.08 7.48 7.85 8.46 7.82 8.30 8.62
		ья		PLOT 35	1982	
DATE	30	45	DEPTH 60	(cm) 90	120	150
820618 820625 820630 820708 820725 820804 820810 820820	8.70 8.70	7.70 8.92 8.51 7.90 8.78 8.61 8.78	8.31 8.80 8.41 8.89 8.79		7.83 8.00 8.13	
	820618 820625 820630 820708 820725 820804 820820 820825 DATE 820618 820625 820630 820708 820725 820804 820820 820820 820825 DATE 820618 820625 820630 820725 820630 820725 820630	820618 7.73 820625 8.55 820630 820708 8.34 820725 8.32 820804 8.40 820810 8.50 820820 3.48 820825 3.48 DATE 30 820618 820625 8.29 820708 8.72 820725 8.29 820804 8.72 820810 820820 8.70 820825 DATE 30 820820 8.70 820825 820820 8.70 820825 820820 8.70 820820 8.70 820820 8.70 820820 8.70	DATE 30 45	DATE 30	DATE 30 45 60 90 820618 7.73 820625 8.55 8.55 820630 820708 8.34 8.32 8.50 7.37 7.60 820804 8.40 8.61 8.56 8.38 820810 8.50 8.34 8.45 8.42 8.20 820825 8.48 8.45 8.42 8.20 820825 8.48 8.45 8.42 8.20 820825 PH PLOT 35G DATE DEPTH (cm) 30 45 60 90 820618 820625 8.53 8.30 8.22 820630 820725 8.29 8.33 820725 8.29 7.98 7.30 820804 8.72 8.70 8.35 820810 8.70 8.70 8.70 8.51 8.80 820625 8.62 8.58 8.49 PH PLOT 35 DEPTH (cm) 30 45 60 90 820810 8.33 8.33 820625 8.29 7.98 7.30 8.35 820810 8.70 8.70 8.52 8.01 820825 PH PLOT 35 DATE DEPTH (cm) 30 45 60 90 820804 8.72 8.70 8.35 8.49 PH PLOT 35 PH PL	DATE 30

	T-P04 as P -	-mag	P	LOT 50A	1982	
DATE	30	45	·DEPTH(c	em) 90	120	150
820618 820625 820630 820708 820725 820804 820810 820820 820825	0.06 0.03 0.03 0.02 0.01 0.14 0.05		0.03 0.04 0.02 0.03 0.05 0.05	0.05 0.01 0.03 0.01 0.09	0.04 0.01 0.04 0.02 0.04 0.10	0.03 0.01 0.03 0.08
	T-PO4 as P -	-mag	F	от 50	1982	
DATE	30	45	DEPTH(c	em) 90	120	150
820618 820625 820630 820708 820725 820804 820810 820820 820825	0.13 0.02 0.12 0.01	0.22	0.04 0.02 0.02 0.02	0.04	0.01 0.05 0.04 0.01	0.09 0.01 0.02 0.02
	T-PO4 as P -	-mag	I	PLOT 35G	1982	
DATE	30	45	DEPTH(0	em) 90	120	150
820618 820625 820630 820708 820725 820804 820810 820820 820825		0.05	0.02	0.03	0.05 0.11 0.06 0.02 0.03	0.02 0.08 0.03 0.02 0.01 0.07 0.20 0.05

	T-PO4 as P	-maga-	P	LOT 35	1982	
DATE	30	45	DEPTH(c	m) 90	120	150
820618		0.13				
820625		0.01				
820630						
820708		0.01	0.70			
820725 820804		0.01				
820810						
820820						
820825						
	NH3 as N	-maa-	P	LOT 50A	1982	
0.3.00			D 77 D 77 / -	\		
DATE	30	45	DEPTH(c	m) 90	120	150
000610						
820618	1.20				0.60	0.00
820625 820630	0.20			0.39	0.14 2.31	0.90 0.51
820708	0.40		0.72	0.65	0.45	0.49
820725	0.22		0.23	0.18	0.10	0.10
820804	0.30		0.11			
820810	0.20		0.21	0.18	0.01	0.19
820820	0.70		0.01	0.11	0.05	
820825	0.20		0.09	0.11	0.05	
	NH3 as N	-mga-	P	LOT 50	1982	
DATE			DEPTH(c	m)		
	30	45	60	90	120	150
820618	0.06				0.53	0.02
820625	0.20			0.07	0.20	0.10
820630						
820708	0.21	1 20	0.24	0.58	0.46	0.56
820725	0.14	1.38 0.20	0.22	0.19	0.21	0.26
820804 820810	0.10 0.16	0.20	$0.01 \\ 0.04$	0.04 0.15	0.15	0.41
820820	0.16	0.19		0.20	0.15	0.50
820825	0.26	0.01	0.06	0.13	0.20	

	NH3 as N -	-ווממ-	P	LOT 35G	1932			
DATE		DEPIH (cm)						
DATE	30	45	60	90	120	150		
820618								
820625		0.60	0.50	4.00		0.09		
820630					0.30	J.71		
820703					0.44	0.93		
320725	0.13		0.33	0.33	0.15	0.14		
820804	0.30		0.15	0.19	0.06	0.04		
820810				0.16		0.08		
320820	J.30	0.80	0.01		0.30	0.14		
820825		J.20	0.09	0.04				
	NH3 as N -	- הממ	Р	LOT 35	1932			
DATE			DEPTH (c	m)				
	30	45	60	90	120	150		
820613		0.20						
820625		0.50	2.00					
820630								
820703		ാ.60	0.50					
820725	5.00	1.38	0.60		2.20			
820804		0.27	0.50					
820810		0.40						
820820	2.00	0.70	0.70		0.80			
820825			0.70					

Appendix D. Soil chemical characteristics 1980-1982. Data by treatments, depth, and sampling date for:

Exchangeable sodium

Exchangeable Sodium Percentage (ESP)

Cation Exchange Capacity

Exchangeable Magnesium

Exchangeable Calcium

Electrical Conductivity of Saturation Extract

pH of Saturated Soil Paste

Sodium Adsorption Ratio (SAR) of Soil Solution

Exchangeab.	1 e	Sodium.	ma/100a
DACHAHACAD.			me/ Tood

PLOT 50

DATE	SITE			DE	PTH(cm)			
		0-3	0-15	15-30	0-30	30-60	60-90	90-120
800519	1				0.8	0.4	0.3	0.3
800519	2				0.8	0.4	0.1	0.1
800519	3				0.9	0.4	0.1	0.1
801104	1				1.3	0.4	0.4	0.4
801104	2				1.5	0.8	0.6	0.2
801104	3				1.6	0.6	0.3	0.1
811009	1				2.0	1.1	1.4	0.8
811009	2				1.7	1.4	0.8	0.7
811009	3				1.8	1.6	0.9	0.3
820426	1		1.9	2.4				
820426	3		1.9	2.1				
820426	5		1.3	2.1				i
820426	6		2.2	2.2				
820911	1	1.3	1.7	1.7		1.6	1.7	2.2
820911	2	1.7	1.8	2.2		1.8	1.2	1.4

Exchangeable Sodium, me/100g

PLOT 35

DATE	SITE	0-3	0-15		PTH (cm) 0-30	30-60	60-90	90-120
			0 13	15 50	0 30	30-00		90-120
800519	1				0.7	0.2	0.1	0.1
800519	2				0.5	0.1	0.1	0.2
800519	3				0.4	0.2	0.3	0.5
801104	1					0.9	0.3	
801104	2				1.1	0.2	0.4	0.4
801104	3				1.6	0.4	0.7	0.8
811009	1				1.9	1.6		
811009	2				1.5	1.3	0.8	0.6
811009	3				1.7	1.4		
820426	1		1.7	2.2				
820426	3		1.5	2.1				
820426	5		1.9	2.1				
820426	6		1.8	2.1				
820911	1	1.2	1.6	1.7		1.8		
820911	2	1.3	1.5	1.8		1.6	1.9	1.0
020711	-		2.3	2.0		1.0	1.7	T.0

Exchai	ngeable	Sodium.me	/100a
LACHAI	INCOPTE	2 00 I um ,c	/ 1004

PLOT 35G

DATE	SITE			DE	PTH(cm)			
		0-3	0-15	15-30	0-30	30-60	60-90	90-120
800519	1				0.4	0.1	0.1	
800519	2				0.5	0.2	0.6	1.3
800519	3.				0.5	0.4	0.5	
801104	3						0.3	
811009	1				2.2	1.1	0.9	0.5
811009	2				2.0	1.4	0.7	0.4
811009	3				2.3	1.2	0.5	0.7
820426	1		1.6	2.0				
820426	3		1.7	2.4				
820426	4		1.7	2.2				
820426	5		1.4	2.2				
820911	1	0.8	1.7	1.8		1.8	1.9	1.2
820911	2	1.3	1.4	2.0		1.7	1.4	0.9

Exchangeable Sodium, me/100g

PLOT 20

DATE	SITE		0.15		PTH(cm)	20.60		00.100
		0-3	0-15	15-30	0-30	30-60	60-90	90-120
800519	1				0.3	0.1	0.2	0.5
800519	2	-			0.6	0.4	0.6	
800519	3				0.4	0.1		
801104	1				1.4	0.5	0.3	1.1
801104	2				1.7		0.6	1.1
						0.6		
801104	3					0.0		
811009	1				3.3	1.4	1.7	1.1
811009	2				3.3	1.5	1.5	
811009	3				2.9	1.5		
820426	1		2.3	2.7				
820426	3		2.5	2.6				
820911	1	0.8	1.5	2.6		1.6	0.9	0.8
820911	2	1.2	1.6	2.0		1.2	0.6	0.7

Exchangeable Sodium Percentage ESP

PLOT 50

DATE	SITE	E DEPTH(cm)							
		0-3	0-15	15-30	0-30	30-60	60-90	90-120	
800519	1				4.6	2.5	2.3	1.4	
800519	2				4.0	2.3	1.3	1.3	
800519	3	*******			5.4	2.2	1.0	0.7	
801104	1				7.7	4.4	3.4	2.3	
801104	2				8.3	7.4	4.1	1.4	
801104	3				7.4	4.4	4.9	1.5	
811009	1	-			12.0	8.3	13.2	4.7	
811009	2				9.0	10.5	6.5	6.0	
811009	3				9.7	10.5	11.0	3.7	
820426	1		7.9	11.3					
820426	3		9.0	10.8					
820426	5		3.1	11.5					
820426	6		10.1	10.7				~~~	
820911	1	6.1	7.5	9.0		9.4	10.3	12.8	
820911	2	7.6	7.9	11.3		10.6	7.5	8.1	

Exchangeable Sodium Percentage ESP

PLOT 35

DATE	SITE	DEPTH (cm)							
		0-3	0-15	15-30	0-30	30-60	60-90	90-120	
800519	1				3.6	1.1	0.4	0.6	
800519	2				3.5	0.4	0.6	1.2	
800519	3				2.1	1.0	2.4	3.7	
801104	1					5.9	2.3		
801104	2	-			5.5	1.5	2.5	2.4	
801104	3				9.1	2.3	6.0	4.5	
811009	1				9.6	10.8			
811009	2				8.4	8.9	6.3	4.3	
811009	3				9.6	8.1			
820426	1		9.0	11.3					
820426	3		3.2	10.1					
820426	5		9.0	10.3					
820426	6		9.1	10.7					
820911	1	5.5	7.6	8.0		10.0			
820911	2	6.1	7.1	8.3		3.8	15.8	7.0	

Exchangeable Sodium Percentage ESP

PLOT 35G

DATE	SITE			DE	PIH(cm)			
		0-3	0-15	15-30	0-30	30-60	60-90	90-120
800519	1				1.9	0.3	1.2	
800519	2	-			2.7	1.2	3.7	7.9
800519	3				2.1	1.9	3.0	
801104	3						1.6	
811009	1				11.9	6.7	10.0	5.3
811009	2				10.1	7.9	4.3	2.6
811009	3		-		11.0	6.0	3.1	4.8
820426	1		7.7	10.1				
820426	3		7.5	10.3				
820426	4		7.6	10.5				
820426	5		6.7	10.8				
820911	1	3.0	8.2	8.5		9.3	10.9	9.1
820911	2	5.1	6.7	9.5	-	8.5	7.7	7.0

Exchangeable Sodium Percentage ESP

PLOT 20

SITE			DEI	PTH(cm)			
	0-3	0-15	15-30	0-30	30-60	60-90	91-120
•							
1				1.7	0.8	1.7	3.4
2				2.5	2.2	4.0	
3				1.9	0.4		
1				6.7	3.4	2.9	8.1
2						5.0	
3					3.3		
1				16.6	9.5	13.7	8.1
2				14.9	7.7	10.3	
3				15.6	6.9		
1			11.9				
3		11.6	10.6				
1	3.3	6.5	11.5		8.6	6.1	5.7
-							5.0
	1 2 3 1 2 3 1 2 3	1 2 3 1 2 3 1 2 3 1 2 3 1 3 3 3	1 1 2 3 1 2 3 1 10.4 3 11.6	1 1 2 3 1 2 1 2 3 1 10.4 11.9 3 11.6 10.6	0-3 0-15 15-30 0-30 1 1.7 2 2.5 3 1.9 1 6.7 2 6.7 2 16.6 2 14.9 3 15.6 1 10.4 11.9 1 1.6 10.6 1 3.3 6.5 11.5	0-3 0-15 15-30 0-30 30-60 1 1.7 0.8 2 2.5 2.2 3 1.9 0.4 1 6.7 3.4 2 3.3 1 3.3 1 16.6 9.5 2 14.9 7.7 3 15.6 6.9 1 10.4 11.9 1 1.6 10.6 3.6	0-3

Cation	Exch	Capacity	(CEC)	me/100q

PLOT 50

DATE	SITE			DE	PTH (cm)			
		0-3	0-15		0-30	30-60	60-90	90-120
800519	1				16.8	16.8	11.5	18.2
800519	2				19.9	15.8	9.4	10.4
800519	3				15.7	17.2	9.9	9.1
801104	1				17.0	9.8	10.3	17.4
801104	2				16.9	10.9	14.8	12.2
801104	3				21.2	13.0	6.3	9.1
811009	1				16.9	13.3	10.9	17.8
811009	2				18.4	13.4	12.1	11.3
811009	3				18.4	15.1	8.1	9.1
820426	1		23.6	21.2				
820426	3		20.5	19.4				
820426	5		21.8	18.2				
820426	6		21.8	21.0				
820911	1	22.0	22.2	19.3		16.9	16.0	17.5
820911	2	22.0	22.2	19.3		17.0	16.0	17.5

Cation Exch Capacity(CEC), me/100g

PLOT 35

DATE	SITE			DEI	PTH (cm)			
		0-3	0-15	15-30	0-30	30-60	60-90	90-120
800519	1				19.7	15.4	13.3	14.6
800519	2				14.2	13.3	10.1	12.7
800519	3				18.5	16.3	11.9	14.5
801104	1					14.7	11.7	
801104	2				20.5	14.9	15.3	17.0
801104	3				17.0	16.9	11.3	17.1
811009	1				19.7	15.1		
811009	2				17.3	14.1	12.7	14.8
811009	3				17.7	16.6		
820426	1		19.3	19.5				
820426	3		18.7	20.5				
820426	5		21.2	19.4				
820426	6		19.7	20.0				
820911	1	21.0	21.5	21.3		17.7		
820911	2	21.0	21.5	21.3		17.7	12.0	13.9

Chemical soil analysis 1980-1982

Exchangeable Magnesium, me/100g PLOT 35G

DATE	SITE			DEI	PTH (cm)			
		0-3	0-15	15-30	0-30	30-60	60-90	90-120
800519	1				4.6	5.7	3.4	
800519	2				4.5	6.4	10.0	13.6
800519	3				5.1	6.6	9.2	
801104	3				ana ara ana		7.8	
820426	1		4.0	4.2				
820426	3		4.3	4.0				
820426	4		4.4	4.4				
820426	5		4.3	4.6				
820911 820911	1 2	4.6 5.8	6.1 5.7	6.9 4.1		7.8 4.3	9.6 7.9	11.4 8.0

Exchangeable Magnesium, me/100g

PLOT 20

DATE	SITE	0-3	0-15	DE1	PTH(cm) 0-30	30-60	60-90	90-120
800519 800519 800519	1 2 3				5.6 5.5 4.8	9.8 4.9 4.9	9.7 14.3	13.7
801104 801104 801104	1 2 3				6.8	10.9	4.0 13.6	13.8
820426 820426	1 3		5.4 4.9	5.5 5.3				
820911 820911	1 2	6.0 6.9	5.1 5.9	4.0		5.3 5.4	11.2	14.2

Exchangeable	Magnesium.	me/100a
L'ACHAIIG EADIE	may he stull!	me/IOOA

PLOT 50

DATE	SITE			DEI	PTH (cm)			
		0-3	0-15	15-30	0-30	30-60	60-90	90-120
800519	1				4.4	4.6	8.1	17.2
800519	2				3.3	1.9	2.7	6.8
800519	3				3.7	5.5	4.1	4.4
801104	1				4.3	4.7	5.7	17.0
801104	2				4.7	3.9	6.7	10.4
801104	3				4.0	3.6	2.9	5.7
820426	1		6.3	6.7				
820426	3		5.1	4.9				
820426	5		5.0	4.3				
820426	6		5.0	4.6				
820911	1	5.4	3.8	4.2		3.7	4.9	9.0
820911	2	6.5	4.7	2.8		2.6	2.6	6.8

Exchangeable Magnesium, me/100g

PLOT 35

DATE	SITE	0-3	0-15	DE E	PTH (cm) 0-30	30-60	60-90	90-120
800519 800519 800519	1 2 3				3.3 2.9 5.4	4.8 2.7 6.6	6.9 3.7 6.4	8.3 4.4 12.0
801104 801104 801104	1 2 3				6.2 4.5	4.6 9.0 10.7	9.2 12.3 10.8	12.1
820426 820426 820426 820426	1 3 5 6		4.6 5.2 4.9 4.1	5.1 4.4 4.2 4.4	===			===
820911 820911	1 2	6.4 7.3	4.7 5.7	4.0 5.5		4.8 5.6	8.6	13.2

Cation Exch Capacity(CEC), me/10	Cation	Exch	Capacity	(CEC)	, me	/100a
----------------------------------	--------	------	----------	-------	------	-------

PLOT 35G

DATE	SITE			DEI	PTH (cm)			
		0-3	0-15		0-30	30-60	60-90	90-120
800519	1				18.3	17.0	9.3	
800519	2				19.4	18.1	15.5	16.2
800519	3				21.1	20.2	15.8	
801104	3						16.8	
811009	1				18.3	17.0	9.3	8.5
811009	2				19.4	18.1	15.5	16.2
811009	3				21.1	20.2	15.8	14.0
820426	1		20.5	19.5				
820426	3		22.8	22.7				
820426	4	-	21.6	20.9				
820426	5		20.6	20.0				
820911	1	25.2	21.0	20.8		19.6	17.8	12.9
820911	2	25.0	21.0	20.8		19.6	17.8	12.9

Cation Exch Capacity(CEC), me/100g

PLOT 20

DATE	SITE			DEI	PTH(cm)			
		0-3	0-15	15-30	0-30	30-60	60-90	90-120
800519	1				19.0	15.8	13.4	13.7
800519	2				22.2	18.9	14.8	
800519	3				18.4	22.3		
801104	1				21.2	13.5	11.1	14.1
801104	2						12.0	
801104	3					17.6		
811009	1				20.1	14.7	12.2	13.9
811009	2				22.2	18.9	14.8	
811009	3				18.4	22.3		
820426	1		21.7	23.0				
820426	3		21.6	24.1				
820911	1	24.6	22.4	23.0		19.0	14.0	13.5
820911	2	24.6	22.4	23.0	-	19.0	14.0	13.5

Chemical soil analysis 1980-1982

	Exchangeable	Calcium,	me/100g	PLOT	50
--	--------------	----------	---------	------	----

DATE	SITE	0-3	0-15	DE1	PTH (cm) 0-30	30-60	60-90	90-120
800519 800519 800519	1 2 3				14.2 14.0 20.2	42.7 18.5 21.9	47.2 43.5 31.8	43.0 44.3 26.6
801104 801104 801104	1 2 3				17.2 14.6 18.6	41.2 25.4 36.6	37.5 46.0 38.6	47.4 40.7 33.0
820426 820426 820426 820426	1 3 5 6		16.1 15.3 12.5 14.7	18.7 14.5 12.3 15.8		===		
820911 820911	1 2	15.7 15.1	12.8 15.6	18.3 10.8		35.6 32.5	45.3 41.8	42.3 47.1

Exchangeable Calcium, me/100g

PLOT 3	15

DATE	SITE	0-3	0-15	DE I	PTH(cm) 0-30	30-60	60-90	90-120
800519 800519 800519	1 2 3				15.4 12.5 24.1	42.3 13.4 48.4	42.8 42.1 47.3	35.4 32.5 47.6
801104 801104 801104	1 2 3				42.2 15.1	45.3 62.6 47.1	39.6 69.5 55.2	44.9 52.0
820426 820426 820426 820426	1 3 5 6	00 00 00 00 00 00 00 00 00	14.9 13.5 15.7 12.9	17.4 14.5 15.2 14.9				
820911 820911	1 2	17.7 16.1	15.6 14.8	25.2 18.5		43.3	46.9	45.0

Chemical soil analysis 1980-1982

Exchangeable	Calcium,	me/100q	PLOT	35G

DATE	SITE			DEI	PTH (cm)			
		0 - 3	0-15	15-30	0-30	30-60	60-90	90-120
800519	1				34.3	29.9	31.3	
800519	2				18.4	62.0	58.6	127.3
800519	3				19.3	58.0	59.9	
801104	3						22.4	
820426	1		13.5	14.7				
820426	3							320
	_		15.6	14.4				
820426	4	-	17.5	17.2				
820426	5		18.1	18.6				
820911	1	22.0	17.1	19.6		4.4	47.0	42.1
820911	2	20.1	19.9	24.1		41.4	45.8	51.2

Exchangeable Calcium, me/100g PLOT

20

DATE	SITE	0-3	0-15	DEI	PTH(cm) 0-30	30-60	60-90	90-120
800519 800519 800519	1 2 3				20.2 23.6 18.7	55.9 44.2 19.0	46.1 59.2	47.7
801104 801104 801104	1 2 3				39.5	48.0 42.0	36.3 44.5	39.9
8 20 4 2 6 8 20 4 2 6	1 3		15.2 11.9	15.2 14.8				
820 9 11 820 9 11	1 2	16.9 17.9	17.2 16.9	18.4 16.3		46.3 44.4	43.9 47.8	46.4 42.2

	EC	of of	Sat Ext	ract, us	S/cm		PLOT 5	0
DATE	SITE	0-3	0-15	DE1	PTH(cm) 0-30	30-60	60-90	90-120
800519 800519 800519	1 2 3				1291 1229 1422	1003 827 776	853 853 872	790 940 821
801104 801104 801104	1 2 3				1782 1782 2075	1489 1306 1416	1349 1440 1233	1098 1147 1294
811009 811009	1 2				2097 1575	2435 1650	1823 3358	2435 1748
811009 820426 820426	3 1 2		2016 2240	2240 2744	2102	2809	1650 	2919
820426 820426 820426 820426	3 4 5 6		1736 1497 1542 1815	1055 1293 1411 1730				
820911 820911	1 2	2037 2767	1652 2019	1 21 1 20 37		1432 2030	1211 1927	1520 1817
	E	c of	Sat Ext	ract, us	S/cm		PLOT 2	0
DATE	SITE	0-3	0-15	DE:	PTH(cm) 0-30	30-60	60-90	90-120
800519 800519 800519	1 2 3				785 1379 716	617 804 1132	492 5138	2416
801104 801104 801104	1 2 3				2148	1428 1477	2288 3204 	3783
811009 811009 811009	1 2 3				3179 2988 3306	3688 3306 4578	2098 2416 	1169
820426 820426 820426 820426	1 2 3 4		1804 1775 1513 1804	1804 1443 2909 2211				
820911 820911	1	562 595	980 595	694 1057		1652 1652	1982 3304	5286 4626

EC of Sat Extract, uS/cm PLOT 35G

	E/	01	Sat Ext	ract, us	5/CIII		FPOI 33	G
DATE	SITE	0-3	0-15		OTH (cm)	30-60	60-90	90-120
800519	1				1079	741	399	
800519	2				1344	669	4027	8332
800519	3				1277	556	1577	
801104	3		***				1684	
811009	1				3433	2990	3051	3306
811009	2				3688	4451	2098	5023
811009	3				4578	3306	3560	5099
820426	1		2688	2128				
820426	2		2912	2408				
820426	3		3472	2800				
820426	4		2632	2240				
820426	5		3024	1848	3			
820426	6		1792	1523				
820911	1	1432	1630	1410		1652	2423	2643
820911	2	1253	1769	2200		1656	2183	4367
	E	C of	Sat Ext	ract, us	S/cm		PLOT 3	5
D)	a t ma			P.0.1	OTILL (or)			
DATE	SITE	0 - 3	0 -15	15 _ 20	PTH(cm)	20-60	60-00	00 120

DATE	SITE			DE	PTH(cm)			
		0-3	0-15	15-30	0-30	30-60	60-90	90-120
800519	1				1329	1010	8 9 5	869
800519	2				1344	984	933	882
800519	3				2103	1203	535	368
801104	1					2209	1965	
801104	2				1495	3753	4271	5004
801104	3				1892	1324	4515	5370
811009	1				3014	4393		
811009	2				2438	2480	2798	5086
811009	3			-,	2543	3306		
820426	1		1270	1316				
820426	2		1470	1327				
820426	3		1746	1117				
820426	4		1513	977				
820426	5		1629	1327				
820426	6		1804	1920				
820911	1	826	1145	1338		1586		
820911	2 .	980	1652	1476		1356	1927	2836

pH of Saturated Soil Paste PLOT 50

DATE	SITE			DE	PTH(cm)			
		0-3	0-15	15-30	0-30	30-60	60-90	90-120
800519	1				6.9	7.7	8.1	8.1
800519	2				6.6	7.4	8.0	8.1
800519	3				7.5	8.2	8.1	8.1
801104	1				7.0	7.6	7.8	7.8
801104	2				6.9	7.5	7.6	7.7
801104	3				6.8	7.5	7.7	7.8
811009	1				7.1	7.5	8.0	7.7
811009	2				7.2	7.4	7.3	7.7
811009	3	***			7.3	7.5	7.3	7.8
820426	1		6.3	6.3				
820426	2		6.8	7.3				
820426	3		7. 0	6.7				
820426	4		7.8	6.8				
820426	5		6.6	6.7				
820426	6		6.4	6.2				
820911	1	7.1	7.2	7.3		7.6	7.8	7.8
820911	2	7.4	7.2	7.4		7.7	8.1	7.9

pH of Saturated Soil Paste PLOT 20

DATE	SITE			DEF	TH(cm)			
		0-3	0-15	15-30	0-30	30-60	60-90	90-120
800519	1				7.0	7.7	8.0	7.7
800519	2				7.4	7.6	7.9	
800519	3				6.5	6 .6		
801104	1				7.5	7.8	7.5	3.0
801104	2						7.3	
801104	3					7.4		,
811009	1				7.6	3.0	7.9	8.0
811009	2				7.0	7.8	7.8	
811009	3				7.1	7.0		
820426	1		6.7	6.2				
820426	2		5.8	6.9				
820426	3		6.7	6.0				
820426	4		6.6	6.3				
820911	1	6.8	7.2	7.4		7.6	7.8	7.6
820911	2 .	7.4	7.4	7.3		7.6	7.7	7.7

pH of Saturated Soil Paste PLOT 35G

DATE	SITE			DE	PTH (cm)			
		0-3	0-15	15-30	0-30	30-60	60-90	90-120
800519	1				7.1	7.0	7.5	
800519	2				6.9	7.5	8.3	7.9
800519	3				6.9	7.4	7.9	
801104	3						7.6	
811009	1				7.3	7.4	7.6	7.8
811009	2				7.3	7.6	7.7	7.7
811009	3				6.8	7.2	7.6	7.8
820426	1		6.6	6.0			-,	
820426	2		6.6	6.0				
820426	3	~~ ~~	6.6	6.3				
820426	4		6.4	5.8				
820426	5		6.9	7.0				
820426	6		7.2	6.4				
820911	1	7.4	7.1	7.1		7.6	7.7	7.8
820911	2	7.6	7.3	7.3		7.8	7.6	7.7

pH of Saturated Soil Paste PLOT 35

DATE	SITE		0.15		PTH (cm)	20.60	60.00	02 120
		0-3	0-12	15-30	0-30	30-60	60-90	90-120
800519	1				7.2	7.7	8.1	8.5
800519	2				6.7	7.3	8.0	7.1
800519	3				6.9	7.5	7.5	8.0
801104	1					7.6	7.5	
801104	2				7.4	7.5	7.6	7.6
801104	3				7.1	7.7	7.7	7.7
001104	3				,	, • ,	, . ,	, . ,
811009	1				7.5	7.5		
811009	2				7.4	7.5	7.7	7.6
811009	3				7.2	7.4		~~-
820426	1		6.5	7.1				
820426	2		6.7	6.2				
820426	3		6.6	6.9				
820426	4		6.7	7.3				
820426	5		6.7	6.6				
820426	6		6.7	6.3				
000013	,	7.6	7 7	7 5		7.0		
820911	1		7.3	7.5		7.9		
820911	2	7.5	7.1	7.4		7.3	7.9	7.8

SAR of Soil Solution PLOT 50

DATE	SITE		0-15	DEP 15-30	TH(cm) 0-30	30-60	60-90	90-120
800519	1				2.6	0.3		
800519 800519	2				3.7 3.5	0.6 0.7	0.5 0.3	0.2 0.4
	,							
801104	1				4.7	2.6	1.5	0.7
801104	2	-	-		4.6	3.7	1.4	0.4
801104	3				5.8	2.6	0.9	0.4
811009	1				6.8	7.3	5.4	4.3
811009	2				7.3	7.9	3.3	2.4
811009	3				9.7	8.5	5.2	6.1
820426	1		6.3	7.0				
820426	2		6.2	7.2				
820426	3		5.4	6.6				
820426	4		6.7	7.1				
820426	5		5.4	5.3				
820426	6		7.3	7.8				
020420	0		1.3	7.0				
820911	1	4.6	4.9	5.9		5.8	4.9	5.1
820911	2	6.6	6.4	7.6		8.4	7.6	4.9

SAR of Soil Solution

PLOT 20

DATE	SITE	0-3	0-15		O-30	30-60	60-90	90-120
800519	1				1.2	0.4	0.8	1.6
800519	2				2.2	1.0	2.1	
800519	3				0.7	1.9		
001104	,				2 5	2 2	2 2	
801104	1				3.5	0.3	0.8	2.5
801104	2						1.0	
801104	3		***			0.5		
811009	1				5.9	2.6	0.8	2.2
811009	2				6.8	1.4	1.9	
811009	3				5.9	2.8		
820426	1		6.5	7.3				
820426	2		5.6	7.5				
820426	3		5.8	8.0				
820426	4		6.7	7.3				
000011	,	2 1	7 0	5 0				
820911	1	2.1	7.8	5.0		5.2	2.7	1.2
820911	2 -	2.4	4.6	7.4		5.3	1.5	1.7

SAR	Ωf	Soil	SOI	lu+i/	n.
JAK	OI	2011	30		

PLOT 35G

DATE	SITE	0-3	0-15	DEI 15-30	PTH (cm) 0-30	30-60	60-90	90-120
800519 800519 800519	1 2 3				1.3 1.5 1.9	0.4 0.3 0.4	0.8 0.7 1.6	2.4
801104	3						0.5	
811009 811009 811009 820426 820426 820426 820426 820426	1 2 3 1 2 3 4 5		5.0 5.7 5.9 5.9	6.7 6.8 7.6 6.8	5.9 6.7 7.8	6.9 5.0 4.0	3.2 5.8 1.5	1.0 1.0 0.8
820426 820911 820911	6 1 2	3.9 4.0	5.4 4.4 4.9	5.6 4.9 6.7		5.6 6.6	4.6	3.5 2.9

SAR of Soil Solution

PLOT 35

DATE	SITE			DE	PTH(cm)			
	_	0-3	0-15	15-30	0-30	30-60	60-90	90-120
800519	1				3.1	0.7	0.3	0.4
800519	2				2.6	0.4	0.4	0.4
800519	3				1.4	0.3	0.4	0.7
801104	1					2.1	0.9	***
801104	2				4.1	0.7	0.9	1.7
801104	3				4.5	1.0	1.0	1.6
811009	1				8.4	8.6		
811009	2				6.9	5.3	2.7	0.8
811009	3			***	8.1	5.3		
820426	1		5.6	7.4				
820426	2		6.8	7.8				
820426	3		4.9	5.7				
820426	4		5.7	4.8				
820426	5		6.4	6.9				
820426	6		6.5	7.6				
820911	1	3.1	4.6	6.9		8.3		
820911	2 .	4.1	6.2	7.2		7.1	4.9	2.3

Chemical soil analysis 1980-1982

Cation Exch (Capacity(CEC), me/100g	PLOT 20G
---------------	------------------------	----------

DATE	SITE	2	DEPTH (cm)						
		0-3	0-15	15-30	0-30	30-60	60-90	90-120	
820426	1	****	23.4	18.6					
820426	2		21.6	19.6					
820911	1	24.5	22.4	22.9		15.1	14.7	18.2	
820911	2	24.6	22.4	22.9		15.1	14.7	18.2	

Exchangeable Sodium, me/100g

PLOT 20G

DATE	SITE	E DEPTH(cm)							
		0-3	0-15	15-30	0-30	30-60	60-90	90-120	
000406	,		1 7						
820426	T		1.7	2.1					
820426	2	-	2.3	1.9					
820911	1	0.8	1.3	1.7		1.2	1.3	1.0	
820911	2	0.8	1.5	2.8		1.7	0.7	1.0	

Exchangeable Magnesium, me/100g

PLOT 20G

DATE	SITE	DEPTH (cm)							
		0-3	0-15	15-30	0-30	30-60	60-90	90-120	
820426	1		5.4	4.5					
820426	2		5.5	3.5					
820911	1	5.1	2.9	4.9		4.9	7.2	14.9	
820911	2	3.9	4.5	4.6		6.6	11.9	14.2	

Exchangeable Calcium, me/100g

PLOT 20G

DATE	SITE			DEF	TH(cm)			
		0-3	0-15	15-30	0-30	30-60	60-90	90-120
	1		17.2					
820911	1	23.7	12.7	15.7		42.3	40.4	37.1
820911	2	20.3	18.1	16.5		42.8	48.5	45.0

Chemical soil analysis 1980-1982

		Ch	nemical	soil an	alysis	1980-19	82	
	E	C of	Sat Ext	tract, u	3/cm		PLOT 20)G
DATE	SITE			DE	PTH(cm)			
		0-3	0-15	15-30	0-30	30-60	60-90	90-120
820426	1		1676.0	1303.0 1684.0				
820426	2		1222.0	1684.0				
820911	1 1	586.0	1432.0	1211.0		1762.0	1735.0	1927.0
820911	2 2	093.0	1520.0	1927.0		2753.0	3634.0	6718.0
	Ηợ	of Sa	aturated	d Soil P	aste		PLOT 20)G
DATE	SITE			DE	PTH(cm)			
22	0213	0 - 3	0-15	15-30	0-30	30-60	60-90	90-120
820426	1		7.0	6.4 6.3	(\$ 22	
820426	2		6.9	6.3				
820911	1	7.1	6.9	6.9 7.0		6.9	7.7	7.8
820911	2	7.3	7.1	7.0		7.6	7.7	7.8
		S	AR of S	oil Solu	tion		PLOT 20)G
DATE	SITE			DE	PTH(cm)			
22				DE 15-30			60-90	90-120
820426				7.6 7.7				
820426	2		7.2	7.7				
820911	1	1.7	2.9	4.7		4.5	4.2	1.8
820911	2	2.5	4.4	7.7		4.5	1.0	2.1
Evaha	ngoah	ala sa	dium De	rcentage	. FSD		PLOT 2	0.0
Excila	ngear)1e 30	arum re				101 2	00
DATE	SITE		0-15	DE 15-30	PTH(cm)		60-20	90-120
		0-3			0-30			
820426				11.1 9.3				*** *** ***
820426	2						************	
820911		3.2	5.6 6.6	7.3 12.3		8.1		
820911	2	3.0	0.0	12.3		11.0	4.6	5.7

Appendix E. James River water quality data 1980-1982. This river supplies the town of Huron with water. (Taken from U.S.G.S. Water Quality Records 1979-1982.)

JAMES RIVER WATER QUALITY 1980-1982

DATE	EC uS/cm	Ca nom	Mg maa	%Na	SAR	Alk(T) as CaCO3	304 maa	C1 ppm	NO3+NO2 as N	Tot PO4
800331	830	68	30	31.0	1.6	220	180	25	0.01	0.16
800430	710	57	26	35.0	1.8	160	170	40	0.02	0.20
800528	970	78	38	32.0	1.8	270	190	39	0.04	0.28
800701	940	69	33	33.0	1.8	230	210	43	0.12	0.20
801229	1720	92	64	43.0	3.5	340	380	120	0.06	0.18
810123	1480	120	66	40.0	3.3	400	390	110	0.00	0.12
810224	1320	76	42	45.0	3.2	250	280	110	0.00	0.11
810323	1540	92	51	42.0	3.1	300	320	110	0.00	0.15
810504	1560	95	57	43.0	3.4	330	400	96	0.00	0.30
810803	1320	79	56	46.0	4.3	320	350	110	0.23	0.69
020226	700	.	27	27 0	2 2	160	100	2.0	1 20	0 55
820226	700	52	27	37.0	2.2	160	180	38	1.30	0.55
820518	690	50	23	35.0	1.9	210	110	30	0.00	0.46
820611	69 0	53	25	33.0	1.7	222	100	26	0.00	0.32
820727	890	65	33	35.0	2.2	322	130	36	0.00	0.26
820903	966	70	38	36.0	2.4	302	160	50	0.56	0.21
820930	970	74	38	36.0	2.4	332	150	36	0.00	0.31
821101	960	62	35	37.0	2.4	290	180	33	0.15	0.21

Appendix F. Secondary-treated municipal effluent water quality at Huron 1980-1982. Samples were taken from the irrigation nozzles as the water was pumped from the last stage of the lagoon.

Electrical Conductivity
Sodium Adsorption Ratio
Adjusted Sodium Adsorption Ratio
Calcium
Magnesium
Sodium
Potassium
Chloride
Sulfate
Bicarbonate
Carbonate
Nitrate
Total Kjeldahl Nitrogen
Total Phosphate
pH

Huron's Secondary-Treated Effluent Water Quality 1980-1982

DATE	EC uS/cm	SAR*	ASAR+	Ca ppm	Mg Mg	Na ppm	Б.БШ К	ppm Cl	SO4 ppm	bow HCO3	CO3	ивси mgg	TKN ppm	Hq 4 09- T mqq
800513	1543	5.0	13.2	88	38	222	24	220	210	473	14	0.3	24.4	5.2 8.2
800523	1880	5.1	13.5	97	52	249	31	255	250	546	0	0.1	23.0	6.3 7.5
800710	1753	5.4	13.5	61	5 6	243	38	265	257	250	91	0.2	4.5	0.5 8.4
300722	1974	5.5	13.1	63	48	235	40	285	270	227	67	0.1	3.4	1.1 9.2
300731	2129	6.2	15.2	92	41	283	39	320	292	264	58	0.1	5.0	1.2 8.8
800813	2183	6.1	15.4	96	50	295	42	300	315	249	77	0.1	3.7	1.3 8.9
800911	2300	6.1	15.5	92	68	315	37	308	370	342	34	0.1	6.1	1.3 8.3
800925	2400	6.1	15.5	100	60	313	39	312	325	365	23	0.1	3.4	0.9 8.3
800930	2250	5.9	15.0	102	61	306	36	305	395	398	0	0.1	5.1	1.8 8.2
801007	260 0	5.2	13.4	88	77	278	42	320	415	28 8	58	6.5	8.6	1.2 8.4
810430	1916	5.8	14.9	96	72	305	42	350	425	274	72	1.1	3.3	2.8 8.8
810519	2300	6.0		136	48	321	45	388	475	378	0	0.2	10.4	1.6 8.1
810501	2800	6.4		112	58	334	45	380	404	464	0	0.7	12.9	3.6 7.5
810612	2700	6.9	18.2		62	366	48	390	500	500	0	0.1	15.8	3.1 7.5
810619	2396	8.1	21.1		65	430	46	405	530	488	0	0.2	16.8	2.2 7.5
810701	2150	8.0		112	48	400	44	415	624	366	0	4.5	6.4	1.1 8.0
810706	2500	8.3	18.0	88	62	415	38	415	550	195	0	0.4	4.2	1.9 7.4
810714	2600	8.4	20.7	112	43	410	41	425	620	354	24	0.1	6.6	1.2 8.3
810721	2500	7.9		112	62	420	42	445	600	305	24	0.2	7.2	1.2 8.5
810311	2748	11.7	28.2		43	560	39	450	640	390	0	0.2	9.3	1.6 8.1
810818	2900	9.2		112	46	460	36	440	570	403	0	0.2	6.7	1.5 8.2
810903	2900	10.6	25.3	96	48	510	44	430	570	356	0	0.1	7.4	1.2 8.0
810917	3000	8.5	21.1	96	72	450	52	530	506	36 6	0	0.2	6.3	0.9 8.0
811008	2800	9.7	22.4	128	31	470	49	490	530	293	0	0.0	7.7	0.6 7.8

Huron's Secondary-Treated Effluent Water Quality 1980-1982

DATE	EC uS/cm	SAR*	ASAR+	Ca ppm	Mg mag	Na ppm	ωσα K	bbw C1	SO4 mga	ECOH mag	CO3	маа маа	TKN	T-PO4 pH
820603 820524	2050 2000	5.6 4.5	14.1	98 104	43 58	265 229	29 34	270 270	369 344	425 295	0 14	0.2	23.8	5.1 7.8 0.3 8.3
820630 820707 820723	2150 2100 2100	5.1 6.4 6.4	12.4 15.6 15.3	96 90 81	58 48 43	254 303 285	32 36 34	272 280 300	344 365 350	332 361 371	0 0 0	1.1 2.6 0.1	8.3 3.7 8.6	2.3 7.9 4.3 7.6 3.7 7.8
820804 820810 820820	2256 2453 2048	5.6 5.8 5.5	13.4 14.0 14.0	101 86 96	55 53 67	282 276 287	39 49 13	280 245 292	357 375 425	220 329 342	36 12 24	10.5 3.7 11.5	6.2 3.8 9.3	3.4 8.6 3.0 8.4 1.5 8.4
820826 820907	2050 2400	5.5 6.5		103	58 63	28 2 3 4 4	22 39	265 310	469 500	354 315	0 30	12.4	17.6 3.1	3.8 8.5 5.6 8.6

^{*=}Sodium Adsorption Ratio

NO3N= Nitrates as Nitrogen

⁺⁼Adjusted Sodium Adsorption Ratio

T-PO4 = Total Phosphates as P

Appendix G. Plot observation well water quality data 1981-1982.

Electrical Conductivity
Sodium
Chloride
Bicarbonate
Nitrate
NH3
Total Phosphate
pH

PLOT OBSERVATION WELL WATER QUALITY 1981-1982

PL	ОТ	20
PL	OT	20

×	DATE	EC us/cm	SAR*	ASAR+	Ca mod	Mg mga	Na ppm	K K	Cl ppm	SO4 mgg	HCO3	800 mag	маа И EON	EHK	T-PO4 pH ppm
	801104	3100	0.0	0.0	0	0	206	0	82	0	64	0	0.0	1.4	0.0 7.7
	810527	3300	1.3	5.4	440	204	130	26	90	2085	395	0	0.0	0.0	0.1 7.8
	810504	3900	1.5	4.8	560	204	153	25	100	2070	532	0	0.0	0.0	0.0 7.5
	310629	3300	0.0	0.0	0	0	184	0	210	0	525	0	0.1	2.0	0.0 7.4
	810715	3500	0.0	0.0	0	0	227	0	112	0	525	0	0.1	2.0	0.1 7.6
	810805	4000	0.0	0.0	0	0	173	0	110	0	525	0	0.1	3.0	0.2 7.6
	810812	3800	0.0	0.0	0	0	180	0	75	0	525	0	0.1	2.6	0.1 7.8
	810819	3900	0.0	0.0	0	0	194	0	69	0	561	0	0.1	2.6	0.0 7.2
	810917	3900	0.0	0.0	0	0	136	0		0	425	0	0.0	2.2	0.0 7.6
	811007	3300	0.0	0.0	0	0	156	0	115	0	476	0	0.1	3.2	0.1 7.4
	820503	3 500	0.0	0.0	0	0	152	0	61	0	761	0	0.1	13.5	1.5 7.7
	820825	3000	2.3	. 7.2	480	162	230	0	80	2035	488	0	0.7	30.0	0.1 8.0
	PLOT	50													
		EC	SAR*	ASAR+	Ca	Mg	Na	K	Cl	SO4	нсо3	C03	NO3N	ин3	T-P34 pH
	DATE	uS/cm	2723.0	.15.11	mgg	ppm	שממ	הממ	mag	mää	màd 1	mag	mag	mgg	mad
	801104	3100	0.0	0.0	0	0	123	0	10	0	364	56	7.2	0.0	0.0 8.2
	810527	3300	1.0	3.0	376		119	8	142	2600	283	0	0.0	0.0	0.1 7.8
	810604	3400	1.1	3.3	340	360	125	14		2420	295	0	0.0	0.0	0.3 7.4
	810715	3600	0.0	0.0	0	0	98	0	95	0	317	0	0.3	0.6	0.1 7.8
	810805	4200	0.0	0.0	0	0	90	0	43	0	336	0	0.2	1.2	0.1 7.5
	810812	4300	0.0	0.0	0	0	112	0	470	0	231	0	0.2	1.5	0.0 7.7
	810917	4100	0.0	0.0	0	0	75	0	0	0	281	22	0.1	0.4	0.9 8.2
	811007	4500	0.0	0.0	0	0	151	0	120	0	305	0	0.2	0.6	0.0 7.8
	820603	3500	0.0	0.0	0	0	70	0	235	0	266	0	0.3	1.4	0.1 7.8
	820630 820825	3700 3500	0.0	0.0	0 36 0	0 50 4	80 125	0	20	0 2370	222 195	0	0.5	0.0	0.2 7.7 0.0 8.4
	オノロガノカー	1000	VIDE CONTRACTOR	4.7	704	J U!3	1/7	0	410	43/U	エフン	U	1.5	U - 4	U.U.X.4

PLOT 35G

DATE	EC uS/cm	SAR*	ASAR+	Ca ppm	Mg Mg	Na ppm	maga K	Cl ppm	\$04 ppm	HCO3	bbw CO3	mgg NO3N	NH3	T-PO4 pH ppm
301104	9700	0.0	0.0	0	0	670	0	312	0	120	20	4.0	0.0	0.0 8.2
810527	8500	2.1	7.0	470	1674	423	32	290	9000	405	0	3.0	0.0	0.1 7.7
810604	9900	2.7	9.1	540	1644	550	31	295	L 7 350	405	0	2.0	0.0	0.0 7.3
810629	10500	0.0	0.0	0	0	360	0	610	U	449	0	7.1	0.0	0.0 7.1
810715	12200	0.0	0.0	0	0	780	0	300	0	454	0	3.3	0.2	0.2 7.1
810305	12200	0.0	0.0	0	0	467	0	340	0	482	0	4.6	0.0	0.0 7.3
810812	12200	0.0	0.0	0	0	7 90	0	380	0	3 90	78	4.1	0.2	0.0 8.2
810819	12900	0.0	0.0	0	0	8 90	0	425	0	598	0	3.7	0.2	0.1 7.2
810917	12267	0.0	0.0	0	0	1040	0	0	0	351	91	3.3	0.1	0.2 8.5
811007		0.0	0.0	0	0	760	0	412	0	390	84	4.7	0.1	0.0 3.3
820603		0.0	0.0	0	0	600	0	292	0	481	0	0.1	3.0	0.2 7.7
820325	8500	2.5	8.3	500	1944	55 0	0	450	9675	244	24	2.8	0.0	0.1 8.4
PLOT	35													
	5.0	G 3 5 4	1010.	•	14			61	204		a aa	***		
D \$ (DD)	EC	SAR	ASAR+	Ca	Ma	Na	K	Cl	S04	HCO3	CO3	NO3N	NH3	T-PO4 pH
DATE	uS/cm			mga	mgg	waa	mag	ppm	mgg_	ppm	mad	mgg	mqg	māā
801104	4500	0.0	0.0	0	0	211	0	25	0	240	0	2.3	0.0	0.0 7.7
810527	4000	1.8	5.4	440	450	2 20	13	160	3000	303	22	4.0	0.0	0.2 8.2
810604	4400	2.0	6.2	700	318	2 55	19	165	2850	354	0	5.0	0.0	0.2 7.7
810529	4500	0.0	0.0	0	. 0	195	0	240	0	346	0	7.4	0.0	0.0 7.3
810715	4500	0.0	0.0	0	0	354	0	115	0	329	0	7.4	0.4	0.0 7.3
810905	5300	0.0	0.0	0	0	206	0	190	0	366	0	10.1	0.0	0.0 7.6
810912	5200	0.0	0.0	0	0	198	0	102	0	268	0	9.0	0.0	0.0 7.8
810319	5200	0.0	0.0	0	0	169	0	106	0	366	0	6.4	0.2	0.0 7.4
810917	4870	0.0	0.0	0	0	180	0	0	0	278	10	9.3	0.0	0.0 8.2
811007	4700	0.0	0.0	0	0	223	0	155	0	293	12	9.6	0.0	0.0 8.1
820603	4700	0.0	0.0	0	0	162	0	945	0	307	0	9.6	0.0	0.0 7.9
820325	3800	1.2	3.4	720	504	168	0	100	4120	195	0	7.2	0.0	0.1 8.3

Appendix H. Dry matter yields of alfalfa by treatment, replication, year, and cutting.

Table H1. Yield of alfalfa plots 1980 kg/ha (tons/acre) dry matter.

					Cutti	ngs			
Treatment	Site				2		3		4.
Plot 50	ì.	3212	(1.43)	1505	(0.07)	2361	(1.00)	-	()
1100 30	2	2514	(1.03)	016	(0.31)	2710	$(1.\overline{21})$	-	()
	3	1932	(0.00)	1757	(0.50)	2905	(1.32)	-	()
Plot 35G	ì	2051	(1.10)	1752	(0.78)	3655	(1.30)	-	()
. 100 330	2	2471	(1.10)	1004	(0.03)	2943	(1.31)	-	()
	3	2449	(1.09)	2224	(0.99)	2920	(1.30)	-	()
Plot 35	1	2336	(1.04)	1730	(Ů.77)	25&3	(1.15)	_	()
riot 33	2	2426	(1.04)	1040	(0.73)	ع أو أو أو	(1.12)	-	i i
	3	2561	(1.14)	1483	(0.60)	2808	(1.25)	-	()
Plot 20	1 2	1932 1820	(0.86) (0.81)	1864 1662	(0.83) (0.74)	2673 2718	(1.13) (1.21)	Ξ	()
	3	2022	(0.90)	2201	(0.90)	2291	(1.02)	-	()
20 (gypsum)	1		() ()	-	()	-	() ()	-	()
	٤	-	()	-	()	-	()	-	(
Check	ì	ن 7 <i>4</i>	(6.36)	1011	(0.45)	o51	(∀.∠∀)	_	()
a	1 2 3	7-1	(ŭ.33)	1309	(0.35)	1280	(0.57)	-	(
	3	2224	(0.99)	1303	(U.Su)	1250	(0.50)	-	(

Table H2. Yield of alfalfa plots 1981 kg/ha (tons/acre) dry matter.

					Cutt	ings			,
Treatment	Site		1		2		3		4
Plot 50	1 2 3	2958 2330 3122	(1.33) (1.25) (1.37)	2965 2965 3437	(1.30) (1.32) (1.53)	3145 2471 2785	(1.40) (1.10) (1.24)	1932 1864 1775	(0.00) (0.83) (0.79)
Plot 35G	1 2 3	1730 2181 2330	(0.77) (1.06) (1.04)	3325 2943 2291	(1.48) (1.31) (1.62)	2628 2608 2508 2588	(1.17) (1.25) (1.33)	1999 2330 1757	(0.89) (1.04) (0.60)
Plot 35	1 2 3	2356 2036 2336	(1.29) (1.20) (1.04)	3145 3260 2943	(1.40) (1.46) (1.31)	3100 3347 2943	(1.36) (1.49) (1.31)	1842 1820 2044	(0.02) (0.01) (0.91)
Plot 20	1 2 3	1752 1820 1752	(0.78) (0.81) (0.76)	2008 2516 2763	(1.25) (1.12) (1.23)	2353 2600 2763	(1.27) (1.16) (1.23)	1572 1842 1820	(0.70) (0.62) (0.81)
20 (gypsum)	1 2 3	Ξ	() () ()	=	()	-	() () ()	=	() ()
Check	1 2 3	=	() () ()	=	() ()	=	() ()	=	() ()

Table H3. Yield of alfalfa plots 1982 kg/ha (tons/acre) dry matter.

•					Cutt	ings			
Treatment	Site				2	3			4
Plot 50	1 2	3257 3729	(1.45) (1.56)	3122 2853	(1.39) (1.27)	2561 1662	(1.14) (0.74)	1752 2201	(0.76) (0.98)
	3	3190	(1.42)	2361	(1.00)	2808	(1.25)	1854	(0.83)
Plot 35G	1	3122	(1.39)	307ა	(1.37)	2075	(1.28)	2291	(1.02)
	3	3235 3402	(1.44) (1.55)	2308 2314	(1.25) (1.03)	2763 3033	(1.23) (1.35)	2500 2044	(1.16) (0.91)
Plot 35	1	3235	(1.44)	3145	(1.40)	2538	(1.13)	2112	(0.94)
	3	3664 3459	(1.54) (1.54)	2404 2404	(1.07) (1.07)	2426 2561	(1.08) (1.14)	199 9 2875	(0.89) (1.26)
Plot 20	1	3190	(1.42)	2336	(1.64)	2501	(1.14)	2259	(1.01)
	3	3370 3370	(1.50) (1.50)	3122 2765	(1.39) (1.24)	25 28 2331	(1.17) (1.06)	2157 1887	(0.96) (0.84)
20 (~~~)	,		,	2261	0.33	22.1	(1.36)	1000	1011
20 (gypsum.)	1 2 3	-	()	2201 2301 2600	(0.93) (1.03) (1.16)	2361 2718 2246	(1.05) (1.21) (1.00)	1820 2471 2201	(0.81) (1.10) (0.98)
Check	1 2	1191 1595	(0.53) (0.71)	1415 809	(0.63) (0.36)	741 1213	(0.33) (0.54)	_	()
	3	1909	(0.71)	719	(0.30)	1050	(0.34)	_	()

Appendix I. Rainfall and irrigation frequency and amounts, Huron, S.D. 1980-1982.

Table II. Rainfall and irrigation dates and amounts (cm).

		may	1980					June	1980		
ate	Rainfall		Irriga	tion		Date	Rainfall		Irriga	tion	
		50	35G	35	20			50	35G	35	20
1						1					
2						2	0.25 1.88				
4						3	0.13				
5						5	1.09				
6						6	1.09				
7						7					
8						8					
9	0.03					9					
LO	0.46					10					
11						11	2.18				
12	0.53					12		2.62	2.72	5.77	2.7
13		12.70	12.70	12.70	12.70	13					
14						14	0.05				
15						15	0.05				
16						16		1.80	2.82	1.80	2.8
17						17					
18 19		0.14	9.14	0 12	0 12	18 19					
20		9.14	9.14	0.13	6.13	20		1 27	1 70	1.27	1 3
21						21	2.24	1.27	1.70	1.27	1.
22						22	2.24				
23						23	0.15				
24				-		24	4.37				
25	0.13					25	0.03				
26	0.03					26					
27						27					
28	0.18	5.84	4.32	3.56	2.03	28					
29	1.30					29					
30 31	0.46 1.07					30					

		July	1980					August	1980		
Date	Rainfall		Irriga	tion		Date	Rainfall		Irriga		
		50	35G	35	20			50	35G	35	20
1						1					
2	2.29	5.08	4.57	3.56	3.05	1 2					
3	0.08					· 3					
4	4.19					4					
5 6 7 8 9	0.30					5	0.08	5.59	4.01	4.06	2.44
6						6	0.03				
7	0.20					7 8	0.41				
8						8	1.12	5.18	3.66	3.66	2.13
9						9	3.30				
10		5.33	3.91	3.81	2.39	10					
11						11					
12	0.46					12	0.23				
13					•	13		7.87	5.33	5.33	3.05
14	0.18					14	0.81				
15						15	1.78				
16	0.10					16					
17						17	1.35				
18	0.30					18	0.58				
19	0.05					19	0.13				
20	*****					20	0.23				
21						21	0.08				
22		7 62	5.33	5.33	3 05	22	0.00	9 22	5.69		2 20
23		7.02	3.33	3.33	3.03	23		0.23	3.09	3.09	3.28
24						24	0.08				
25		4 65	3 66	3.38	2 30	25	0.00				
26		4.03	3.00	3.30	2.39	26					
27						27					
28						28					
29						29					
30						30	0.03				
31	0.03	6.91	4 37	5.08	2.54	31	0.03				
21		0.71	7.3/	J. 00	4.37	31					

Table I2. Rainfall and irrigation dates and amounts (cm).

September 1980						October 1980					
Date	Rainfall		Irriga			Date			Irriga	tion	
		50	35G	35	20			50	35G	35	20
1						1	0.03				
2						2					
3						3					
4						4					
5 6						5 6					
7						7		3 86	2.72	2 72	1 57
8						8		3.00	2.72	2.72	1.57
9	0.51					9					
10						10					
11	0.41	8.56	5.66	5.66	3.05	11					
12	0.05					12					
13						13					
14						14	0.30				
15	0.05					15	1.35				
16		8.00	5.66	5.66	3.15	16	0.23				
17						17	0.03				
18 19						18 19					
20	0.23					20					
21	0.23					21					
22						22					
23	0.10					23					
24						24					
25		5.23	3.71	3.71	2.18	25					
26						26	0.38				
27						27					
28						28					
29						29					
30		4.04	2.90	2.90	1.60	30 31					

		мау	1981			June 1981						
Date	Rainfall		Irriga	tion		Date	Rainfall		Irriga	tion		
		50	35G	35	20			50	35G	35	20	
1 2 3 4	0.05					1 2 3 4	0.74	6.45	4.47	4.47	2.59	
5 6 7 8 9		7.62	5.84	5.84	3.45	5 6 7	0.81					
10						8 9 10	0.03 0.46	5.13	3.86	3.86	2.92	
11 12 13 14	0.05	6.83	4.50	4.50	2.34	11 12 13 14	0.13 0.03 0.03 0.28	2.26	1.24	1.24		
15 16 17 18	0.43					15 16 17 18	0.03					
19 20 21 22	0.03	8.41	5.87	5.87	3.56	19 20 21 22	0.05 0.41	6.58	4.67	4.67	2.77	
23 24 25	0.03 0.76 0.10 0.03					23 24 25	0.23					
26 27 28 29	0.28					26 27 28 29	0.03 0.36 0.18	9.83	6.78	6.78	3.05	
30 31						30						

Table I3. Rainfall and irrigation dates and amounts (cm).

		July						August	1981		
ate	Rainfall		Irriga	tion		Date			Irriga	tion	
		50	35G	35	20			50	35G	35	20
1						1	7.32				
2						2	0.74				
3						3	1.42				
4						4					
5 6						5 6					
6		8.23	5.87	5.87	3.58	6					
7						7					
8						8					
9						9					
0						10					
1						11		7.57	5.28	5.28	3.0
.2	0.10					12 13					
. . 4	0.10	7 07	5.59	5 50	2 20	14	0.91				
5	0.13	7.87	3.39	3.39	3.30	15	0.91				
6						16					
7						17					
8						18		7.75	5.46	5.46	3.1
9						19		5	3	3	٠
0						20					
1	0.41	7.92	5.33	5.33	3.05	21					
2	1.85					22					
23	0.13					23	0.91				
2.4	0.25					24					
25	0.41					25	0.15				
26	0.58					26	0.30	4.93	3.40	3.40	1.8
27	0.20					27					
28						28					
29						29					
30						30					
31						31					

	Set	otember	1981					Oc tober	1981		
Date	Rainfall		Irriga	tion		Date			Irriga	tion	
		50	3 5G	35	20			50	35G	35	20
1						1 2					
2						2					
1 2 3 4						3	0.43				
						4					
5 6 7						5	1.40				
6						6					
						7					
8						8					
9						9	0.15				
10						10					
11						11	0.00				
12						12	0.03				
13 14	0.20					13 14	1.02				
15	0.03					15	0.03				
16	0.03					16	1.52				
17		5 44	3.66	3.66	2 21	17	1.32				
18		3	3.00	3		18					
19						19					
20						20					
21						21					
22						22					
23	0.25					23					
24	0.08					24	0.03				
25						25					
26	0.08					26					
27						27					
28						28					
29		5.08	3.56	3.56	2.03	29					
30						30					
						31					

Table I4. Rainfall and irrigation dates and amounts (cm).

ate	Rainfall				June 1982						
		Irriga			Date	Rainfall		Irriga	tion		
		35G	35	20			50	35G	35	20	
1	•	 			1						
2					2						
3					3						
4					4						
5					5						
6					6	0.76					
7					7						
8					8	0.51	6.05	3.20	3.20		
9	0.74				9						
10	1.14				10						
11	1.93				11	0.10					
12	0.71				12						
13	1.12				13 14	0.50			•		
14 15	0.61 0.18				15	0.58					
16	0.10				16	0.76					
17	0.03				17	0.05	3 58	1 91	1 91		
18	0.03				18	0.03	3.30	,.	/-		
19					19						
20	0.13				20						
21	0.15				21						
22					22						
23					23						
24	0.18				24	0.13	6.02	2.46	2.46	4.1	
25	1.45				25						
26	0.69				26						
27					27						
28	0.05				28						
29	0.25				29	0 20	0			, ,	
30 31	2.18				30	0.28	0.00	6.38	6.38	1.6	
		 									
		 1982					August				

		July	1982			August 1982					
Date	Rainfall		Irriga	tion		Date	Rainfall		Irriga	tion	
		50	35G	35	20			50	35G	35	20
1 2 3 4	0.30					1 2 3 4	0.25	5.97	4.14	4.14	
2 3 4 5 6 7 8 9	0.56	3.78	2.64	2.64		5 6 7 8 9					
10 11 12 13		0.50	1 05			10 11 12		7.62	5.33	5.33	9.14
14 15 16 17	0.86 3.58	9.36	1.85	1.85	5.59	13 14 15 16 17					
18 19 20 21	0.10 2.29 0.03					18 19 20 21		7.65	5.31	5.31	
22 23 24	0.00	3.18	0.79	0.79		22 23 24	0.33 0.74 0.58				
25 26 27 28	0.08 4.57 0.58	2.18	2.18	2.18		25 26 27 28		5.31	3.38	3.38	
29 30 31						29 30 31	0.74 0.99 3.61				

Table I5. Rainfall and irrigation dates and amounts (cm).

September 1982

	56	prember	1902		
Date	Rainfall		Irriga	tion	
		50	35G	35	20
1 2 3 4 5 6 7		3.71	2.18	2.18	
8 9 10	0.23	5.08	3.56	3.56	6.20
11 12 13 14	2.13 2.13				
15 16 17 18 19 20 21	0.58				
22 23 24 25 26 27 28 29					
30	0.36				